



## 1 Identification

- **Product identifier**
- **Trade name:** 19403 GM Olympic White WA8624
- **Article number:** 19403
- **Application of the substance / the mixture** Coating

## 2 Hazard(s) identification

- **Classification of the substance or mixture**



GHS02 GHS04 Flame, Gas cylinder

Flam. Aerosol 1 H222 Extremely flammable aerosol.



GHS04 Gas cylinder

Press. Gas H280 Contains gas under pressure; may explode if heated.



GHS08 Health hazard

Carc. 2 H351 Suspected of causing cancer.

Repr. 2 H361 Suspected of damaging fertility or the unborn child.

STOT RE 2 H373 May cause damage to organs through prolonged or repeated exposure.



GHS07

Eye Irrit. 2A H319 Causes serious eye irritation.

STOT SE 3 H336 May cause drowsiness or dizziness.

- **Label elements**

- **GHS label elements** The product is classified and labeled according to the Globally Harmonized System (GHS).

(Contd. on page 2)



Printing date 06/28/2017

Reviewed on 06/28/2017

Trade name: 19403 GM Olympic White WA8624

(Contd. of page 1)

· Hazard pictograms



GHS02 GHS04 GHS07 GHS08

· Signal word *Danger*

· Hazard-determining components of labeling:

acetone  
4-methylpentan-2-one  
toluene  
n-butyl acetate

· Hazard statements

H222 Extremely flammable aerosol.  
H280 Contains gas under pressure; may explode if heated.  
H319 Causes serious eye irritation.  
H351 Suspected of causing cancer.  
H361 Suspected of damaging fertility or the unborn child.  
H336 May cause drowsiness or dizziness.  
H373 May cause damage to organs through prolonged or repeated exposure.

· Precautionary statements

P201 Obtain special instructions before use.  
P202 Do not handle until all safety precautions have been read and understood.  
P210 Keep away from heat/sparks/open flames/hot surfaces. No smoking.  
P211 Do not spray on an open flame or other ignition source.  
P251 Do not pierce or burn, even after use.  
P260 Do not breathe dust/fume/gas/mist/vapors/spray.  
P264 Wash thoroughly after handling.  
P271 Use only outdoors or in a well-ventilated area.  
P280 Wear protective gloves/protective clothing/eye protection/face protection.  
P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.  
P305+P351+P338 If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.  
P308+P313 IF exposed or concerned: Get medical advice/attention.  
P312 Call a POISON CENTER/doctor if you feel unwell.  
P314 Get medical advice/attention if you feel unwell.  
P337+P313 If eye irritation persists: Get medical advice/attention.  
P403+P233 Store in a well-ventilated place. Keep container tightly closed.  
P405 Store locked up.  
P410+P403 Protect from sunlight. Store in a well-ventilated place.  
P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F.  
P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

· Classification system:

· NFPA ratings (scale 0 - 4)



Health = 1  
Fire = 4  
Reactivity = 3

(Contd. on page 3)



Printing date 06/28/2017

Reviewed on 06/28/2017

Trade name: 19403 GM Olympic White WA8624

(Contd. of page 2)

· **HMIS-ratings (scale 0 - 4)**

HEALTH	1	Health = *1
FIRE	4	Fire = 4
REACTIVITY	3	Reactivity = 3

- **Other hazards**
- **Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.

**3 Composition/information on ingredients**

- **Chemical characterization: Mixtures**
- **Description:**  
Mixture: consisting of the following components.  
Weight percentages

· **Dangerous components:**

67-64-1	acetone	30 - 40%
68476-86-8	Petroleum gases, liquefied, sweetened	13 - 30%
123-86-4	n-butyl acetate	5 - 7%
108-10-1	4-methylpentan-2-one	5 - 7%
110-19-0	isobutyl acetate	5 - 7%
763-69-9	ethyl 3-ethoxypropionate	1.5 - 5%
108-88-3	toluene	1.5 - 5%
110-43-0	heptan-2-one	1-1.5%

**4 First-aid measures**

- **Description of first aid measures**
- **After inhalation:** Supply fresh air; consult doctor in case of complaints.
- **After skin contact:** Generally the product does not irritate the skin.
- **After eye contact:**  
Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.
- **After swallowing:** If symptoms persist consult doctor.
- **Information for doctor:**
- **Most important symptoms and effects, both acute and delayed** No further relevant information available.
- **Indication of any immediate medical attention and special treatment needed**  
No further relevant information available.

**5 Fire-fighting measures**

- **Extinguishing media**
- **Suitable extinguishing agents:**  
CO<sub>2</sub>, extinguishing powder or water spray. Fight larger fires with water spray or alcohol resistant foam.
- **Special hazards arising from the substance or mixture** No further relevant information available.

(Contd. on page 4)



Printing date 06/28/2017

Reviewed on 06/28/2017

Trade name: 19403 GM Olympic White WA8624

(Contd. of page 3)

- **Advice for firefighters**
- **Protective equipment:** Wear self-contained respiratory protective device.

## 6 Accidental release measures

- **Personal precautions, protective equipment and emergency procedures**  
Wear protective equipment. Keep unprotected persons away.
- **Environmental precautions:** Do not allow to enter sewers/ surface or ground water.
- **Methods and material for containment and cleaning up:**  
Dispose contaminated material as waste according to item 13.  
Ensure adequate ventilation.
- **Reference to other sections**  
See Section 7 for information on safe handling.  
See Section 8 for information on personal protection equipment.  
See Section 13 for disposal information.
- **Protective Action Criteria for Chemicals**

### · PAC-1:

67-64-1	acetone	200 ppm
123-86-4	n-butyl acetate	5 ppm
108-10-1	4-methylpentan-2-one	75 ppm
13463-67-7	titanium dioxide	30 mg/m <sup>3</sup>
110-19-0	isobutyl acetate	450 ppm
763-69-9	ethyl 3-ethoxypropionate	1.6 ppm
108-88-3	toluene	67 ppm
110-43-0	heptan-2-one	150 ppm
1330-20-7	xylene	130 ppm
100-41-4	ethylbenzene	33 ppm
108-83-8	2,6-dimethylheptan-4-one	75 ppm
1333-86-4	Carbon black	9 mg/m <sup>3</sup>
57-55-6	Methyl glycol	30 mg/m <sup>3</sup>
78-83-1	butanol	150 ppm
108-65-6	2-methoxy-1-methylethyl acetate	50 ppm
21645-51-2	aluminium hydroxide	8.7 mg/m <sup>3</sup>
7631-86-9	silicon dioxide, chemically prepared	18 mg/m <sup>3</sup>
95-63-6	1,2,4-trimethylbenzene	140 ppm

### · PAC-2:

67-64-1	acetone	3200* ppm
123-86-4	n-butyl acetate	200 ppm
108-10-1	4-methylpentan-2-one	500 ppm
13463-67-7	titanium dioxide	330 mg/m <sup>3</sup>
110-19-0	isobutyl acetate	1300* ppm
763-69-9	ethyl 3-ethoxypropionate	18 ppm
108-88-3	toluene	560 ppm
110-43-0	heptan-2-one	670 ppm

(Contd. on page 5)



Printing date 06/28/2017

Reviewed on 06/28/2017

Trade name: 19403 GM Olympic White WA8624

(Contd. of page 4)

1330-20-7	xylene	920* ppm
100-41-4	ethylbenzene	1100* ppm
108-83-8	2,6-dimethylheptan-4-one	330 ppm
1333-86-4	Carbon black	99 mg/m <sup>3</sup>
57-55-6	Methyl glycol	1,300 mg/m <sup>3</sup>
78-83-1	butanol	1,300 ppm
108-65-6	2-methoxy-1-methylethyl acetate	1,000 ppm
21645-51-2	aluminium hydroxide	73 mg/m <sup>3</sup>
7631-86-9	silicon dioxide, chemically prepared	740 mg/m <sup>3</sup>
95-63-6	1,2,4-trimethylbenzene	360 ppm

· PAC-3:

67-64-1	acetone	5700* ppm
123-86-4	n-butyl acetate	3000* ppm
108-10-1	4-methylpentan-2-one	3000* ppm
13463-67-7	titanium dioxide	2,000 mg/m <sup>3</sup>
110-19-0	isobutyl acetate	7500** ppm
763-69-9	ethyl 3-ethoxypropionate	110 ppm
108-88-3	toluene	3700* ppm
110-43-0	heptan-2-one	4000* ppm
1330-20-7	xylene	2500* ppm
100-41-4	ethylbenzene	1800* ppm
108-83-8	2,6-dimethylheptan-4-one	2000* ppm
1333-86-4	Carbon black	590 mg/m <sup>3</sup>
57-55-6	Methyl glycol	7,900 mg/m <sup>3</sup>
78-83-1	butanol	8000* ppm
108-65-6	2-methoxy-1-methylethyl acetate	5000* ppm
21645-51-2	aluminium hydroxide	440 mg/m <sup>3</sup>
7631-86-9	silicon dioxide, chemically prepared	4,500 mg/m <sup>3</sup>
95-63-6	1,2,4-trimethylbenzene	480 ppm

**7 Handling and storage**

· **Handling:**

· **Precautions for safe handling** No special measures required.

· **Information about protection against explosions and fires:**

Do not spray on a naked flame or any incandescent material.  
Keep ignition sources away - Do not smoke.

Pressurized container: protect from sunlight and do not expose to temperatures exceeding 50 °C, i.e. electric lights. Do not pierce or burn, even after use.

· **Conditions for safe storage, including any incompatibilities**

· **Storage:**

· **Requirements to be met by storerooms and receptacles:**

Observe official regulations on storing packagings with pressurized containers.

· **Information about storage in one common storage facility:** Store away from oxidizing agents.

(Contd. on page 6)



Printing date 06/28/2017

Reviewed on 06/28/2017

Trade name: 19403 GM Olympic White WA8624

(Contd. of page 5)

- **Further information about storage conditions:** Keep receptacle tightly sealed.
- **Specific end use(s)** No further relevant information available.

## 8 Exposure controls/personal protection

- **Additional information about design of technical systems:** No further data; see item 7.
- **Control parameters**
- **Components with limit values that require monitoring at the workplace:**  
The following constituents are the only constituents of the product which have a PEL, TLV or other recommended exposure limit.  
At this time, the other constituents have no known exposure limits.

### 67-64-1 acetone

PEL	Long-term value: 2400 mg/m <sup>3</sup> , 1000 ppm
REL	Long-term value: 590 mg/m <sup>3</sup> , 250 ppm
TLV	Short-term value: 1187 mg/m <sup>3</sup> , 500 ppm
	Long-term value: 594 mg/m <sup>3</sup> , 250 ppm
	BEI

### 123-86-4 n-butyl acetate

PEL	Long-term value: 710 mg/m <sup>3</sup> , 150 ppm
REL	Long-term value: 950 mg/m <sup>3</sup> , 200 ppm
TLV	Short-term value: 712 mg/m <sup>3</sup> , 150 ppm
	Long-term value: 238 mg/m <sup>3</sup> , 50 ppm

### 108-10-1 4-methylpentan-2-one

PEL	Long-term value: 410 mg/m <sup>3</sup> , 100 ppm
REL	Short-term value: 300 mg/m <sup>3</sup> , 75 ppm
	Long-term value: 205 mg/m <sup>3</sup> , 50 ppm
TLV	Short-term value: 307 mg/m <sup>3</sup> , 75 ppm
	Long-term value: 82 mg/m <sup>3</sup> , 20 ppm
	BEI

### 110-19-0 isobutyl acetate

PEL	Long-term value: 700 mg/m <sup>3</sup> , 150 ppm
REL	Long-term value: 700 mg/m <sup>3</sup> , 150 ppm
TLV	Short-term value: 172 mg/m <sup>3</sup> , 150 ppm
	Long-term value: 238 mg/m <sup>3</sup> , 50 ppm

### 108-88-3 toluene

PEL	Long-term value: 200 ppm
	Ceiling limit value: 300; 500* ppm
	*10-min peak per 8-hr shift
REL	Short-term value: 560 mg/m <sup>3</sup> , 150 ppm
	Long-term value: 375 mg/m <sup>3</sup> , 100 ppm
TLV	Long-term value: 75 mg/m <sup>3</sup> , 20 ppm
	BEI

### 110-43-0 heptan-2-one

PEL	Long-term value: 465 mg/m <sup>3</sup> , 100 ppm
REL	Long-term value: 465 mg/m <sup>3</sup> , 100 ppm

(Contd. on page 7)



Printing date 06/28/2017

Reviewed on 06/28/2017

Trade name: 19403 GM Olympic White WA8624

(Contd. of page 6)

TLV Long-term value: 233 mg/m<sup>3</sup>, 50 ppm

**Ingredients with biological limit values:**

**67-64-1 acetone**

BEI 50 mg/L  
Medium: urine  
Time: end of shift  
Parameter: Acetone (nonspecific)

**108-10-1 4-methylpentan-2-one**

BEI 1 mg/L  
Medium: urine  
Time: end of shift  
Parameter: MIBK

**108-88-3 toluene**

BEI 0.02 mg/L  
Medium: blood  
Time: prior to last shift of workweek  
Parameter: Toluene

0.03 mg/L  
Medium: urine  
Time: end of shift  
Parameter: Toluene

0.3 mg/g creatinine  
Medium: urine  
Time: end of shift  
Parameter: o-Cresol with hydrolysis (background)

**Additional information:** The lists that were valid during the creation were used as basis.

**Exposure controls**

**Personal protective equipment:**

**General protective and hygienic measures:**

- Keep away from foodstuffs, beverages and feed.
- Immediately remove all soiled and contaminated clothing.
- Wash hands before breaks and at the end of work.
- Store protective clothing separately.
- Avoid contact with the eyes.
- Avoid contact with the eyes and skin.

**Breathing equipment:**

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use respiratory protective device that is independent of circulating air.

**Protection of hands:**

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

(Contd. on page 8)





Printing date 06/28/2017

Reviewed on 06/28/2017

Trade name: 19403 GM Olympic White WA8624

(Contd. of page 7)

· **Material of gloves**

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· **Penetration time of glove material**

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· **Eye protection:**

Safety glasses



Tightly sealed goggles

**9 Physical and chemical properties**

· **Information on basic physical and chemical properties**

· **General Information**

· **Appearance:**

Form:	Aerosol
Color:	White
Odor:	Characteristic
Odor threshold:	Not determined.

· **pH-value:** Not determined.

· **Change in condition**

Melting point/Melting range:	Undetermined.
Boiling point/Boiling range:	55 °C

· **Flash point:** -103 °C

· **Flammability (solid, gaseous):** Not applicable.

· **Ignition temperature:** 370 °C

· **Decomposition temperature:** Not determined.

· **Auto igniting:** Product is not selfigniting.

· **Danger of explosion:** In use, may form flammable/explosive vapour-air mixture.  
Avoid high heat

· **Explosion limits:**

Lower:	1.9 Vol %
Upper:	13.0 Vol %

· **Vapor pressure at 20 °C:** 233 hPa

Density at 20 °C:	0.761 g/cm <sup>3</sup>
Relative density	Not determined.
Vapor density	Not determined.
Evaporation rate	Not applicable.

· **Solubility in / Miscibility with**

Water: Not miscible or difficult to mix.

(Contd. on page 9)





Printing date 06/28/2017

Reviewed on 06/28/2017

Trade name: 19403 GM Olympic White WA8624

(Contd. of page 8)

- **Partition coefficient (n-octanol/water):** Not determined.
- **Viscosity:**
  - Dynamic:** Not determined.
  - Kinematic:** Not determined.
- **Solvent content:**
  - Organic solvents:** 88.8 %
  - VOC content:** 50.9 %
  - 609.5 g/l / 5.09 lb/gl
- **Solids content:** 11.2 %
- **Other information** No further relevant information available.

## 10 Stability and reactivity

- **Reactivity** No further relevant information available.
- **Chemical stability**
- **Thermal decomposition / conditions to be avoided:** No decomposition if used according to specifications.
- **Possibility of hazardous reactions** No dangerous reactions known.
- **Conditions to avoid** No further relevant information available.
- **Incompatible materials:** No further relevant information available.
- **Hazardous decomposition products:**
  - Nitrogen oxides
  - Hydrocarbons
  - Carbon monoxide and carbon dioxide

## 11 Toxicological information

- **Information on toxicological effects**
- **Acute toxicity:**
- **Primary irritant effect:**
  - **on the skin:** No irritant effect.
  - **on the eye:** Irritating effect.
- **Sensitization:** No sensitizing effects known.
- **Additional toxicological information:**
  - The product shows the following dangers according to internally approved calculation methods for preparations:
  - Irritant
- **Carcinogenic categories**

· IARC (International Agency for Research on Cancer)		
108-10-1	4-methylpentan-2-one	2B
13463-67-7	titanium dioxide	2B
108-88-3	toluene	3
	BENTONITE	suspected carcinogen <2% 14808-60-7
1330-20-7	xylene	3
100-41-4	ethylbenzene	2B
1333-86-4	Carbon black	2B

(Contd. on page 10)



Printing date 06/28/2017

Reviewed on 06/28/2017

Trade name: 19403 GM Olympic White WA8624

(Contd. of page 9)

7631-86-9 silicon dioxide, chemically prepared

3

· **NTP (National Toxicology Program)**

None of the ingredients is listed.

· **OSHA-Ca (Occupational Safety & Health Administration)**

None of the ingredients is listed.

**12 Ecological information**

· **Toxicity**

- **Aquatic toxicity:** No further relevant information available.
- **Persistence and degradability** No further relevant information available.
- **Behavior in environmental systems:**
- **Bioaccumulative potential** No further relevant information available.
- **Mobility in soil** No further relevant information available.

· **Additional ecological information:**

· **General notes:**

Water hazard class 3 (Self-assessment): extremely hazardous for water  
Do not allow product to reach ground water, water course or sewage system, even in small quantities.  
Danger to drinking water if even extremely small quantities leak into the ground.

· **Results of PBT and vPvB assessment**

- **PBT:** Not applicable.
- **vPvB:** Not applicable.
- **Other adverse effects** No further relevant information available.

**13 Disposal considerations**

· **Waste treatment methods**

· **Recommendation:**

Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

· **Uncleaned packagings:**

- **Recommendation:** Disposal must be made according to official regulations.

**14 Transport information**

· **UN-Number**

· **DOT, ADR, IMDG, IATA** UN1950

· **UN proper shipping name**

· **DOT** Aerosols, flammable  
· **ADR** 1950 Aerosols  
· **IMDG** AEROSOLS  
· **IATA** AEROSOLS, flammable

(Contd. on page 11)



Trade name: 19403 GM Olympic White WA8624

(Contd. of page 10)

· **Transport hazard class(es)**

· **DOT**



· **Class** 2.1  
· **Label** 2.1

· **ADR**



· **Class** 2 5F Gases  
· **Label** 2.1

· **IMDG, IATA**



· **Class** 2.1  
· **Label** 2.1

· **Packing group**  
· **DOT, ADR, IMDG, IATA** Void

· **Environmental hazards:**  
· **Marine pollutant:** No

· **Special precautions for user** Warning: Gases  
· **EMS Number:** F-D,S-U  
· **Stowage Code** SW1 Protected from sources of heat.  
SW22 For AEROSOLS with a maximum capacity of 1 litre: Category A. For AEROSOLS with a capacity above 1 litre: Category B. For WASTE AEROSOLS: Category C, Clear of living quarters.  
· **Segregation Code** SG69 For AEROSOLS with a maximum capacity of 1 litre: Segregation as for class 9. Stow "separated from" class 1 except for division 1.4. For AEROSOLS with a capacity above 1 litre: Segregation as for the appropriate subdivision of class 2. For WASTE AEROSOLS: Segregation as for the appropriate subdivision of class 2.

· **Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code** Not applicable.

(Contd. on page 12)



Printing date 06/28/2017

Reviewed on 06/28/2017

Trade name: 19403 GM Olympic White WA8624

(Contd. of page 11)

· **Transport/Additional information:**

· **DOT**

· **Quantity limitations**

On passenger aircraft/rail: 75 kg

On cargo aircraft only: 150 kg

· **ADR**

· **Excepted quantities (EQ)**

Code: E0

Not permitted as Excepted Quantity

· **IMDG**

· **Limited quantities (LQ)**

1L

· **Excepted quantities (EQ)**

Code: E0

Not permitted as Excepted Quantity

· **UN "Model Regulation":**

UN 1950 AEROSOLS, 2.1

**15 Regulatory information**

· **Safety, health and environmental regulations/legislation specific for the substance or mixture**

· **Sara**

· **Section 355 (extremely hazardous substances):**

None of the ingredient is listed.

· **Section 313 (Specific toxic chemical listings):**

108-10-1	4-methylpentan-2-one
	Acrylic Resin
108-88-3	toluene
1330-20-7	xylene
100-41-4	ethylbenzene
95-63-6	1,2,4-trimethylbenzene
147-14-8	Phthalocyanine Blue

· **TSCA (Toxic Substances Control Act):**

67-64-1	acetone
123-86-4	n-butyl acetate
108-10-1	4-methylpentan-2-one
13463-67-7	titanium dioxide
110-19-0	isobutyl acetate
763-69-9	ethyl 3-ethoxypropionate
108-88-3	toluene
9004-36-8	Cellulose Acetate Butyrate
110-43-0	heptan-2-one
16883-83-3	benzyl 3-isobutyryloxy-1-isopropyl-2-2-dimethylpropyl phthalate
1330-20-7	xylene
41556-26-7	bis(1,2,2,6,6-Pentamethyl-4-piperidinyl) sebacate
100-41-4	ethylbenzene

(Contd. on page 13)



Printing date 06/28/2017

Reviewed on 06/28/2017

Trade name: 19403 GM Olympic White WA8624

(Contd. of page 12)

9038-95-3	OXIRANE,ME, POLYMER
82919-37-7	Methyl (1,2,2,6,6,- pentamethyl-4-piperidinyl) sebacate
108-83-8	2,6-dimethylheptan-4-one
19549-80-5	4,6-dimethylheptan-2-one
1333-86-4	Carbon black
57-55-6	Methyl glycol
78-83-1	butanol
5567-15-7	Novaperm yellow HR02
106-79-6	Dimethyl sebacate(Impurity)
108-65-6	2-methoxy-1-methylethyl acetate
21645-51-2	aluminium hydroxide
7631-86-9	silicon dioxide, chemically prepared
2403-89-6	4-Piperidinol, 1,2,2,6,6 pentamethyl- (Impurity)
95-63-6	1,2,4-trimethylbenzene
147-14-8	Phthalocyanine Blue

· **Proposition 65**

· **Chemicals known to cause cancer:**

108-10-1	4-methylpentan-2-one
13463-67-7	titanium dioxide
1330-20-7	xylene
100-41-4	ethylbenzene
1333-86-4	Carbon black
95-63-6	1,2,4-trimethylbenzene

· **Chemicals known to cause reproductive toxicity for females:**

None of the ingredients is listed.

· **Chemicals known to cause reproductive toxicity for males:**

None of the ingredients is listed.

· **Chemicals known to cause developmental toxicity:**

108-10-1	4-methylpentan-2-one
108-88-3	toluene

· **Carcinogenity categories**

· **EPA (Environmental Protection Agency)**

67-64-1	acetone	I
108-10-1	4-methylpentan-2-one	I
108-88-3	toluene	II
1330-20-7	xylene	I
100-41-4	ethylbenzene	D
95-63-6	1,2,4-trimethylbenzene	II

· **TLV (Threshold Limit Value established by ACGIH)**

67-64-1	acetone	A4
13463-67-7	titanium dioxide	A4

(Contd. on page 14)



Printing date 06/28/2017

Reviewed on 06/28/2017

Trade name: 19403 GM Olympic White WA8624

(Contd. of page 13)

108-88-3	toluene	A4
1330-20-7	xylene	A4
100-41-4	ethylbenzene	A3
1333-86-4	Carbon black	A4

· **NIOSH-Ca (National Institute for Occupational Safety and Health)**

13463-67-7	titanium dioxide
1333-86-4	Carbon black

· **GHS label elements** The product is classified and labeled according to the Globally Harmonized System (GHS).

· **Hazard pictograms**



GHS02 GHS04 GHS07 GHS08

· **Signal word** Danger

· **Hazard-determining components of labeling:**

- acetone
- 4-methylpentan-2-one
- toluene
- n-butyl acetate

· **Hazard statements**

- H222 Extremely flammable aerosol.
- H280 Contains gas under pressure; may explode if heated.
- H319 Causes serious eye irritation.
- H351 Suspected of causing cancer.
- H361 Suspected of damaging fertility or the unborn child.
- H336 May cause drowsiness or dizziness.
- H373 May cause damage to organs through prolonged or repeated exposure.

· **Precautionary statements**

- P201 Obtain special instructions before use.
- P202 Do not handle until all safety precautions have been read and understood.
- P210 Keep away from heat/sparks/open flames/hot surfaces. No smoking.
- P211 Do not spray on an open flame or other ignition source.
- P251 Do not pierce or burn, even after use.
- P260 Do not breathe dust/fume/gas/mist/vapors/spray.
- P264 Wash thoroughly after handling.
- P271 Use only outdoors or in a well-ventilated area.
- P280 Wear protective gloves/protective clothing/eye protection/face protection.
- P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.
- P305+P351+P338 If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
- P308+P313 IF exposed or concerned: Get medical advice/attention.
- P312 Call a POISON CENTER/doctor if you feel unwell.
- P314 Get medical advice/attention if you feel unwell.
- P337+P313 If eye irritation persists: Get medical advice/attention.
- P403+P233 Store in a well-ventilated place. Keep container tightly closed.
- P405 Store locked up.
- P410+P403 Protect from sunlight. Store in a well-ventilated place.

(Contd. on page 15)



Printing date 06/28/2017

Reviewed on 06/28/2017

Trade name: 19403 GM Olympic White WA8624

(Contd. of page 14)

- P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F.  
P501 Dispose of contents/container in accordance with local/regional/national/international regulations.
- **Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

## 16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- **Department issuing SDS:** Environment protection department.
- **Date of preparation / last revision** 06/28/2017 / 16
- **Abbreviations and acronyms:**
  - RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)
  - ICAO: International Civil Aviation Organisation
  - ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)
  - IMDG: International Maritime Code for Dangerous Goods
  - DOT: US Department of Transportation
  - IATA: International Air Transport Association
  - ACGIH: American Conference of Governmental Industrial Hygienists
  - EINECS: European Inventory of Existing Commercial Chemical Substances
  - ELINCS: European List of Notified Chemical Substances
  - CAS: Chemical Abstracts Service (division of the American Chemical Society)
  - NFPA: National Fire Protection Association (USA)
  - HMIS: Hazardous Materials Identification System (USA)
  - VOC: Volatile Organic Compounds (USA, EU)
  - PBT: Persistent, Bioaccumulative and Toxic
  - vPvB: very Persistent and very Bioaccumulative
  - NIOSH: National Institute for Occupational Safety
  - OSHA: Occupational Safety & Health
  - TLV: Threshold Limit Value
  - PEL: Permissible Exposure Limit
  - REL: Recommended Exposure Limit
  - BEI: Biological Exposure Limit
  - Flam. Aerosol 1: Aerosols – Category 1
  - Press. Gas: Gases under pressure – Compressed gas
  - Eye Irrit. 2A: Serious eye damage/eye irritation – Category 2A
  - Carc. 2: Carcinogenicity – Category 2
  - Repr. 2: Reproductive toxicity – Category 2
  - STOT SE 3: Specific target organ toxicity (single exposure) – Category 3
  - STOT RE 2: Specific target organ toxicity (repeated exposure) – Category 2
- **\* Data compared to the previous version altered.**

USA