

Re

Reviewed on 06/20/2017

Page 1/11

# Printing date 06/28/2017 **1 Identification**

- · Product identifier
- Trade name: 38364 Sand Free
- · Article number: 38364
- · Application of the substance / the mixture Interior vehicle cleaner

## 2 Hazard(s) identification

· Classification of the substance or mixture



Flam. Liq. 2 H225 Highly flammable liquid and vapor.



Acute Tox. 4H332Harmful if inhaled.Skin Irrit. 2H315Causes skin irritation.Eye Irrit. 2AH319Causes serious eye irritation.

· Label elements

- · GHS label elements The product is classified and labeled according to the Globally Harmonized System (GHS).
- · Hazard pictograms



- · Signal word Danger
- Hazard-determining components of labeling: xylene

• Hazard statements

H225 Highly flammable liquid and vapor.

- H332 Harmful if inhaled.
- H315 Causes skin irritation.
- H319 Causes serious eye irritation.
- Precautionary statements P210 Keep c
  - Keep away from heat/sparks/open flames/hot surfaces. No smoking.

Printing date 06/28/2017



Reviewed on 06/20/2017

#### Trade name: 38364 Sand Free

(Contd. of page 1) P233 Keep container tightly closed. P240 Ground/bond container and receiving equipment. P241 Use explosion-proof electrical/ventilating/lighting/equipment. P242 Use only non-sparking tools. P243 Take precautionary measures against static discharge. P261 Avoid breathing dust/fume/gas/mist/vapors/spray P264 Wash thoroughly after handling. P271 Use only outdoors or in a well-ventilated area. P280 Wear protective gloves/protective clothing/eye protection/face protection. P303+P361+P353 If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/ shower. P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing. P305+P351+P338 If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. P312 Call a POISON CENTER/doctor if you feel unwell. P321 Specific treatment (see on this label). P332+P313 If skin irritation occurs: Get medical advice/attention. P337+P313 If eye irritation persists: Get medical advice/attention. P362+P364 Take off contaminated clothing and wash it before reuse. P370+P378 In case of fire: Use for extinction: CO2, powder or water spray. P403+P235 Store in a well-ventilated place. Keep cool. P501 Dispose of contents/container in accordance with local/regional/national/international regulations. · Classification system:

· NFPA ratings (scale 0 - 4)



· HMIS-ratings (scale 0 - 4)

	HEALTH	1	Health = 1
			Fire = 3
ſ	REACTIVITY	0	Reactivity = 0

· Other hazards

· Results of PBT and vPvB assessment

· PBT: Not applicable.

· vPvB: Not applicable.

## 3 Composition/information on ingredients

- · Chemical characterization: Mixtures
- · Description:

Mixture: consisting of the following components. Weight percentages

#### · Dangerous components:

0	•	
1330-20-7	xylene	70 - 100%
67-64-1	acetone	13 - 30%
2807-30-9	2-(propyloxy)ethanol	5 - 7%
	(C	contd. on page 3)



Printing date 06/28/2017

Reviewed on 06/20/2017

(Contd. of page 2)

1.5 - 5%

Trade name: 38364 Sand Free

108-65-6 2-methoxy-1-methylethyl acetate

## 4 First-aid measures

- · Description of first aid measures
- General information:

Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.

· After inhalation:

Supply fresh air. If required, provide artificial respiration. Keep patient warm. Consult doctor if symptoms persist.

In case of unconsciousness place patient stably in side position for transportation.

· After skin contact: Immediately wash with water and soap and rinse thoroughly.

• After eye contact:

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

- · After swallowing: If symptoms persist consult doctor.
- · Information for doctor:
- Most important symptoms and effects, both acute and delayed No further relevant information available.
- · Indication of any immediate medical attention and special treatment needed
- No further relevant information available.

#### 5 Fire-fighting measures

- · Extinguishing media
- · Suitable extinguishing agents:

CO2, extinguishing powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

- · For safety reasons unsuitable extinguishing agents: Water with full jet
- · Special hazards arising from the substance or mixture No further relevant information available.
- · Advice for firefighters
- · Protective equipment: Mouth respiratory protective device.

#### 6 Accidental release measures

- Personal precautions, protective equipment and emergency procedures Wear protective equipment. Keep unprotected persons away.
- Environmental precautions: Do not allow to enter sewers/ surface or ground water.

• *Methods and material for containment and cleaning up:* Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust). Ensure adequate ventilation.

· Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

## • Protective Action Criteria for Chemicals

· PAC-1:		
1330-20-7	xylene	130 ppm
67-64-1	acetone	200 ppm
2807-30-9	2-(propyloxy)ethanol	2.2 ppm
		(Contd. on page 4)

acc. to

Printing date 06/28/2017

Reviewed on 06/20/2017

EZ

#### Trade name: 38364 Sand Free

		(Con	td. of page 3)
108-65-6	2-methoxy-1-methylethyl acetate		50 ppm
· PAC-2:			
1330-20-7	xylene	92	20* ppm
67-64-1	acetone	32	200* ppm
2807-30-9	2-(propyloxy)ethanol	24	4 ppm
108-65-6	2-methoxy-1-methylethyl acetate	1,	000 ppm
· PAC-3:			
1330-20-7	xylene	2.	500* ppm
67-64-1	acetone	52	700* ppm
2807-30-9	2-(propyloxy)ethanol	14	40 ppm
108-65-6	2-methoxy-1-methylethyl acetate	50	000* ppm

## 7 Handling and storage

#### · Handling:

- **Precautions for safe handling** No special measures required. Ensure good ventilation/exhaustion at the workplace.
- Information about protection against explosions and fires: Keep ignition sources away - Do not smoke. Protect against electrostatic charges.
- · Conditions for safe storage, including any incompatibilities
- · Storage:
- Requirements to be met by storerooms and receptacles: Store in a cool location.
- · Information about storage in one common storage facility: Not required.
- $\cdot$  Further information about storage conditions:
- Keep receptacle tightly sealed.
- Store in cool, dry conditions in well sealed receptacles.
- Specific end use(s) No further relevant information available.

## 8 Exposure controls/personal protection

· Additional information about design of technical systems: No further data; see item 7.

· Control parameters

· Components with limit values that require monitoring at the workplace:

The following constituents are the only constituents of the product which have a PEL, TLV or other recommended exposure limit.

At this time, the remaining constituent has no known exposure limits.

1330-20-7 xylenePELLong-term value: 435 mg/m³, 100 ppmRELShort-term value: 655 mg/m³, 150 ppmLong-term value: 435 mg/m³, 100 ppmTLVShort-term value: 651 mg/m³, 150 ppmLong-term value: 434 mg/m³, 100 ppmBEI



Reviewed on 06/20/2017

Printing date 06/28/2017

#### Trade name: 38364 Sand Free

	(Contd. of page 4)				
67-64-	-1 acetone				
PEL	Long-term value: 2400 mg/m <sup>3</sup> , 1000 ppm				
REL	Long-term value: 590 mg/m <sup>3</sup> , 250 ppm				
TLV	Short-term value: 1187 mg/m <sup>3</sup> , 500 ppm				
	Long-term value: 594 mg/m <sup>3</sup> , 250 ppm				
	BEI				
	5-6 2-methoxy-1-methylethyl acetate				
WEEL	Long-term value: 50 ppm				
· Ingrea	dients with biological limit values:				
1330-2	20-7 xylene				
BEI 1	1.5 g/g creatinine				
	Aedium: urine				
	<i>Time: end of shift</i>				
	Parameter: Methylhippuric acids				
	-1 acetone				
	50  mg/L				
	Aedium: urine				
	Fime: end of shift				
	Parameter: Acetone (nonspecific)				
• Additi	ional information: The lists that were valid during the creation were used as basis.				
	sure controls				
	nal protective equipment:				
	al protective and hygienic measures:				
	away from foodstuffs, beverages and feed.				
	liately remove all soiled and contaminated clothing.				
	hands before breaks and at the end of work.				
	contact with the eyes and skin. hing equipment:				
	e of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use				
	atory protective device that is independent of circulating air.				
	ction of hands:				
	p missing tests no recommendation to the glove material can be given for the product/ the preparation/ the				
	cal mixture.				
Select	Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation				
Mark Party	Protective gloves				

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

· Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· Penetration time of glove material

The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be observed.



Reviewed on 06/20/2017

Printing date 06/28/2017

Trade name: 38364 Sand Free

(Contd. of page 5)

· Eye protection:



\*

Tightly sealed goggles

· Information on basic physical and chemical properties		
General Information		
· Appearance:		
Form:	Liquid	
Color:	According to product specification	
· Odor:	Characteristic	
Odor threshold:	Not determined.	
pH-value:	Not determined.	
· Change in condition		
Melting point/Melting range:	Undetermined.	
Boiling point/Boiling range:	55.8-56.6 °C	
· Flash point:	-18 °C	
· Flammability (solid, gaseous):	Not applicable.	
· Ignition temperature:	230 °C	
• Decomposition temperature:	Not determined.	
• Auto igniting:	Product is not selfigniting.	
Danger of explosion:	In use, may form flammable/explosive vapour-air mixture.	
· Explosion limits:		
Lower:	1.1 Vol %	
Upper:	13.0 Vol %	
• Vapor pressure at 20 •C:	233 hPa	
· Density at 20 •C:	0.86515 g/cm <sup>3</sup>	
· Relative density	Not determined.	
· Vapor density	Not determined.	
· Evaporation rate	Not determined.	
· Solubility in / Miscibility with		
Water:	Not miscible or difficult to mix.	
· Partition coefficient (n-octanol/wat	er): Not determined.	
· Viscosity:		
Dynamic:	Not determined.	
Kinematic:	Not determined.	
Solvent content:		
Organic solvents:	100.0 %	
VOC content:	86.0 %	

(Contd. of page 6)

Safety Data Sheet acc. to OSHA HCS



Printing date 06/28/2017

Trade name: 38364 Sand Free

· Other information

No further relevant information available.

## 10 Stability and reactivity

- · Reactivity No further relevant information available.
- · Chemical stability
- Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- · Possibility of hazardous reactions No dangerous reactions known.
- · Conditions to avoid No further relevant information available.
- · Incompatible materials: No further relevant information available.
- · Hazardous decomposition products: No dangerous decomposition products known.

#### 11 Toxicological information

#### · Information on toxicological effects

· Acute toxicity:

#### · LD/LC50 values that are relevant for classification:

#### 1330-20-7 xylene

LD50 4300 mg/kg (rat) Oral

Dermal LD50 2000 mg/kg (rabbit)

#### · Primary irritant effect:

- · on the skin: Irritant to skin and mucous membranes.
- on the eye: Irritating effect.
- · Sensitization: No sensitizing effects known.
- · Additional toxicological information:

The product shows the following dangers according to internally approved calculation methods for preparations: Harmful

Irritant

#### · Carcinogenic categories

· IARC (International Agency for Research on Cancer)

#### 1330-20-7 xylene

· NTP (National Toxicology Program)

None of the ingredients is listed.

#### · OSHA-Ca (Occupational Safety & Health Administration)

None of the ingredients is listed.

## **12** Ecological information

- · Toxicity
- · Aquatic toxicity: No further relevant information available.
- · Persistence and degradability No further relevant information available.
- Behavior in environmental systems:
- · Bioaccumulative potential No further relevant information available.
- *Mobility in soil* No further relevant information available.

3

SEM

Printing date 06/28/2017

Reviewed on 06/20/2017

Trade name: 38364 Sand Free

(Contd. of page 7)

- Additional ecological information:
- General notes:
- Water hazard class 2 (Self-assessment): hazardous for water

Do not allow product to reach ground water, water course or sewage system.

- Danger to drinking water if even small quantities leak into the ground.
- Results of PBT and vPvB assessment
- **PBT:** Not applicable.
- · **vPvB:** Not applicable.
- · Other adverse effects No further relevant information available.

## 13 Disposal considerations

- · Waste treatment methods
- · Recommendation:

Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

- · Uncleaned packagings:
- Recommendation: Disposal must be made according to official regulations.

· UN-Number	
· DOT, ADR, IMDG, IATA	UN1263
· UN proper shipping name	
DOT	Paint related material
ADR	1263 Paint related material, special provision 640D
· IMDG, IATA	PAINT RELATED MATERIAL
· Transport hazard class(es)	
DOT	
· Class · Label	3 Flammable liquids 3
· ADR, IMDG, IATA	
· Class	3 Flammable liquids
· Label	3
· Packing group	
· DOT, ÅDR, İMDG, IATA	II
· Environmental hazards:	
• Marine pollutant:	No

(Contd. on page 9)



Printing date 06/28/2017

Page 9/11

Reviewed on 06/20/2017

Trade name: 38364 Sand Free

	(Contd. of page
· Special precautions for user	Warning: Flammable liquids
· EMS Number:	<i>F-E,<u>S-E</u></i>
· Stowage Category	В
· Transport in bulk according to Annex II of	
MARPOL73/78 and the IBC Code	Not applicable.
Transport/Additional information:	
DOT	
· Quantity limitations	On passenger aircraft/rail: 5 L
	On cargo aircraft only: 60 L
ADR	
Excepted quantities (EQ)	Code: E2
	Maximum net quantity per inner packaging: 30 ml
	Maximum net quantity per outer packaging: 500 ml
· IMDG	
Limited quantities (LQ)	5L
Excepted quantities ( $\widetilde{E}Q$ )	Code: E2
	Maximum net quantity per inner packaging: 30 ml
	Maximum net quantity per outer packaging: 500 ml
UN ''Model Regulation'':	UN 1263 PAINT RELATED MATERIAL, SPECIAL PROVISIO 640D, 3, II

## 15 Regulatory information

 $\cdot$  Safety, health and environmental regulations/legislation specific for the substance or mixture  $\cdot$  Sara

· Section 355 (extremely hazardous substances):

None of the ingredient is listed.

· Section 313 (Specific toxic chemical listings):

1330-20-7 xylene

· TSCA (Toxic Substances Control Act):

All ingredients are listed.

· Proposition 65

· Chemicals known to cause cancer:

1330-20-7 xylene

· Chemicals known to cause reproductive toxicity for females:

None of the ingredients is listed.

· Chemicals known to cause reproductive toxicity for males:

None of the ingredients is listed.

· Chemicals known to cause developmental toxicity:

None of the ingredients is listed.

(Contd. on page 10)

Page 10/11

Safety Data Sheet acc. to OSHA HCS

SEM

Printing date 06/28/2017

Reviewed on 06/20/2017

Trade name: 38364 Sand Free

Ι

Ι

A4

A4

- · Cancerogenity categories
- · EPA (Environmental Protection Agency)

1330-20-7 xylene

67-64-1 acetone

#### · TLV (Threshold Limit Value established by ACGIH)

1330-20-7 xylene

67-64-1 acetone

#### · NIOSH-Ca (National Institute for Occupational Safety and Health)

None of the ingredients is listed.

• *GHS label elements* The product is classified and labeled according to the Globally Harmonized System (GHS). • *Hazard pictograms* 



#### · Signal word Danger

Hazard-determinin	ng components of labeling:
xylene	
Hazard statements	
H225 Highly flamm	nable liquid and vapor.
H332 Harmful if in	
H315 Causes skin	irritation.
H319 Causes serio	us eye irritation.
Precautionary stat	ements
P210	Keep away from heat/sparks/open flames/hot surfaces. No smoking.
P233	Keep container tightly closed.
P240	Ground/bond container and receiving equipment.
P241	Use explosion-proof electrical/ventilating/lighting/equipment.
P242	Use only non-sparking tools.
P243	Take precautionary measures against static discharge.
P261	Avoid breathing dust/fume/gas/mist/vapors/spray
P264	Wash thoroughly after handling.
P271	Use only outdoors or in a well-ventilated area.
P280	Wear protective gloves/protective clothing/eye protection/face protection.
P303+P361+P353	If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/
	shower.
P304+P340	IF INHALED: Remove person to fresh air and keep comfortable for breathing.
P305+P351+P338	B If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present
	and easy to do. Continue rinsing.
P312	Call a POISON CENTER/doctor if you feel unwell.
P321	Specific treatment (see on this label).
P332+P313	If skin irritation occurs: Get medical advice/attention.
P337+P313	If eye irritation persists: Get medical advice/attention.
P362+P364	Take off contaminated clothing and wash it before reuse.
P370+P378	In case of fire: Use for extinction: CO2, powder or water spray.
P403+P235	Store in a well-ventilated place. Keep cool.
P501	Dispose of contents/container in accordance with local/regional/national/international
	regulations.

SEM

Reviewed on 06/20/2017

Trade name: 38364 Sand Free

Printing date 06/28/2017

· Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

## 16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Department issuing SDS: Environment protection department.

• Date of preparation / last revision 06/28/2017 / 6	
· Abbreviations and acronyms:	
RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning th	ie
International Transport of Dangerous Goods by Rail)	
ICAO: International Civil Aviation Organisation	
ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International	al
Carriage of Dangerous Goods by Road)	
IMDG: International Maritime Code for Dangerous Goods	
DOT: US Department of Transportation	
IATA: International Air Transport Association	
ACGIH: American Conference of Governmental Industrial Hygienists	
EINECS: European Inventory of Existing Commercial Chemical Substances	
ELINCS: European List of Notified Chemical Substances	
CAS: Chemical Abstracts Service (division of the American Chemical Society)	
NFPA: National Fire Protection Association (USA)	
HMIS: Hazardous Materials Identification System (USA)	
VOC: Volatile Organic Compounds (USA, EU)	
LC50: Lethal concentration, 50 percent	
LD50: Lethal dose, 50 percent	
PBT: Persistent, Bioaccumulative and Toxic	
vPvB: very Persistent and very Bioaccumulative	
NIOSH: National Institute for Occupational Safety	
OSHA: Occupational Safety & Health	
TLV: Threshold Limit Value	
PEL: Permissible Exposure Limit	
REL: Recommended Exposure Limit	
BEI: Biological Exposure Limit	
Flam. Liq. 2: Flammable liquids – Category 2	
Acute Tox. 4: Acute toxicity – Category 4	
Skin Irrit. 2: Skin corrosion/irritation – Category 2	
Eye Irrit. 2A: Serious eye damage/eye irritation – Category 2A	
• * Data compared to the previous version altered.	
	ISA —

(Contd. of page 10)