

Printing date 06/28/2017

1 Identification

· Product identifier

· Trade name: 39377 Seam Sealer

· Article number: 39377

· Application of the substance / the mixture Sealant

2 Hazard(s) identification

· Classification of the substance or mixture



Acute Tox. 4 H302 Harmful if swallowed.

Skin Irrit. 2 H315 Causes skin irritation.

Eye Irrit. 2A H319 Causes serious eye irritation.

Skin Sens. 1 H317 May cause an allergic skin reaction.

STOT SE 3 H335 May cause respiratory irritation.

- · Label elements
- · GHS label elements The product is classified and labeled according to the Globally Harmonized System (GHS).
- · Hazard pictograms



GHS07

- · Signal word Warning
- · Hazard-determining components of labeling:

bisphenolA(chloro)oxirane polymer

Mercaptan Terminated Polymer NJTS 800938 5952

2,4,6-tris(dimethylaminomethyl)phenol

[3-(2,3-epoxypropoxy)propyl]trimethoxysilane

1,3-bis(2,3-epoxypropoxy)-2,2-dimethylpropane

CASTOR OIL GLYCIDAL ETHER

· Hazard statements

H302 Harmful if swallowed.

H315 Causes skin irritation.

H319 Causes serious eye irritation.

H317 May cause an allergic skin reaction.

(Contd. on page 2)

Printing date 06/28/2017 Reviewed on 06/20/2017

Trade name: 39377 Seam Sealer

(Contd. of page 1)

H335 May cause respiratory irritation.

· Precautionary statements

P261 Avoid breathing dust/fume/gas/mist/vapors/spray

P264 Wash thoroughly after handling.

P270 Do not eat, drink or smoke when using this product. P271 Use only outdoors or in a well-ventilated area.

P272 Contaminated work clothing must not be allowed out of the workplace.

P280 Wear protective gloves / eye protection / face protection.

P301+P312 IF SWALLOWED: Call a POISON CENTER/doctor if you feel unwell.

P302+P352 IF ON SKIN: Wash with plenty of water.

P304+P340 *IF INHALED: Remove person to fresh air and keep comfortable for breathing.*

P305+P351+P338 If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present

and easy to do. Continue rinsing.

P321 Specific treatment (see on this label).

P330 Rinse mouth.

P333+P313 If skin irritation or rash occurs: Get medical advice/attention.

P337+P313 If eye irritation persists: Get medical advice/attention. P362+P364 Take off contaminated clothing and wash it before reuse.

P363 Wash contaminated clothing before reuse.

P403+P233 Store in a well-ventilated place. Keep container tightly closed.

P405 Store locked up.

P501 Dispose of contents/container in accordance with local/regional/national/international

regulations.

· Classification system:

· NFPA ratings (scale 0 - 4)



Health = 2Fire = 1Reactivity = 0

· HMIS-ratings (scale 0 - 4)



Health = 2Fire = 1REACTIVITY 0 Reactivity = 0

- · Other hazards
- · Results of PBT and vPvB assessment
- · **PBT**: Not applicable. · vPvB: Not applicable.

3 Composition/information on ingredients

- · Chemical characterization: Mixtures
- · Description:

Mixture: consisting of the following components.

Weight percentages

· Dangerous components:		
	Mercaptan Terminated Polymer NJTS 800938 5952	30 - 40%
25068-38-6	bisphenolA(chloro)oxirane polymer	30 - 40%
67762-90-7	FUMED SILICA	5 - 7%

(Contd. on page 3)



Printing date 06/28/2017 Reviewed on 06/20/2017

Trade name: 39377 Seam Sealer

	(Cor	ntd. of page 2)
26142-30-3	Epoxy Resin	1.5 - 5%
68909-14-8	Modified diglycidal ether	1.5 - 5%
90-72-2	2,4,6-tris(dimethylaminomethyl)phenol	1.5 - 5%
17557-23-2	1,3-bis(2,3-epoxypropoxy)-2,2-dimethylpropane	1-1.5%
74398-71-3	CASTOR OIL GLYCIDAL ETHER	≤1%

4 First-aid measures

- · Description of first aid measures
- · General information:

Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.

· After inhalation:

Supply fresh air and to be sure call for a doctor.

In case of unconsciousness place patient stably in side position for transportation.

- · After skin contact: Immediately wash with water and soap and rinse thoroughly.
- · After eye contact:

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

- · After swallowing: Immediately call a doctor.
- · Information for doctor:
- · Most important symptoms and effects, both acute and delayed No further relevant information available.
- · Indication of any immediate medical attention and special treatment needed

No further relevant information available.

5 Fire-fighting measures

- · Extinguishing media
- · Suitable extinguishing agents: Use fire fighting measures that suit the environment.
- · Special hazards arising from the substance or mixture No further relevant information available.
- · Advice for firefighters
- · Protective equipment: No special measures required.

6 Accidental release measures

- · Personal precautions, protective equipment and emergency procedures Not required.
- · Environmental precautions: No special measures required.
- · Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Ensure adequate ventilation.

· Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

· Protective Action Criteria for Chemicals

· PAC-1:		
25068-38-6 bisphe	nolA(chloro)oxirane polymer	90 mg/m3
67762-90-7 FUME	ED SILICA	120 mg/m3
-		(Contd. on page 4



Printing date 06/28/2017 Reviewed on 06/20/2017

Trade name: 39377 Seam Sealer

		(Contd. of page
90-72-2	2,4,6-tris(dimethylaminomethyl)phenol	6.5 mg/m3
	ethanediol	30 ppm
2530-83-8	[3-(2,3-epoxypropoxy)propyl]trimethoxysilane	9.3 mg/m3
	3-aminopropyltriethoxysilane	1.9 mg/m3
13463-67-7	titanium dioxide	30 mg/m3
1333-86-4	Carbon black	9 mg/m3
14808-60-7	Quartz (SiO2)	0.075 mg/m
67-56-1	methanol	530 ppm
64-17-5	ethanol	1,800 ppm
· PAC-2:		
	bisphenolA(chloro)oxirane polymer	990 mg/m3
67762-90-7	FUMED SILICA	1,300 mg/m
90-72-2	2,4,6-tris(dimethylaminomethyl)phenol	72 mg/m3
107-21-1	ethanediol	150 ppm
2530-83-8	[3-(2,3-epoxypropoxy)propyl]trimethoxysilane	100 mg/m3
919-30-2	3-aminopropyltriethoxysilane	21 mg/m3
13463-67-7	titanium dioxide	330 mg/m3
1333-86-4	Carbon black	99 mg/m3
14808-60-7	Quartz (SiO2)	33 mg/m3
67-56-1	methanol	2,100 ppm
64-17-5	ethanol	3300* ppm
· PAC-3:		·
25068-38-6	bisphenolA(chloro)oxirane polymer	5,900 mg/m
67762-90-7	FUMED SILICA	7,900 mg/m
90-72-2	2,4,6-tris(dimethylaminomethyl)phenol	430 mg/m3
107-21-1	ethanediol	900 ppm
2530-83-8	[3-(2,3-epoxypropoxy)propyl]trimethoxysilane	230 mg/m3
	3-aminopropyltriethoxysilane	350 mg/m3
13463-67-7	titanium dioxide	2,000 mg/m
1333-86-4	Carbon black	590 mg/m3
14808-60-7	Quartz (SiO2)	200 mg/m3
67-56-1	methanol	7200* ppm
64-17-5	ethanol	15000* ppr

7 Handling and storage

- · Handling:
- · Precautions for safe handling No special measures required.
- · Information about protection against explosions and fires: No special measures required.
- · Conditions for safe storage, including any incompatibilities
- · Storage:
- Requirements to be met by storerooms and receptacles: No special requirements.
- · Information about storage in one common storage facility: Not required.

(Contd. on page 5)

Reviewed on 06/20/2017

Printing date 06/28/2017

Trade name: 39377 Seam Sealer

(Contd. of page 4)

- · Further information about storage conditions: Keep receptacle tightly sealed.
- · Specific end use(s) No further relevant information available.

8 Exposure controls/personal protection

- · Additional information about design of technical systems: No further data; see item 7.
- · Control parameters
- · Components with limit values that require monitoring at the workplace:

The product does not contain any relevant quantities of materials with critical values that have to be monitored at the workplace.

- · Additional information: The lists that were valid during the creation were used as basis.
- · Exposure controls
- · Personal protective equipment:
- · General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing.

Wash hands before breaks and at the end of work.

Avoid contact with the eyes and skin.

· Breathing equipment:

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use respiratory protective device that is independent of circulating air.

· Protection of hands:

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

· Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· Penetration time of glove material

The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be observed.

· Eye protection:



Tightly sealed goggles

Reviewed on 06/20/2017

Printing date 06/28/2017

Trade name: 39377 Seam Sealer

(Contd. of page 5)

🏻 9 Physica	l and c	hemical	properties
-------------	---------	---------	------------

· Information on basic physical and	chemical properties
· General Information · Appearance:	
Form:	Liquid
Color:	Dark grey
· Odor:	Amine-like
· Odor threshold:	Not determined.
· pH-value:	Not determined.
· Change in condition	
Melting point/Melting range:	Undetermined.
Boiling point/Boiling range:	261 °C
· Flash point:	257 °C
· Flammability (solid, gaseous):	Not applicable.
· Ignition temperature:	
Decomposition temperature:	Not determined.
· Auto igniting:	Product is not selfigniting.
· Danger of explosion:	Product does not present an explosion hazard.
.	In use, may form flammable/explosive vapour-air mixture.
· Explosion limits:	
Lower:	Not determined.
Upper:	Not determined.
· Vapor pressure:	Not determined.
· Density at 20 °C:	1.25234 g/cm³
· Relative density	Not determined.
· Vapor density	Not determined.
· Evaporation rate	Not determined.
· Solubility in / Miscibility with	
Water:	Not miscible or difficult to mix.
· Partition coefficient (n-octanol/wat	t er): Not determined.
· Viscosity:	
Dynamic at 20 °C:	160000 mPas
Kinematic:	Not determined.
· Solvent content:	
Organic solvents:	0.0 %
Water:	0.1 %
Solids content:	93.8 %
· Other information	No further relevant information available.

10 Stability and reactivity

 $\cdot \textit{Reactivity No further relevant information available}.$



Printing date 06/28/2017

Reviewed on 06/20/2017

Trade name: 39377 Seam Sealer

(Contd. of page 6)

- · Chemical stability
- Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- · Possibility of hazardous reactions No dangerous reactions known.
- · Conditions to avoid No further relevant information available.
- · Incompatible materials: No further relevant information available.
- · Hazardous decomposition products: No dangerous decomposition products known.

11 Toxicological information

- · Information on toxicological effects
- · Acute toxicity:
- · Primary irritant effect:
- · on the skin: Irritant to skin and mucous membranes.
- · on the eye: Irritating effect.
- · Sensitization: Sensitization possible through skin contact.
- · Additional toxicological information:

The product shows the following dangers according to internally approved calculation methods for preparations: Harmful

Irritant

· Carcinogenic categories

,	national Agency for Research on Cancer)	
13463-67-7	titanium dioxide	2B
1333-86-4	Carbon black	2B
14808-60-7	Quartz (SiO2)	1
64-17-5	ethanol	1
· NTP (Nation	nal Toxicology Program)	
14808-60-7	Quartz (SiO2)	K
· OSHA-Ca (Occupational Safety & Health Administration)		
None of the	ingredients is listed.	

12 Ecological information

- · Toxicity
- · Aquatic toxicity: No further relevant information available.
- · Persistence and degradability No further relevant information available.
- · Behavior in environmental systems:
- · Bioaccumulative potential No further relevant information available.
- · Mobility in soil No further relevant information available.
- · Additional ecological information:
- · General notes: Generally not hazardous for water
- · Results of PBT and vPvB assessment
- · **PBT**: Not applicable.
- · vPvB: Not applicable.
- · Other adverse effects No further relevant information available.

USA

Reviewed on 06/20/2017

Printing date 06/28/2017

Trade name: 39377 Seam Sealer

(Contd. of page 7)

13 Disposal considerations

- · Waste treatment methods
- · Recommendation:

Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

- · Uncleaned packagings:
- · Recommendation: Disposal must be made according to official regulations.

UN-Number	
DOT	Void
ADR, IMDG, IATA	UN3082
UN proper shipping name	
DOT	Void
ADR	3082 Environmentally hazardous substances, liquid, n.o.s.
IMDG, IATA	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUI
	N.O.S.
Transport hazard class(es)	
DOT	
Class	Void
•	
Class	9 Miscellaneous dangerous substances and articles
Class Label	9 Miscellaneous dangerous substances and articles 9
Label Packing group DOT	
Label Packing group	9
Label Packing group DOT	Void III Product contains environmentally hazardous substance
Label Packing group DOT ADR, IMDG, IATA	9 Void III
Label Packing group DOT ADR, IMDG, IATA Environmental hazards:	Void III Product contains environmentally hazardous substance bisphenolA(chloro)oxirane polymer Yes Symbol (fish and tree)
Label Packing group DOT ADR, IMDG, IATA Environmental hazards: Marine pollutant: Special marking (ADR):	Void III Product contains environmentally hazardous substance bisphenolA(chloro)oxirane polymer Yes Symbol (fish and tree) Symbol (fish and tree)
Label Packing group DOT ADR, IMDG, IATA Environmental hazards: Marine pollutant:	Void III Product contains environmentally hazardous substance bisphenolA(chloro)oxirane polymer Yes Symbol (fish and tree)
Label Packing group DOT ADR, IMDG, IATA Environmental hazards: Marine pollutant: Special marking (ADR): Special marking (IATA): Special precautions for user	Void III Product contains environmentally hazardous substance bisphenolA(chloro)oxirane polymer Yes Symbol (fish and tree) Symbol (fish and tree)
Label Packing group DOT ADR, IMDG, IATA Environmental hazards: Marine pollutant: Special marking (ADR): Special marking (IATA):	Void III Product contains environmentally hazardous substance bisphenolA(chloro)oxirane polymer Yes Symbol (fish and tree) Symbol (fish and tree) Symbol (fish and tree)

(Contd. on page 9)

Reviewed on 06/20/2017

Printing date 06/28/2017

Trade name: 39377 Seam Sealer

(Contd. of page 8) · Transport/Additional information: ORM-D 49CFR 173.150,156,306 · Remarks · Excepted quantities (EQ) Code: E1 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml · Limited quantities (LO) 5L· Excepted quantities (EQ) Code: E1 Maximum net quantity per inner packaging: 30 ml

LIQUID, N.O.S., 9, III

Maximum net quantity per outer packaging: 1000 ml

UN 3082 ENVIRONMENTALLY HAZARDOUS SUBSTANCES.

15 Regulatory information

· UN "Model Regulation":

· Safety, health and environmental regulations/legislation specific for the substance or mixture

· Sara

 $\cdot ADR$

· IMDG

· Section 355 (extremely hazardous substances): None of the ingredient is listed. · Section 313 (Specific toxic chemical listings): 68909-14-8 Modified diglycidal ether 107-21-1 ethanediol 67-56-1 methanol · TSCA (Toxic Substances Control Act): 25068-38-6 bisphenolA(chloro)oxirane polymer 1317-65-3 GROUND CALCIUM CARBONATE 67762-90-7 FUMED SILICA 26142-30-3 Epoxy Resin 68909-14-8 Modified diglycidal ether 90-72-2 2,4,6-tris(dimethylaminomethyl)phenol 17557-23-2 1,3-bis(2,3-epoxypropoxy)-2,2-dimethylpropane 74398-71-3 CASTOR OIL GLYCIDAL ETHER 107-21-1 ethanediol 2530-83-8 [3-(2,3-epoxypropoxy)propyl]trimethoxysilane 919-30-2 3-aminopropyltriethoxysilane 13463-67-7 titanium dioxide 1333-86-4 Carbon black 14808-60-7 Quartz (SiO2) 67-56-1 methanol 64-17-5 ethanol

(Contd. on page 10)

Reviewed on 06/20/2017

Printing date 06/28/2017

Trade name: 39377 Seam Sealer

(Contd. of page 9) 7732-18-5 water · Proposition 65 · Chemicals known to cause cancer: 25068-38-6 bisphenolA(chloro)oxirane polymer 74398-71-3 CASTOR OIL GLYCIDAL ETHER 107-21-1 ethanediol 13463-67-7 titanium dioxide 1333-86-4 Carbon black 14808-60-7 Quartz (SiO2) · Chemicals known to cause reproductive toxicity for females: None of the ingredients is listed. · Chemicals known to cause reproductive toxicity for males: None of the ingredients is listed. · Chemicals known to cause developmental toxicity: 107-21-1 ethanediol 67-56-1 methanol 64-17-5 ethanol · Cancerogenity categories · EPA (Environmental Protection Agency) None of the ingredients is listed. · TLV (Threshold Limit Value established by ACGIH) 107-21-1 ethanediol A413463-67-7 titanium dioxide A41333-86-4 Carbon black A414808-60-7 Quartz (SiO2) $\overline{A2}$ 64-17-5 ethanol *A3* · NIOSH-Ca (National Institute for Occupational Safety and Health) 13463-67-7 titanium dioxide 1333-86-4 Carbon black 14808-60-7 Quartz (SiO2) 67-56-1 methanol

· GHS label elements The product is classified and labeled according to the Globally Harmonized System (GHS).

· Hazard pictograms



GHS07

- · Signal word Warning
- · Hazard-determining components of labeling:

bisphenolA(chloro)oxirane polymer

Mercaptan Terminated Polymer NJTS 800938 5952

2,4,6-tris(dimethylaminomethyl)phenol

Reviewed on 06/20/2017

Printing date 06/28/2017

Trade name: 39377 Seam Sealer

(Contd. of page 10)

[3-(2,3-epoxypropoxy)propyl]trimethoxysilane 1.3-bis(2.3-epoxypropoxy)-2.2-dimethylpropane

CASTOR OIL GLYCIDAL ETHER

· Hazard statements

H302 Harmful if swallowed.

H315 Causes skin irritation. H319 Causes serious eye irritation.

H317 May cause an allergic skin reaction.

H335 May cause respiratory irritation.

· Precautionary statements

P261	Avoid breathing dust/fume/gas/mist/vapors/spray
P264	Wash thoroughly after handling.
D250	

P270 Do not eat, drink or smoke when using this product. P271 Use only outdoors or in a well-ventilated area.

P272 Contaminated work clothing must not be allowed out of the workplace.

P280 Wear protective gloves / eye protection / face protection.

P301+P312 IF SWALLOWED: Call a POISON CENTER/doctor if you feel unwell.

P302+P352IF ON SKIN: Wash with plenty of water.

P304+P340IF INHALED: Remove person to fresh air and keep comfortable for breathing.

P305+P351+P338 If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present

and easy to do. Continue rinsing.

P321 Specific treatment (see on this label).

P330 Rinse mouth.

P333+P313 If skin irritation or rash occurs: Get medical advice/attention.

P337+P313 *If eye irritation persists: Get medical advice/attention.* P362+P364 *Take off contaminated clothing and wash it before reuse.*

P363 Wash contaminated clothing before reuse.

P403+P233 Store in a well-ventilated place. Keep container tightly closed.

P405 Store locked up.

P501 Dispose of contents/container in accordance with local/regional/national/international

regulations.

· Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- · Department issuing SDS: Environment protection department.
- · Date of preparation / last revision 06/28/2017 / 6
- · Abbreviations and acronyms:

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)

ICAO: International Civil Aviation Organisation

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation

IATA: International Air Transport Association

ACGIH: American Conference of Governmental Industrial Hygienists

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

NFPA: National Fire Protection Association (USA)

(Contd. on page 12)

Page 12/12

SEM

Reviewed on 06/20/2017

Printing date 06/28/2017

Trade name: 39377 Seam Sealer

(Contd. of page 11)

HMIS: Hazardous Materials Identification System (USA)

PBT: Persistent, Bioaccumulative and Toxic vPvB: very Persistent and very Bioaccumulative NIOSH: National Institute for Occupational Safety

OSHA: Occupational Safety & Health

TLV: Threshold Limit Value PEL: Permissible Exposure Limit REL: Recommended Exposure Limit

Acute Tox. 4: Acute toxicity – Category 4

Skin Irrit. 2: Skin corrosion/irritation – Category 2

Eye Irrit. 2A: Serious eye damage/eye irritation - Category 2A

Skin Sens. 1: Skin sensitisation – Category 1

STOT SE 3: Specific target organ toxicity (single exposure) – Category 3

* * Data compared to the previous version altered.

JSA -