



1 Identification

- **Product identifier**
- **Trade name:** 39693 Self Etching Primer Green
- **Article number:** 39693
- **Application of the substance / the mixture**
Coating
aerosol metal primer

2 Hazard(s) identification

- **Classification of the substance or mixture**



GHS02 GHS04 Flame, Gas cylinder

Flam. Aerosol 1 H222 Extremely flammable aerosol.



GHS04 Gas cylinder

Press. Gas H280 Contains gas under pressure; may explode if heated.



GHS08 Health hazard

Carc. 1A H350 May cause cancer.

Repr. 2 H361 Suspected of damaging fertility or the unborn child.

STOT SE 1 H370 Causes damage to organs.

STOT RE 2 H373 May cause damage to organs through prolonged or repeated exposure.

Asp. Tox. 1 H304 May be fatal if swallowed and enters airways.



GHS07

Skin Irrit. 2 H315 Causes skin irritation.

Eye Irrit. 2A H319 Causes serious eye irritation.

STOT SE 3 H336 May cause drowsiness or dizziness.

- **Label elements**

- **GHS label elements** The product is classified and labeled according to the Globally Harmonized System (GHS).

(Contd. on page 2)

Trade name: 39693 Self Etching Primer Green

(Contd. of page 1)

· Hazard pictograms



GHS02 GHS04 GHS07 GHS08

· Signal word *Danger*

· Hazard-determining components of labeling:

toluene

acetone

Quartz (SiO₂)

ethyl acetate

· Hazard statements

H222 Extremely flammable aerosol.

H280 Contains gas under pressure; may explode if heated.

H315 Causes skin irritation.

H319 Causes serious eye irritation.

H350 May cause cancer.

H361 Suspected of damaging fertility or the unborn child.

H370 Causes damage to organs.

H336 May cause drowsiness or dizziness.

H373 May cause damage to organs through prolonged or repeated exposure.

H304 May be fatal if swallowed and enters airways.

· Precautionary statements

P201 Obtain special instructions before use.

P202 Do not handle until all safety precautions have been read and understood.

P210 Keep away from heat/sparks/open flames/hot surfaces. - No smoking.

P211 Do not spray on an open flame or other ignition source.

P251 Pressurized container: Do not pierce or burn, even after use.

P260 Do not breathe dust/fume/gas/mist/vapors/spray.

P264 Wash thoroughly after handling.

P270 Do not eat, drink or smoke when using this product.

P280 Wear protective gloves/protective clothing/eye protection/face protection.

P301+P310 If swallowed: Immediately call a poison center/doctor.

P302+P352 If on skin: Wash with plenty of water.

P305+P351+P338 If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P308+P313 IF exposed or concerned: Get medical advice/attention.

P314 Get medical advice/attention if you feel unwell.

P321 Specific treatment (see on this label).

P331 Do NOT induce vomiting.

P332+P313 If skin irritation occurs: Get medical advice/attention.

P337+P313 If eye irritation persists: Get medical advice/attention.

P362+P364 Take off contaminated clothing and wash it before reuse.

P405 Store locked up.

P410+P403 Protect from sunlight. Store in a well-ventilated place.

P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F.

P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

(Contd. on page 3)



Printing date 09/26/2017

Reviewed on 09/26/2017

Trade name: 39693 Self Etching Primer Green

(Contd. of page 2)

- **Classification system:**
- **NFPA ratings (scale 0 - 4)**



- **HMIS-ratings (scale 0 - 4)**



- **Other hazards**
- **Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.

3 Composition/information on ingredients

- **Chemical characterization: Mixtures**
- **Description:**
Mixture: consisting of the following components.
Weight percentages

- **Dangerous components:**

67-64-1	acetone	13-30%
68476-86-8	Petroleum gases, liquefied, sweetened	13-30%
108-88-3	toluene	7-10%
110-19-0	isobutyl acetate	7-10%
141-78-6	ethyl acetate	5-7%
78-93-3	butanone	5-7%
9004-70-0	CELLULOSE NITRATE	1.5-5%
14808-60-7	Quartz (SiO ₂)	1.5-5%
123-86-4	n-butyl acetate	1.5-5%
64742-94-5	Solvent naphtha (petroleum), heavy arom.	1-1.5%
67-63-0	propan-2-ol	1-1.5%
1330-78-5	tris(methylphenyl) phosphate	≤1%

4 First-aid measures

- **Description of first aid measures**
- **After inhalation:** In case of unconsciousness place patient stably in side position for transportation.
- **After skin contact:** Immediately wash with water and soap and rinse thoroughly.
- **After eye contact:**
Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.
- **After swallowing:** If symptoms persist consult doctor.
- **Information for doctor:**
- **Most important symptoms and effects, both acute and delayed** No further relevant information available.

(Contd. on page 4)



Printing date 09/26/2017

Reviewed on 09/26/2017

Trade name: 39693 Self Etching Primer Green

(Contd. of page 3)

- **Indication of any immediate medical attention and special treatment needed**
No further relevant information available.

5 Fire-fighting measures

- **Extinguishing media**
- **Suitable extinguishing agents:**
CO₂, extinguishing powder or water spray. Fight larger fires with water spray or alcohol resistant foam.
- **Special hazards arising from the substance or mixture** No further relevant information available.
- **Advice for firefighters**
- **Protective equipment:** No special measures required.

6 Accidental release measures

- **Personal precautions, protective equipment and emergency procedures**
Wear protective equipment. Keep unprotected persons away.
- **Environmental precautions:** Do not allow to enter sewers/ surface or ground water.
- **Methods and material for containment and cleaning up:**
Dispose contaminated material as waste according to item 13.
Ensure adequate ventilation.
- **Reference to other sections**
See Section 7 for information on safe handling.
See Section 8 for information on personal protection equipment.
See Section 13 for disposal information.
- **Protective Action Criteria for Chemicals**

· PAC-I:

67-64-1	acetone	200 ppm
108-88-3	toluene	67 ppm
110-19-0	isobutyl acetate	450 ppm
141-78-6	ethyl acetate	1,200 ppm
78-93-3	butanone	200 ppm
14808-60-7	Quartz (SiO ₂)	0.075 mg/m ³
123-86-4	n-butyl acetate	5 ppm
13463-67-7	titanium dioxide	30 mg/m ³
67-63-0	propan-2-ol	400 ppm
108-65-6	2-methoxy-1-methylethyl acetate	50 ppm
1333-86-4	Carbon black	9 mg/m ³
6915-15-7	malic acid	4.8 mg/m ³
1330-20-7	xylene	130 ppm
112945-52-5	SILICA	18 mg/m ³
67-56-1	methanol	530 ppm
100-41-4	ethylbenzene	33 ppm
91-20-3	naphthalene	15 ppm
122-99-6	2-Phenoxyethanol	1.5 ppm
78-83-1	butanol	150 ppm

(Contd. on page 5)



Printing date 09/26/2017

Reviewed on 09/26/2017

Trade name: 39693 Self Etching Primer Green

(Contd. of page 4)

57-55-6	Methyl glycol	30 mg/m ³
95-63-6	1,2,4-trimethylbenzene	140 ppm

· PAC-2:

67-64-1	acetone	3200* ppm
108-88-3	toluene	560 ppm
110-19-0	isobutyl acetate	1300* ppm
141-78-6	ethyl acetate	1,700 ppm
78-93-3	butanone	2700* ppm
14808-60-7	Quartz (SiO ₂)	33 mg/m ³
123-86-4	n-butyl acetate	200 ppm
13463-67-7	titanium dioxide	330 mg/m ³
67-63-0	propan-2-ol	2000* ppm
108-65-6	2-methoxy-1-methylethyl acetate	1,000 ppm
1333-86-4	Carbon black	99 mg/m ³
6915-15-7	malic acid	53 mg/m ³
1330-20-7	xylene	920* ppm
112945-52-5	SILICA	100 mg/m ³
67-56-1	methanol	2,100 ppm
100-41-4	ethylbenzene	1100* ppm
91-20-3	naphthalene	83 ppm
122-99-6	2-Phenoxyethanol	16 ppm
78-83-1	butanol	1,300 ppm
57-55-6	Methyl glycol	1,300 mg/m ³
95-63-6	1,2,4-trimethylbenzene	360 ppm

· PAC-3:

67-64-1	acetone	5700* ppm
108-88-3	toluene	3700* ppm
110-19-0	isobutyl acetate	7500** ppm
141-78-6	ethyl acetate	10000** ppm
78-93-3	butanone	4000* ppm
14808-60-7	Quartz (SiO ₂)	200 mg/m ³
123-86-4	n-butyl acetate	3000* ppm
13463-67-7	titanium dioxide	2,000 mg/m ³
67-63-0	propan-2-ol	12000** ppm
108-65-6	2-methoxy-1-methylethyl acetate	5000* ppm
1333-86-4	Carbon black	590 mg/m ³
6915-15-7	malic acid	320 mg/m ³
1330-20-7	xylene	2500* ppm
112945-52-5	SILICA	630 mg/m ³
67-56-1	methanol	7200* ppm
100-41-4	ethylbenzene	1800* ppm

(Contd. on page 6)



Trade name: 39693 Self Etching Primer Green

(Contd. of page 5)

91-20-3	naphthalene	500 ppm
122-99-6	2-Phenoxyethanol	97 ppm
78-83-1	butanol	8000* ppm
57-55-6	Methyl glycol	7,900 mg/m ³
95-63-6	1,2,4-trimethylbenzene	480 ppm

7 Handling and storage

· **Handling:**

· **Precautions for safe handling**

No special measures required.

Ensure good ventilation/exhaustion at the workplace.

· **Information about protection against explosions and fires:**

Do not spray on a naked flame or any incandescent material.

Keep ignition sources away - Do not smoke.

Pressurized container: protect from sunlight and do not expose to temperatures exceeding 50°C, i.e. electric lights. Do not pierce or burn, even after use.

· **Conditions for safe storage, including any incompatibilities**

· **Storage:**

· **Requirements to be met by storerooms and receptacles:**

Observe official regulations on storing packagings with pressurized containers.

· **Information about storage in one common storage facility:** Not required.

· **Further information about storage conditions:** Keep receptacle tightly sealed.

· **Specific end use(s)** No further relevant information available.

8 Exposure controls/personal protection

· **Additional information about design of technical systems:** No further data; see item 7.

· **Control parameters**

· **Components with limit values that require monitoring at the workplace:**

The following constituents are the only constituents of the product which have a PEL, TLV or other recommended exposure limit.

At this time, the other constituents have no known exposure limits.

67-64-1 acetone

PEL Long-term value: 2400 mg/m³, 1000 ppm

REL Long-term value: 590 mg/m³, 250 ppm

TLV Short-term value: 1187 mg/m³, 500 ppm

Long-term value: 594 mg/m³, 250 ppm

BEI

108-88-3 toluene

PEL Long-term value: 200 ppm

Ceiling limit value: 300; 500* ppm

*10-min peak per 8-hr shift

REL Short-term value: 560 mg/m³, 150 ppm

Long-term value: 375 mg/m³, 100 ppm

(Contd. on page 7)



Printing date 09/26/2017

Reviewed on 09/26/2017

Trade name: 39693 Self Etching Primer Green

(Contd. of page 6)

TLV	Long-term value: 75 mg/m ³ , 20 ppm BEI
-----	---

110-19-0 isobutyl acetate

PEL	Long-term value: 700 mg/m ³ , 150 ppm
REL	Long-term value: 700 mg/m ³ , 150 ppm
TLV	Short-term value: 172 mg/m ³ , 150 ppm Long-term value: 238 mg/m ³ , 50 ppm

141-78-6 ethyl acetate

PEL	Long-term value: 1400 mg/m ³ , 400 ppm
REL	Long-term value: 1400 mg/m ³ , 400 ppm
TLV	Long-term value: 1440 mg/m ³ , 400 ppm

78-93-3 butanone

PEL	Long-term value: 590 mg/m ³ , 200 ppm
REL	Short-term value: 885 mg/m ³ , 300 ppm Long-term value: 590 mg/m ³ , 200 ppm
TLV	Short-term value: 885 mg/m ³ , 300 ppm Long-term value: 590 mg/m ³ , 200 ppm BEI

14808-60-7 Quartz (SiO₂)

PEL	see Quartz listing
REL	Long-term value: 0.05* mg/m ³ *respirable dust; See Pocket Guide App. A
TLV	Long-term value: 0.025* mg/m ³ *as respirable fraction

123-86-4 n-butyl acetate

PEL	Long-term value: 710 mg/m ³ , 150 ppm
REL	Long-term value: 950 mg/m ³ , 200 ppm
TLV	Short-term value: 712 mg/m ³ , 150 ppm Long-term value: 238 mg/m ³ , 50 ppm

67-63-0 propan-2-ol

PEL	Long-term value: 980 mg/m ³ , 400 ppm
REL	Short-term value: 1225 mg/m ³ , 500 ppm Long-term value: 980 mg/m ³ , 400 ppm
TLV	Short-term value: 984 mg/m ³ , 400 ppm Long-term value: 492 mg/m ³ , 200 ppm BEI

· Ingredients with biological limit values:

67-64-1 acetone

BEI	50 mg/L Medium: urine Time: end of shift Parameter: Acetone (nonspecific)
-----	--

(Contd. on page 8)



Trade name: 39693 Self Etching Primer Green

(Contd. of page 7)

108-88-3 toluene

BEI 0.02 mg/L
Medium: blood
Time: prior to last shift of workweek
Parameter: Toluene

0.03 mg/L
Medium: urine
Time: end of shift
Parameter: Toluene

0.3 mg/g creatinine
Medium: urine
Time: end of shift
Parameter: o-Cresol with hydrolysis (background)

78-93-3 butanone

BEI 2 mg/L
Medium: urine
Time: end of shift
Parameter: MEK

67-63-0 propan-2-ol

BEI 40 mg/L
Medium: urine
Time: end of shift at end of workweek
Parameter: Acetone (background, nonspecific)

- **Additional information:** The lists that were valid during the creation were used as basis.
- **Exposure controls**
- **Personal protective equipment:**
- **General protective and hygienic measures:**
Keep away from foodstuffs, beverages and feed.
Immediately remove all soiled and contaminated clothing.
Wash hands before breaks and at the end of work.
Store protective clothing separately.
Avoid contact with the eyes and skin.
- **Breathing equipment:**
In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use respiratory protective device that is independent of circulating air.
- **Protection of hands:**
Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.
Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

- **Material of gloves**
The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

(Contd. on page 9)

Trade name: 39693 Self Etching Primer Green

(Contd. of page 8)

· **Penetration time of glove material**

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· **Eye protection:**

Safety glasses



Tightly sealed goggles

9 Physical and chemical properties

· **Information on basic physical and chemical properties**

· **General Information**

· **Appearance:**

Form: Aerosol
Color: According to product specification

· **Odor:** Characteristic

· **Odor threshold:** Not determined.

· **pH-value:** Not determined.

· **Change in condition**

Melting point/Melting range: Undetermined.
Boiling point/Boiling range: 55.8-56.6 °C

· **Flash point:** -103 °C

· **Flammability (solid, gaseous):** Not applicable.

· **Ignition temperature:** 405 °C

· **Decomposition temperature:** Not determined.

· **Auto igniting:** Product is not selfigniting.

· **Danger of explosion:** In use, may form flammable/explosive vapour-air mixture.

· **Explosion limits:**

Lower: 1.9 Vol %
Upper: 13 Vol %

· **Vapor pressure at 20 °C:** 233 hPa

· **Density at 20 °C:** 0.76577 g/cm³
· **Relative density:** Not determined.
· **Vapor density:** Not determined.
· **Evaporation rate:** Not applicable.

· **Solubility in / Miscibility with**

Water: Not miscible or difficult to mix.

· **Partition coefficient (n-octanol/water):** Not determined.

· **Viscosity:**

Dynamic: Not determined.
Kinematic: Not determined.

(Contd. on page 10)



Printing date 09/26/2017

Reviewed on 09/26/2017

Trade name: 39693 Self Etching Primer Green

(Contd. of page 9)

· Solvent content:	
Organic solvents:	85.9 %
Water:	0.0 %
VOC content:	59.50 %
	612.6 g/l / 5.11 lb/gl
Solids content: 14.0 %	
· Other information	No further relevant information available.

10 Stability and reactivity

- **Reactivity** No further relevant information available.
- **Chemical stability**
- **Thermal decomposition / conditions to be avoided:** No decomposition if used according to specifications.
- **Possibility of hazardous reactions** No dangerous reactions known.
- **Conditions to avoid** No further relevant information available.
- **Incompatible materials:** No further relevant information available.
- **Hazardous decomposition products:** No dangerous decomposition products known.

11 Toxicological information

- **Information on toxicological effects**
- **Acute toxicity:**

· **LD/LC50 values that are relevant for classification:**

108-88-3 toluene

Oral	LD50	5,000 mg/kg (rat)
Dermal	LD50	12,124 mg/kg (rabbit)
Inhalative	LC50/4 h	5,320 mg/l (mouse)

- **Primary irritant effect:**
- **on the skin:** Irritant to skin and mucous membranes.
- **on the eye:** Irritating effect.
- **Sensitization:** No sensitizing effects known.
- **Additional toxicological information:**
The product shows the following dangers according to internally approved calculation methods for preparations:
Irritant

- **Carcinogenic categories**

· **IARC (International Agency for Research on Cancer)**

108-88-3	toluene	3
14808-60-7	Quartz (SiO ₂)	1
13463-67-7	titanium dioxide	2B
67-63-0	propan-2-ol	3
14807-96-6	Talc	3
1333-86-4	Carbon black	2B
1330-20-7	xylene	3
100-41-4	ethylbenzene	2B

(Contd. on page 11)



Printing date 09/26/2017

Reviewed on 09/26/2017

Trade name: 39693 Self Etching Primer Green

(Contd. of page 10)

91-20-3	naphthalene	2B
· NTP (National Toxicology Program)		
14808-60-7	Quartz (SiO ₂)	K
91-20-3	naphthalene	R
· OSHA-Ca (Occupational Safety & Health Administration)		
68911-87-5	montmorilontie clay complex	

12 Ecological information

- **Toxicity**
- **Aquatic toxicity:** No further relevant information available.
- **Persistence and degradability** No further relevant information available.
- **Behavior in environmental systems:**
- **Bioaccumulative potential** No further relevant information available.
- **Mobility in soil** No further relevant information available.
- **Additional ecological information:**
- **General notes:**
Water hazard class 3 (Self-assessment): extremely hazardous for water
Do not allow product to reach ground water, water course or sewage system, even in small quantities.
Danger to drinking water if even extremely small quantities leak into the ground.
- **Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.
- **Other adverse effects** No further relevant information available.

13 Disposal considerations

- **Waste treatment methods**
- **Recommendation:**
Must not be disposed of together with household garbage. Do not allow product to reach sewage system.
- **Uncleaned packagings:**
- **Recommendation:** Disposal must be made according to official regulations.

14 Transport information

- **UN-Number**
- **DOT, ADR, IMDG, IATA** UN1950
- **UN proper shipping name**
- **DOT** Aerosols, flammable
- **ADR** 1950 Aerosols
- **IMDG** AEROSOLS
- **IATA** AEROSOLS, flammable

(Contd. on page 12)



Trade name: 39693 Self Etching Primer Green

(Contd. of page 11)

· **Transport hazard class(es)**

· **DOT**



· **Class** 2.1
· **Label** 2.1

· **ADR**



· **Class** 2 5F Gases
· **Label** 2.1

· **IMDG, IATA**



· **Class** 2.1
· **Label** 2.1

· **Packing group**
· **DOT, ADR, IMDG, IATA** Void

· **Environmental hazards:**
· **Marine pollutant:** No

· **Special precautions for user** Warning: Gases
· **EMS Number:** F-D,S-U
· **Stowage Code** SW1 Protected from sources of heat.
SW22 For AEROSOLS with a maximum capacity of 1 litre:
Category A. For AEROSOLS with a capacity above 1 litre:
Category B. For WASTE AEROSOLS: Category C, Clear of living
quarters.
· **Segregation Code** SG69 For AEROSOLS with a maximum capacity of 1 litre:
Segregation as for class 9. Stow "separated from" class 1 except for
division 1.4. For AEROSOLS with a capacity above 1 litre:
Segregation as for the appropriate subdivision of class 2. For
WASTE AEROSOLS: Segregation as for the appropriate subdivision
of class 2.

· **Transport in bulk according to Annex II of
MARPOL73/78 and the IBC Code** Not applicable.

(Contd. on page 13)



Printing date 09/26/2017

Reviewed on 09/26/2017

Trade name: 39693 Self Etching Primer Green

(Contd. of page 12)

· **Transport/Additional information:**

· **DOT**

· **Quantity limitations**

On passenger aircraft/rail: 75 kg

On cargo aircraft only: 150 kg

· **ADR**

· **Excepted quantities (EQ)**

Code: E0

Not permitted as Excepted Quantity

· **IMDG**

· **Limited quantities (LQ)**

1L

· **Excepted quantities (EQ)**

Code: E0

Not permitted as Excepted Quantity

· **UN "Model Regulation":**

UN 1950 AEROSOLS, 2.1

15 Regulatory information

· **Safety, health and environmental regulations/legislation specific for the substance or mixture**

· **Sara**

· **Section 355 (extremely hazardous substances):**

None of the ingredient is listed.

· **Section 313 (Specific toxic chemical listings):**

108-88-3	toluene
78-93-3	butanone
67-63-0	propan-2-ol
14807-96-6	Talc
1330-20-7	xylene
67-56-1	methanol
	Acrylic Resin
100-41-4	ethylbenzene
91-20-3	naphthalene
122-99-6	2-Phenoxyethanol
95-63-6	1,2,4-trimethylbenzene
104-68-7	Diethylene glycol monophenyl ether

· **TSCA (Toxic Substances Control Act):**

67-64-1	acetone
108-88-3	toluene
110-19-0	isobutyl acetate
141-78-6	ethyl acetate
78-93-3	butanone
9004-70-0	CELLULOSE NITRATE
68038-41-5	Modified Rosin Ester
14808-60-7	Quartz (SiO ₂)

(Contd. on page 14)



Printing date 09/26/2017

Reviewed on 09/26/2017

Trade name: 39693 Self Etching Primer Green

(Contd. of page 13)

123-86-4	<i>n</i> -butyl acetate
13463-67-7	titanium dioxide
64742-94-5	Solvent naphtha (petroleum), heavy arom.
67-63-0	propan-2-ol
1330-78-5	tris(methylphenyl) phosphate
14807-96-6	Talc
18268-70-7	Tetraethylene Glycol Di 2-ethylhexoate
108-65-6	2-methoxy-1-methylethyl acetate
68911-87-5	montmorilontie clay complex
1333-86-4	Carbon black
51274-00-1	YELLOW IRON OXIDE
6915-15-7	malic acid
1330-20-7	xylene
67-56-1	methanol
1328-53-6	PHTHALO GREEN PIGMENT
100-41-4	ethylbenzene
91-20-3	naphthalene
122-99-6	2-Phenoxyethanol
78-83-1	butanol
57-55-6	Methyl glycol
95-63-6	1,2,4-trimethylbenzene
104-68-7	Diethylene glycol monophenyl ether

· **Proposition 65**

· **Chemicals known to cause cancer:**

14808-60-7	Quartz (SiO ₂)
13463-67-7	titanium dioxide
1333-86-4	Carbon black
1330-20-7	xylene
100-41-4	ethylbenzene
91-20-3	naphthalene
95-63-6	1,2,4-trimethylbenzene

· **Chemicals known to cause reproductive toxicity for females:**

None of the ingredients is listed.

· **Chemicals known to cause reproductive toxicity for males:**

None of the ingredients is listed.

· **Chemicals known to cause developmental toxicity:**

108-88-3	toluene
67-56-1	methanol

· **Carcinogenicity categories**

· **EPA (Environmental Protection Agency)**

67-64-1	acetone	<i>I</i>
---------	---------	----------

(Contd. on page 15)



Printing date 09/26/2017

Reviewed on 09/26/2017

Trade name: 39693 Self Etching Primer Green

(Contd. of page 14)

108-88-3	toluene	II
78-93-3	butanone	I
1330-20-7	xylene	I
100-41-4	ethylbenzene	D
91-20-3	naphthalene	C, CBD
95-63-6	1,2,4-trimethylbenzene	II

· **TLV (Threshold Limit Value established by ACGIH)**

67-64-1	acetone	A4
108-88-3	toluene	A4
14808-60-7	Quartz (SiO ₂)	A2
13463-67-7	titanium dioxide	A4
67-63-0	propan-2-ol	A4
14807-96-6	Talc	A4
1333-86-4	Carbon black	A4
1330-20-7	xylene	A4
100-41-4	ethylbenzene	A3
91-20-3	naphthalene	A4

· **NIOSH-Ca (National Institute for Occupational Safety and Health)**

14808-60-7	Quartz (SiO ₂)
13463-67-7	titanium dioxide
1333-86-4	Carbon black
67-56-1	methanol

· **GHS label elements** The product is classified and labeled according to the Globally Harmonized System (GHS).

· **Hazard pictograms**



GHS02 GHS04 GHS07 GHS08

· **Signal word** Danger

· **Hazard-determining components of labeling:**

toluene
acetone
Quartz (SiO₂)
ethyl acetate

· **Hazard statements**

H222 Extremely flammable aerosol.
H280 Contains gas under pressure; may explode if heated.
H315 Causes skin irritation.
H319 Causes serious eye irritation.
H350 May cause cancer.
H361 Suspected of damaging fertility or the unborn child.
H370 Causes damage to organs.
H336 May cause drowsiness or dizziness.
H373 May cause damage to organs through prolonged or repeated exposure.

(Contd. on page 16)



Printing date 09/26/2017

Reviewed on 09/26/2017

Trade name: 39693 Self Etching Primer Green

(Contd. of page 15)

H304 May be fatal if swallowed and enters airways.

· **Precautionary statements**

- P201 Obtain special instructions before use.
P202 Do not handle until all safety precautions have been read and understood.
P210 Keep away from heat/sparks/open flames/hot surfaces. - No smoking.
P211 Do not spray on an open flame or other ignition source.
P251 Pressurized container: Do not pierce or burn, even after use.
P260 Do not breathe dust/fume/gas/mist/vapors/spray.
P264 Wash thoroughly after handling.
P270 Do not eat, drink or smoke when using this product.
P280 Wear protective gloves/protective clothing/eye protection/face protection.
P301+P310 If swallowed: Immediately call a poison center/doctor.
P302+P352 If on skin: Wash with plenty of water.
P305+P351+P338 If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P308+P313 IF exposed or concerned: Get medical advice/attention.
P314 Get medical advice/attention if you feel unwell.
P321 Specific treatment (see on this label).
P331 Do NOT induce vomiting.
P332+P313 If skin irritation occurs: Get medical advice/attention.
P337+P313 If eye irritation persists: Get medical advice/attention.
P362+P364 Take off contaminated clothing and wash it before reuse.
P405 Store locked up.
P410+P403 Protect from sunlight. Store in a well-ventilated place.
P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F.
P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

· **National regulations:**

· **Additional classification according to Decree on Hazardous Materials:**

Carcinogenic hazardous material group III (dangerous).

· **Information about limitation of use:**

Workers are not allowed to be exposed to the hazardous carcinogenic materials contained in this preparation. Exceptions can be made by the authorities in certain cases.

· **Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· **Department issuing SDS:** Environment protection department.

· **Date of preparation / last revision** 09/26/2017 / 19

· **Abbreviations and acronyms:**

ICAO: International Civil Aviation Organisation

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation

IATA: International Air Transport Association

ACGIH: American Conference of Governmental Industrial Hygienists

EINECS: European Inventory of Existing Commercial Chemical Substances

(Contd. on page 17)



Printing date 09/26/2017

Reviewed on 09/26/2017

Trade name: 39693 Self Etching Primer Green

(Contd. of page 16)

ELINCS: European List of Notified Chemical Substances
CAS: Chemical Abstracts Service (division of the American Chemical Society)
NFPA: National Fire Protection Association (USA)
HMIS: Hazardous Materials Identification System (USA)
VOC: Volatile Organic Compounds (USA, EU)
LC50: Lethal concentration, 50 percent
LD50: Lethal dose, 50 percent
PBT: Persistent, Bioaccumulative and Toxic
vPvB: very Persistent and very Bioaccumulative
NIOSH: National Institute for Occupational Safety
OSHA: Occupational Safety & Health
TLV: Threshold Limit Value
PEL: Permissible Exposure Limit
REL: Recommended Exposure Limit
BEI: Biological Exposure Limit
Flam. Aerosol 1: Aerosols – Category 1
Press. Gas: Gases under pressure – Compressed gas
Skin Irrit. 2: Skin corrosion/irritation – Category 2
Eye Irrit. 2A: Serious eye damage/eye irritation – Category 2A
Carc. 1A: Carcinogenicity – Category 1A
Repr. 2: Reproductive toxicity – Category 2
STOT SE 1: Specific target organ toxicity (single exposure) – Category 1
STOT RE 2: Specific target organ toxicity (repeated exposure) – Category 2
Asp. Tox. 1: Aspiration hazard – Category 1

· *** Data compared to the previous version altered.**

USA