

DESCRIPTION

Super SEM Flex is a paint additive that adds flexibility to urethanes, enamels and lacquers. Perfect for refinishing flexible substrates such as bumpers, vinyl convertible tops and flexible plastics.

FEATURES

- Use with most paint systems
- Adds chip resistance
- Improves gloss
- Ideal with Color Coat for vinyl convertible tops

SUITABLE SUBSTRATES

- Color Coat
- Most aftermarket automotive paint systems

TYPICAL PROPERTIES

Part:	Product Name:	Color:	Container:
39728	Super SEM Flex	Clear	Pint
Regulatory VOC:		410 g/L	
Actual VOC:		410 g/L	

Check local VOC regulations to ensure compliance of all products in your area.

HANDLING AND APPLICATION

PREPARATION:

Prep substrate according to paint manufacturer's specifications.

MIXING:

MIX 39728 TO UNREDUCED COMPLIANT MATERIAL AS FOLLOWS:

1 Part	8 Parts
Super SEM Flex	Color Coat for most substrates
1 Part	10 Parts
Super SEM Flex	Color Coat for vinyl convertible tops



Check local VOC regulations to ensure compliance of all products in your area.

FOR OTHER PAINT TYPES:

Start with a 10%-20% addition. Spray a sample panel to test for flex & compatibility.

APPLICATION:

Apply per paint manufacturer's specifications.

CLEAN UP:

Use appropriate cleaning materials compliant with VOC regulations in your area.

STORAGE:

Super SEM Flex should be stored in a cool dry place with adequate ventilation away from heat, sparks and flames. The shelf life for **Super SEM Flex** is 5 years when stored under normal conditions.