Reviewed on 06/21/2017

Printing date 06/28/2017

1 Identification

- · Product identifier
- · Trade name: 39847 Multi-Plastic Repair Material
- · Article number: 39847
- · Application of the substance / the mixture Adhesives

2 Hazard(s) identification

· Classification of the substance or mixture



Acute Tox. 4 H302 Harmful if swallowed.

Skin Irrit. 2 H315 Causes skin irritation.

Eye Irrit. 2A H319 Causes serious eye irritation.

Skin Sens. 1 H317 May cause an allergic skin reaction.

STOT SE 3 H335 May cause respiratory irritation.

- · Label elements
- · GHS label elements The product is classified and labeled according to the Globally Harmonized System (GHS).
- · Hazard pictograms



- · Signal word Warning
- · Hazard-determining components of labeling:

bisphenolA(chloro)oxirane polymer

Talc

2,4,6-tris(dimethylaminomethyl)phenol

Mercaptan Terminated Polymer NJTS 800938 5952

ELASTOMER MODIFIED DIGLYCIDAL ETHER

CYCLOHEXANEDIMETHANOL DIGLYCIDAL ETHER

· Hazard statements

H302 Harmful if swallowed.

H315 Causes skin irritation.

H319 Causes serious eye irritation.

H317 May cause an allergic skin reaction.

(Contd. on page 2)

Printing date 06/28/2017 Reviewed on 06/21/2017

Trade name: 39847 Multi-Plastic Repair Material

(Contd. of page 1)

H335 May cause respiratory irritation.

· Precautionary statements

P261 Avoid breathing dust/fume/gas/mist/vapors/spray

P264 Wash thoroughly after handling.

P270 Do not eat, drink or smoke when using this product. P271 Use only outdoors or in a well-ventilated area.

P272 Contaminated work clothing must not be allowed out of the workplace.

P280 Wear protective gloves / eye protection / face protection.

P301+P312 IF SWALLOWED: Call a POISON CENTER/doctor if you feel unwell.

P302+P352 IF ON SKIN: Wash with plenty of water.

P304+P340 *IF INHALED: Remove person to fresh air and keep comfortable for breathing.*

P305+P351+P338 If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present

and easy to do. Continue rinsing.

P321 Specific treatment (see on this label).

P330 Rinse mouth.

P333+P313 If skin irritation or rash occurs: Get medical advice/attention.

P337+P313 If eye irritation persists: Get medical advice/attention. P362+P364 Take off contaminated clothing and wash it before reuse.

P363 Wash contaminated clothing before reuse.

P403+P233 Store in a well-ventilated place. Keep container tightly closed.

P405 Store locked up.

P501 Dispose of contents/container in accordance with local/regional/national/international

regulations.

· Classification system:

· NFPA ratings (scale 0 - 4)



Health = 1Fire = 1Reactivity = 0

· HMIS-ratings (scale 0 - 4)



Health = 1Fire = 1REACTIVITY 0 Reactivity = 0

- · Other hazards
- · Results of PBT and vPvB assessment
- · **PBT**: Not applicable. · vPvB: Not applicable.

3 Composition/information on ingredients

- · Chemical characterization: Mixtures
- · Description:

Mixture: consisting of the following components.

Weight percentages

· Dangerous components:				
Talc	30 - 40%			
Mercaptan Terminated Polymer NJTS 800938 5952	13 - 30%			
25068-38-6 bisphenolA(chloro)oxirane polymer	13 - 30%			



Reviewed on 06/21/2017 Printing date 06/28/2017

Trade name: 39847 Multi-Plastic Repair Material

	(Co	ntd. of page 2)
65997-17-3	Glass	5 - 7%
26142-30-3	Epoxy Resin	5 - 7%
90-72-2	2,4,6-tris(dimethylaminomethyl)phenol	1.5 - 5%
163440-98-0	ELASTOMER MODIFIED DIGLYCIDAL ETHER	1-1.5%
14228-73-0	CYCLOHEXANEDIMETHANOL DIGLYCIDAL ETHER	≤1%

4 First-aid measures

- · Description of first aid measures
- · General information:

Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.

· After inhalation:

Supply fresh air and to be sure call for a doctor.

In case of unconsciousness place patient stably in side position for transportation.

- · After skin contact: Immediately wash with water and soap and rinse thoroughly.
- · After eye contact:

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

- · After swallowing: Immediately call a doctor.
- · Information for doctor:
- · Most important symptoms and effects, both acute and delayed No further relevant information available.
- · Indication of any immediate medical attention and special treatment needed

No further relevant information available.

5 Fire-fighting measures

- · Extinguishing media
- · Suitable extinguishing agents: Use fire fighting measures that suit the environment.
- · Special hazards arising from the substance or mixture No further relevant information available.
- · Advice for firefighters
- · Protective equipment: No special measures required.

6 Accidental release measures

- · Personal precautions, protective equipment and emergency procedures Not required.
- · Environmental precautions: Do not allow to enter sewers/ surface or ground water.
- · Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust). Ensure adequate ventilation.

· Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

· Protective Action Criteria for Chemicals

· PAC-1:		
25068-38-6	bisphenolA(chloro)oxirane polymer	90 mg/m3
65997-17-3	Glass	15 mg/m3
		(Contd. on page 4

SEM

Printing date 06/28/2017

Reviewed on 06/21/2017

Trade name: 39847 Multi-Plastic Repair Material

		(Contd. of pag
90-72-2 2	2,4,6-tris(dimethylaminomethyl)phenol	6.5 mg/m3
	itanium dioxide	30 mg/m3
919-30-2 3	R-aminopropyltriethoxysilane	1.9 mg/m3
	3-(2,3-epoxypropoxy)propyl]trimethoxysilane	9.3 mg/m3
	tearic acid, pure	14 mg/m3
	FUMED SILICA	120 mg/m3
280-57-9 t	riethylenediamine	5.1 mg/m3
107-21-1 e	· · · · · · · · · · · · · · · · · · ·	30 ppm
1333-86-4	Carbon black	9 mg/m3
14808-60-7 Q	Duartz (SiO2)	0.075 mg/n
64-17-5 e		1,800 ppm
67-56-1 n	nethanol	530 ppm
7631-86-9 s	ilicon dioxide, chemically prepared	18 mg/m3
	uluminium hydroxide	8.7 mg/m3
· PAC-2:	`	
25068-38-6 b	sisphenolA(chloro)oxirane polymer	990 mg/m3
65997-17-3		170 mg/m3
90-72-2 2	2,4,6-tris(dimethylaminomethyl)phenol	72 mg/m3
13463-67-7 t	itanium dioxide	330 mg/m3
919-30-2 3	R-aminopropyltriethoxysilane	21 mg/m3
	3-(2,3-epoxypropoxy)propyl]trimethoxysilane	100 mg/m3
57-11-4 s	tearic acid, pure	150 mg/m3
67762-90-7 I	FUMED SILICA	1,300 mg/n
280-57-9 t	riethylenediamine	56 mg/m3
107-21-1 е	thanediol	150 ppm
1333-86-4	Carbon black	99 mg/m3
14808-60-7 Q	Quartz (SiO2)	33 mg/m3
64-17-5 e	thanol	3300* ppm
67-56-1 n	nethanol	2,100 ppm
7631-86-9 s	ilicon dioxide, chemically prepared	740 mg/m3
21645-51-2 a	luminium hydroxide	73 mg/m3
· PAC-3:		
25068-38-6 b	risphenolA(chloro)oxirane polymer	5,900 mg/n
65997-17-3	Glass	990 mg/m3
90-72-2 2	2,4,6-tris(dimethylaminomethyl)phenol	430 mg/m3
13463-67-7 t	itanium dioxide	2,000 mg/n
919-30-2 3	-aminopropyltriethoxysilane	350 mg/m3
2530-83-8 [3-(2,3-epoxypropoxy)propyl]trimethoxysilane	230 mg/m3
57-11-4 s	tearic acid, pure	910 mg/m3
67762-90-7 I	FUMED SILICA	7,900 mg/n
280-57-9 t	riethylenediamine	340 mg/m3



Printing date 06/28/2017 Reviewed on 06/21/2017

Trade name: 39847 Multi-Plastic Repair Material

		(Contd. of page 4)
107-21-1	ethanediol	900 ppm
1333-86-4	Carbon black	590 mg/m3
14808-60-7	Quartz (SiO2)	200 mg/m3
64-17-5	ethanol	15000* ppm
67-56-1	methanol	7200* ppm
	silicon dioxide, chemically prepared	4,500 mg/m3
21645-51-2	aluminium hydroxide	440 mg/m3

7 Handling and storage

- · Handling:
- · Precautions for safe handling No special measures required.
- · Information about protection against explosions and fires: No special measures required.
- · Conditions for safe storage, including any incompatibilities
- · Storage:
- Requirements to be met by storerooms and receptacles: No special requirements.
- · Information about storage in one common storage facility: Not required.
- · Further information about storage conditions: Keep receptacle tightly sealed.
- · Specific end use(s) No further relevant information available.

8 Exposure controls/personal protection

- · Additional information about design of technical systems: No further data; see item 7.
- · Control parameters
- · Components with limit values that require monitoring at the workplace:

The product does not contain any relevant quantities of materials with critical values that have to be monitored at the workplace.

- · Additional information: The lists that were valid during the creation were used as basis.
- · Exposure controls
- · Personal protective equipment:
- · General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing.

Wash hands before breaks and at the end of work.

Avoid contact with the eyes and skin.

· Breathing equipment:

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use respiratory protective device that is independent of circulating air.

· Protection of hands:

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

(Contd. on page 6)

SEM

Printing date 06/28/2017

Reviewed on 06/21/2017

Trade name: 39847 Multi-Plastic Repair Material

(Contd. of page 5)

· Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· Penetration time of glove material

The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be observed.

· Eye protection:



Tightly sealed goggles

9 Physical	and	c	hemical	nro	nerties
I II II ysicui	unu	U	iemicui	PIU	pernes

· General Information

· Appearance:

Form: Liquid

Color: According to product specification

Odor: CharacteristicOdor threshold: Not determined.

· pH-value: Not determined.

· Change in condition

Melting point/Melting range: Undetermined.
Boiling point/Boiling range: 201 °C

• Flash point: 257 °C

· Flammability (solid, gaseous): Not applicable.

· Ignition temperature:

Decomposition temperature: Not determined.

· Auto igniting: Product is not selfigniting.

• Danger of explosion: Product does not present an explosion hazard.
In use, may form flammable/explosive vapour-air mixture.

Not determined.

· Explosion limits:

· Evaporation rate

Lower:Not determined.Upper:Not determined.

· Vapor pressure: Not determined.
· Density at 20 °C: 1.59895 g/cm³

Relative density
Vapor density
Not determined.
Not determined.

· Solubility in / Miscibility with

Water: Not miscible or difficult to mix.

(Contd. on page 7)

SEM

Printing date 06/28/2017 Reviewed on 06/21/2017

Trade name: 39847 Multi-Plastic Repair Material

		(Contd. of page 6)
· Partition coefficient (n-octan	ol/water): Not determined.	
· Viscosity: Dynamic: Kinematic:	Not determined. Not determined.	
· Solvent content: Organic solvents:	0.0 %	
Solids content: · Other information	99.9 % No further relevant information available.	

10 Stability and reactivity

- · Reactivity No further relevant information available.
- · Chemical stability
- Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- · Possibility of hazardous reactions No dangerous reactions known.
- · Conditions to avoid No further relevant information available.
- · Incompatible materials: No further relevant information available.
- · Hazardous decomposition products: No dangerous decomposition products known.

11 Toxicological information

- · Information on toxicological effects
- · Acute toxicity:
- · Primary irritant effect:
- · on the skin: Irritant to skin and mucous membranes.
- · on the eye: Irritating effect.
- · Sensitization: Sensitization possible through skin contact.
- · Additional toxicological information:

The product shows the following dangers according to internally approved calculation methods for preparations: Harmful

Irritant

· Carcinogenic categories

· IARC (International Agency for Research on Cancer)				
	Talc	3		
13463-67-7	titanium dioxide	2B		
1333-86-4	Carbon black	2B		
14808-60-7	Quartz (SiO2)	1		
64-17-5	ethanol	1		
7631-86-9	silicon dioxide, chemically prepared	3		

· NTP (National Toxicology Program) 14808-60-7 | Quartz (SiO2)

(Contd. on page 8)

SEM

Printing date 06/28/2017

Reviewed on 06/21/2017

Trade name: 39847 Multi-Plastic Repair Material

(Contd. of page 7)

· OSHA-Ca (Occupational Safety & Health Administration)

None of the ingredients is listed.

12 Ecological information

- · Toxicity
- · Aquatic toxicity: No further relevant information available.
- · Persistence and degradability No further relevant information available.
- · Behavior in environmental systems:
- · Bioaccumulative potential No further relevant information available.
- · Mobility in soil No further relevant information available.
- · Additional ecological information:
- · General notes:

Water hazard class 2 (Self-assessment): hazardous for water

Do not allow product to reach ground water, water course or sewage system.

Danger to drinking water if even small quantities leak into the ground.

- · Results of PBT and vPvB assessment
- · **PBT**: Not applicable.
- · vPvB: Not applicable.
- · Other adverse effects No further relevant information available.

13 Disposal considerations

- · Waste treatment methods
- · Recommendation:

Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

- · Uncleaned packagings:
- **Recommendation:** Disposal must be made according to official regulations.

· UN-Number		
· DOT, ADR, ADN, IMDG, IATA	Void	
· UN proper shipping name		
· DOT, ADR, ADN, IMDG, IATA	Void	
· Transport hazard class(es)		
· DOT, ADR, ADN, IMDG, IATA		
·Class	Void	
· Packing group		
· DOT, ADR, IMDG, IATA	Void	
· Environmental hazards:		
· Marine pollutant:	No	
· Special precautions for user	Not applicable.	

(Contd. on page 9)

Page 9/12 Reviewed on 06/21/2017

Printing date 06/28/2017

Trade name: 39847 Multi-Plastic Repair Material

(Contd. of page 8)

· Transport in bulk according to Annex II of	
MARPOL73/78 and the IBC Code	Not applicable.

· Transport/Additional information:

 $\cdot DOT$

NOT REGULATED · Remarks

· UN "Model Regulation": Void

			^f orma	
0011	at a way	770	O TATAL O	tion
CAPILII			E 0 3 M 1 1 7 F 0	,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,

· Safety, health and environmental regulations/legislation specific for the substance or mixture

· Sara				
· Section 355 (extremely hazardous substances): None of the ingredient is listed. · Section 313 (Specific toxic chemical listings):				
				Talc
			163440-98-0	ELASTOMER MODIFIED DIGLYCIDAL ETHER
107-21-1	ethanediol			
67-56-1	methanol			
· TSCA (Toxic	Substances Control Act):			
	Talc			
25068-38-6	bisphenolA(chloro)oxirane polymer			
1317-65-3	GROUND CALCIUM CARBONATE			
65997-17-3	Glass			
26142-30-3	Epoxy Resin			
90-72-2	2,4,6-tris(dimethylaminomethyl)phenol			
13463-67-7	titanium dioxide			
163440-98-0	ELASTOMER MODIFIED DIGLYCIDAL ETHER			
18268-70-7	Tetraethylene Glycol Di 2-ethylhexoate			
14228-73-0	CYCLOHEXANEDIMETHANOL DIGLYCIDAL ETHER			
919-30-2	3-aminopropyltriethoxysilane			
2530-83-8	[3-(2,3-epoxypropoxy)propyl]trimethoxysilane			
57-11-4	stearic acid, pure			
67762-90-7	FUMED SILICA			
280-57-9	triethylenediamine			
107-21-1	ethanediol			
1333-86-4	Carbon black			
14808-60-7	Quartz (SiO2)			
64-17-5	ethanol			
67-56-1	methanol			
7631-86-9	silicon dioxide, chemically prepared			
21645-51-2	aluminium hydroxide			

(Contd. on page 10)

Reviewed on 06/21/2017

Printing date 06/28/2017

Trade name: 39847 Multi-Plastic Repair Material

		(Contd. of page 9)
7732-18		
· Proposition		
· Chemicals I	cnown to cause cancer:	
25068-38-0	bisphenolA(chloro)oxirane polymer	
13463-67-	titanium dioxide	
163440-98-0	ELASTOMER MODIFIED DIGLYCIDAL ETHER	
107-21-	l ethanediol	
1333-86-	Carbon black	
14808-60-	Quartz (SiO2)	
· Chemicals I	nown to cause reproductive toxicity for females:	
None of the	ingredients is listed.	
	nown to cause reproductive toxicity for males:	
None of the ingredients is listed.		
· Chemicals I	nown to cause developmental toxicity:	
107-21-1 ethanediol		
64-17-5 ei	hanol	
67-56-1 m	ethanol	
· Cancerogen	ity categories	
· EPA (Envir	onmental Protection Agency)	
None of the	ingredients is listed.	
· TLV (Thres	hold Limit Value established by ACGIH)	
	Talc	A4
13463-67-7	titanium dioxide	A4
107-21-1	ethanediol	A4
1333-86-4	Carbon black	A4
14808-60-7	Quartz (SiO2)	A2
64-17-5	ethanol	A3
· NIOSH-Ca	(National Institute for Occupational Safety and Health)	
13463-67-7	titanium dioxide	
1333-86-4	Carbon black	
14808-60-7	Quartz (SiO2)	
67-56-1	methanol	

- · GHS label elements The product is classified and labeled according to the Globally Harmonized System (GHS).
- · Hazard pictograms



- · Signal word Warning
- · Hazard-determining components of labeling: bisphenolA(chloro)oxirane polymer Talc

(Contd. on page 11)

Reviewed on 06/21/2017

Printing date 06/28/2017

Trade name: 39847 Multi-Plastic Repair Material

(Contd. of page 10)

2,4,6-tris(dimethylaminomethyl)phenol

Mercaptan Terminated Polymer NJTS 800938 5952 ELASTOMER MODIFIED DIGLYCIDAL ETHER

CYCLOHEXANEDIMETHANOL DIGLYCIDAL ETHER

· Hazard statements

H302 Harmful if swallowed.

H315 Causes skin irritation.

H319 Causes serious eye irritation.

H317 May cause an allergic skin reaction.

H335 May cause respiratory irritation.

· Precautionary statements

P261 Avoid breathing dust/fume/gas/mist/vapors/spray

P264 Wash thoroughly after handling.

P270 Do not eat, drink or smoke when using this product. P271 Use only outdoors or in a well-ventilated area.

P272 Contaminated work clothing must not be allowed out of the workplace.

P280 *Wear protective gloves / eye protection / face protection.*

P301+P312IF SWALLOWED: Call a POISON CENTER/doctor if you feel unwell.

P302+P352IF ON SKIN: Wash with plenty of water.

P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.

P305+P351+P338 If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present

and easy to do. Continue rinsing.

P321 Specific treatment (see on this label).

P330 Rinse mouth.

P333+P313 If skin irritation or rash occurs: Get medical advice/attention.

P337+P313 *If eye irritation persists: Get medical advice/attention.* P362+P364 Take off contaminated clothing and wash it before reuse.

P363 Wash contaminated clothing before reuse.

P403+P233 Store in a well-ventilated place. Keep container tightly closed.

P405 Store locked up.

P501 Dispose of contents/container in accordance with local/regional/national/international

regulations.

· Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- · Department issuing SDS: Environment protection department.
- · Date of preparation / last revision 06/28/2017 / 6
- · Abbreviations and acronyms:

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)

ICAO: International Civil Aviation Organisation

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation

IATA: International Air Transport Association

ACGIH: American Conference of Governmental Industrial Hygienists

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

(Contd. on page 12)

Page 12/12 Reviewed on 06/21/2017

Printing date 06/28/2017

Trade name: 39847 Multi-Plastic Repair Material

(Contd. of page 11)

NFPA: National Fire Protection Association (USA) HMIS: Hazardous Materials Identification System (USA)

PBT: Persistent, Bioaccumulative and Toxic vPvB: very Persistent and very Bioaccumulative NIOSH: National Institute for Occupational Safety

OSHA: Occupational Safety & Health

TLV: Threshold Limit Value PEL: Permissible Exposure Limit REL: Recommended Exposure Limit Acute Tox. 4: Acute toxicity – Category 4

Skin Irrit. 2: Skin corrosion/irritation – Category 2

Eye Irrit. 2A: Serious eye damage/eye irritation - Category 2A

Skin Sens. 1: Skin sensitisation – Category 1

STOT SE 3: Specific target organ toxicity (single exposure) - Category 3

* Data compared to the previous version altered.