Reviewed on 06/20/2017

Printing date 06/28/2017

1 Identification

- · Product identifier
- · Trade name: 40502, 40507 QUICK SET 50 Adhesive
- · Article number: 40502, 40507
- · Application of the substance / the mixture Adhesives

2 Hazard(s) identification

· Classification of the substance or mixture



GHS08 Health hazard

Resp. Sens. 1 H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled.

H351 Suspected of causing cancer.

STOT RE 2 H373 May cause damage to organs through prolonged or repeated exposure.



GHS07

Skin Irrit. 2 H315 Causes skin irritation.

Eye Irrit. 2A H319 Causes serious eye irritation.

Skin Sens. 1 H317 May cause an allergic skin reaction.

STOT SE 3 H335 May cause respiratory irritation.

- · Label elements
- GHS label elements The product is classified and labeled according to the Globally Harmonized System (GHS).
- · Hazard pictograms





GHS07

GHS08

- · Signal word Danger
- · Hazard-determining components of labeling:

POLYMERIC MDI

4,4'-methylenediphenyl diisocyanate

Hydroxy terminated poly(oxyalkylated)polyol / proprietary

3-aminomethyl-3,5,5-trimethylcyclohexylamine

(Contd. on page 2)



Printing date 06/28/2017 Reviewed on 06/20/2017

Trade name: 40502, 40507 QUICK SET 50 Adhesive

(Contd. of page 1)

· Hazard statements

- H315 Causes skin irritation.
- H319 Causes serious eye irritation.
- H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled.
- H317 May cause an allergic skin reaction.
- H351 Suspected of causing cancer.
- H335 May cause respiratory irritation.
- H373 May cause damage to organs through prolonged or repeated exposure.

· Precautionary statements

P201	Obtain	special	instructions	before use.

- P202 Do not handle until all safety precautions have been read and understood.
- P260 Do not breathe dust/fume/gas/mist/vapors/spray.
- *P264 Wash thoroughly after handling.*
- P271 Use only outdoors or in a well-ventilated area.
- P272 Contaminated work clothing must not be allowed out of the workplace.
 P280 Wear protective gloves/protective clothing/eye protection/face protection.
- *P284* [In case of inadequate ventilation] wear respiratory protection.
- *P302+P352 IF ON SKIN: Wash with plenty of water.*
- P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.
- P305+P351+P338 If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present
 - and easy to do. Continue rinsing.
- P308+P313 IF exposed or concerned: Get medical advice/attention.
 P312 Call a POISON CENTER/doctor if you feel unwell.
 P314 Get medical advice/attention if you feel unwell.
- *P321* Specific treatment (see on this label).
- P333+P313 If skin irritation or rash occurs: Get medical advice/attention.
- P337+P313 If eye irritation persists: Get medical advice/attention.
- P342+P311 If experiencing respiratory symptoms: Call a POISON CENTER/doctor.
- *P362+P364 Take off contaminated clothing and wash it before reuse.*
- *P363* Wash contaminated clothing before reuse.
- P403+P233 Store in a well-ventilated place. Keep container tightly closed.
- P405 Store locked up.
- P501 Dispose of contents/container in accordance with local/regional/national/international
 - regulations.
- · Classification system:
- · NFPA ratings (scale 0 4)



Health = 2 Fire = 1Reactivity = 0

· HMIS-ratings (scale 0 - 4)



- · Other hazards
- · Results of PBT and vPvB assessment
- **PBT**: Not applicable.
- · vPvB: Not applicable.



Printing date 06/28/2017 Reviewed on 06/20/2017

Trade name: 40502, 40507 QUICK SET 50 Adhesive

(Contd. of page 2)

3 Composition/information on ingredients

- · Chemical characterization: Mixtures
- · Description:

Mixture: consisting of the following components.

Weight percentages

· Dangerous components:		
	Hydroxy terminated poly(oxyalkylated)polyol / proprietary	30 - 40%
53862-89-8	POLYMERIC MDI	30 - 40%
101-68-8	4,4'-methylenediphenyl diisocyanate	13 - 30%
2855-13-2	3-aminomethyl-3,5,5-trimethylcyclohexylamine	1.5 - 5%

4 First-aid measures

- · Description of first aid measures
- · After inhalation:

Supply fresh air and to be sure call for a doctor.

In case of unconsciousness place patient stably in side position for transportation.

- · After skin contact: Immediately wash with water and soap and rinse thoroughly.
- · After eye contact:

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

- · After swallowing: If symptoms persist consult doctor.
- · Information for doctor:
- · Most important symptoms and effects, both acute and delayed No further relevant information available.
- · Indication of any immediate medical attention and special treatment needed

No further relevant information available.

5 Fire-fighting measures

- · Extinguishing media
- · Suitable extinguishing agents:

CO2, extinguishing powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

- · Special hazards arising from the substance or mixture No further relevant information available.
- · Advice for firefighters
- · Protective equipment: No special measures required.

6 Accidental release measures

- · Personal precautions, protective equipment and emergency procedures Not required.
- · Environmental precautions: Do not allow to enter sewers/ surface or ground water.
- · Methods and material for containment and cleaning up:

Dispose contaminated material as waste according to item 13.

Ensure adequate ventilation.

· Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

(Contd. on page 4)

SEM

Printing date 06/28/2017 Reviewed on 06/20/2017

Trade name: 40502, 40507 QUICK SET 50 Adhesive

(Contd. of page 3)

· Protective Action Criteria for Chemicals

· PAC-1:		
101-68-8	4,4'-methylenediphenyl diisocyanate	0.45 mg/m3
102-60-3	1,1',1"',1'''-ethylenedinitrilotetrapropan-2-ol	34 mg/m3
1333-86-4	Carbon black	9 mg/m3
· PAC-2:		
101-68-8	4,4'-methylenediphenyl diisocyanate	5 mg/m3
102-60-3	1,1',1"',1'''-ethylenedinitrilotetrapropan-2-ol	370 mg/m3
1333-86-4	Carbon black	99 mg/m3
· PAC-3:		
101-68-8	4,4'-methylenediphenyl diisocyanate	55 mg/m3
102-60-3	1,1',1'',1'''-ethylenedinitrilotetrapropan-2-ol	2,200 mg/m3
1333-86-4	Carbon black	590 mg/m3

7 Handling and storage

- · Handling:
- · Precautions for safe handling

No special measures required.

Ensure good ventilation/exhaustion at the workplace.

- · Information about protection against explosions and fires: No special measures required.
- · Conditions for safe storage, including any incompatibilities
- · Storage:
- Requirements to be met by storerooms and receptacles: No special requirements.
- · Information about storage in one common storage facility: Not required.
- · Further information about storage conditions: Keep receptacle tightly sealed.
- · Specific end use(s) No further relevant information available.

8 Exposure controls/personal protection

- · Additional information about design of technical systems: No further data; see item 7.
- · Control parameters
- · Components with limit values that require monitoring at the workplace:

The following constituent is the only constituent of the product which has a PEL, TLV or other recommended exposure limit.

At this time, the other constituents have no known exposure limits.

101-0	101-68-8 4,4'-methylenediphenyl diisocyanate		
PEL	Ceiling limit value: 0.2 mg/m³, 0.02 ppm		
	Long-term value: 0.05 mg/m^3 , 0.005 ppm Ceiling limit value: $0.2* \text{ mg/m}^3$, $0.02* \text{ ppm}$ *10-min		
TLV	Long-term value: 0.051 mg/m³, 0.005 ppm		

· Additional information: The lists that were valid during the creation were used as basis.

(Contd. on page 5)

SEM

Printing date 06/28/2017

Reviewed on 06/20/2017

Trade name: 40502, 40507 OUICK SET 50 Adhesive

(Contd. of page 4)

- · Exposure controls
- · Personal protective equipment:
- · General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing.

Wash hands before breaks and at the end of work.

Store protective clothing separately.

Avoid contact with the eyes and skin.

· Breathing equipment:

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use respiratory protective device that is independent of circulating air.

· Protection of hands:

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

· Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· Penetration time of glove material

The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be observed.

· Eye protection:



Tightly sealed goggles

9 Physical and chemical properties

- · Information on basic physical and chemical properties
- · General Information
- · Appearance:

Form: Liquid

Color: According to product specification

Odor: CharacteristicOdor threshold: Not determined.

· pH-value: Not applicable.

· Change in condition

Melting point/Melting range:Undetermined.Boiling point/Boiling range:208 °C

· Flash point: 94 °C

(Contd. on page 6)

SEM

Printing date 06/28/2017

Reviewed on 06/20/2017

Trade name: 40502, 40507 QUICK SET 50 Adhesive

	(Contd. of page
Flammability (solid, gaseous):	Not determined.
Ignition temperature:	520 °C
Decomposition temperature:	Not determined.
Auto igniting:	Product is not selfigniting.
Danger of explosion:	Product does not present an explosion hazard. In use, may form flammable/explosive vapour-air mixture.
Explosion limits:	
Lower:	0.4 Vol %
Upper:	0.0 Vol %
Vapor pressure:	Not applicable.
Density at 20 °C:	1.10967 g/cm³
Relative density	Not determined.
Vapor density	Not applicable.
Evaporation rate	Not applicable.
Solubility in / Miscibility with	
Water:	Insoluble.
Partition coefficient (n-octanol/wat	ter): Not determined.
Viscosity:	
Dynamic:	Not applicable.
Kinematic:	Not applicable.
Solvent content:	
Organic solvents:	0.0 %
Solids content:	98.0 %
Other information	No further relevant information available.

10 Stability and reactivity

- · Reactivity No further relevant information available.
- · Chemical stability
- · Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- · Possibility of hazardous reactions No dangerous reactions known.
- · Conditions to avoid No further relevant information available.
- · Incompatible materials: No further relevant information available.
- · Hazardous decomposition products: No dangerous decomposition products known.

11 Toxicological information

- · Information on toxicological effects
- · Acute toxicity:
- · LD/LC50 values that are relevant for classification:

101-68-8 4,4'-methylenediphenyl diisocyanate

Oral LD50 2200 mg/kg (mouse)

(Contd. on page 7)



Printing date 06/28/2017 Reviewed on 06/20/2017

Trade name: 40502, 40507 QUICK SET 50 Adhesive

(Contd. of page 6)

- · Primary irritant effect:
- · on the skin: Irritant to skin and mucous membranes.
- · on the eye: Irritating effect.
- · Sensitization:

Sensitization possible through inhalation.

Sensitization possible through skin contact.

· Additional toxicological information:

The product shows the following dangers according to internally approved calculation methods for preparations: Harmful

Irritant

· Carcinogenic categories

· IARC (International Agency for Research on Cancer)		
101-68-8	4,4'-methylenediphenyl diisocyanate	3
1333-86-4	Carbon black	2B
· NTP (National Toxicology Program)		
None of the ingredients is listed.		
· OSHA-Ca (Occupational Safety & Health Administration)		
None of the ingredients is listed.		

12 Ecological information

- · Toxicity
- · Aquatic toxicity: No further relevant information available.
- · Persistence and degradability No further relevant information available.
- · Behavior in environmental systems:
- · Bioaccumulative potential No further relevant information available.
- · Mobility in soil No further relevant information available.
- · Additional ecological information:
- · General notes:

Water hazard class 1 (Self-assessment): slightly hazardous for water

Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

- · Results of PBT and vPvB assessment
- · **PBT**: Not applicable.
- · vPvB: Not applicable.
- · Other adverse effects No further relevant information available.

13 Disposal considerations

- · Waste treatment methods
- · Recommendation:

Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

- · Uncleaned packagings:
- · Recommendation: Disposal must be made according to official regulations.

USA ·

SEM

Printing date 06/28/2017

Reviewed on 06/20/2017

Trade name: 40502, 40507 QUICK SET 50 Adhesive

(Contd. of page 7)

Transport information		
UN-Number DOT, ADR, ADN, IMDG, IATA	Void	
UN proper shipping name DOT, ADR, ADN, IMDG, IATA	Void	
Transport hazard class(es)		
DOT, ADR, ADN, IMDG, IATA Class	Void	
Packing group DOT, ADR, IMDG, IATA	Void	
Environmental hazards: Marine pollutant:	No	
Special precautions for user	Not applicable.	
Transport in bulk according to Annex	II of	
MARPOL73/78 and the IBC Code	Not applicable.	
UN ''Model Regulation'':	Void	

15 Regulatory information

- · Safety, health and environmental regulations/legislation specific for the substance or mixture
- · Sara
- · Section 355 (extremely hazardous substances):

None of the ingredient is listed.

· Section 313 (Specific toxic chemical listings):

101-68-8 4,4'-methylenediphenyl diisocyanate

· TSCA (Toxic Substances Control Act):

53862-89-8 POLYMERIC MDI

101-68-8 4,4'-methylenediphenyl diisocyanate

102-60-3 1,1',1",1"'-ethylenedinitrilotetrapropan-2-ol

2855-13-2 3-aminomethyl-3,5,5-trimethylcyclohexylamine

1333-86-4 Carbon black

· Proposition 65

· Chemicals known to cause cancer:

1333-86-4 | Carbon black

· Chemicals known to cause reproductive toxicity for females:

None of the ingredients is listed.

· Chemicals known to cause reproductive toxicity for males:

None of the ingredients is listed.

· Chemicals known to cause developmental toxicity:

None of the ingredients is listed.

(Contd. on page 9)

Reviewed on 06/20/2017 Printing date 06/28/2017

Trade name: 40502, 40507 QUICK SET 50 Adhesive

(Contd. of page 8)

· Cancerogenity categories

· EPA (Environmental Protection Agency)	
101-68-8 4,4'-methylenediphenyl diisocyanate	D, CBD
· TLV (Threshold Limit Value established by ACGIH)	
1333-86-4 Carbon black	A4
· NIOSH-Ca (National Institute for Occupational Safety and Health)	
1333-86-4 Carbon black	

· GHS label elements The product is classified and labeled according to the Globally Harmonized System (GHS).

· Hazard pictograms





· Signal word Danger

· Hazard-determining components of labeling:

POLYMERIC MDI

4,4'-methylenediphenyl diisocyanate

Hydroxy terminated poly(oxyalkylated)polyol / proprietary

3-aminomethyl-3,5,5-trimethylcyclohexylamine

· Hazard statements

H315 Causes skin irritation.

H319 Causes serious eye irritation.

H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled.

H317 May cause an allergic skin reaction.

H351 Suspected of causing cancer.

H335 May cause respiratory irritation.

P362+P364

lamage to organs through prolonged or repeated exposure.
tements
Obtain special instructions before use.
Do not handle until all safety precautions have been read and understood.
Do not breathe dust/fume/gas/mist/vapors/spray.
Wash thoroughly after handling.
Use only outdoors or in a well-ventilated area.
Contaminated work clothing must not be allowed out of the workplace.
Wear protective gloves/protective clothing/eye protection/face protection.
[In case of inadequate ventilation] wear respiratory protection.
IF ON SKIN: Wash with plenty of water.
IF INHALED: Remove person to fresh air and keep comfortable for breathing.
8 If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present
and easy to do. Continue rinsing.
IF exposed or concerned: Get medical advice/attention.
Call a POISON CENTER/doctor if you feel unwell.
Get medical advice/attention if you feel unwell.
Specific treatment (see on this label).
If skin irritation or rash occurs: Get medical advice/attention.
If eye irritation persists: Get medical advice/attention.
If experiencing respiratory symptoms: Call a POISON CENTER/doctor.

Take off contaminated clothing and wash it before reuse.

(Contd. on page 10)

SEM

Printing date 06/28/2017 Reviewed on 06/20/2017

Trade name: 40502, 40507 QUICK SET 50 Adhesive

(Contd. of page 9)

P363 Wash contaminated clothing before reuse.

P403+P233 Store in a well-ventilated place. Keep container tightly closed.

P405 Store locked up.

P501 Dispose of contents/container in accordance with local/regional/national/international

regulations.

· Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- · Department issuing SDS: Environment protection department.
- · Date of preparation / last revision 06/28/2017 / 8
- · Abbreviations and acronyms:

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)

ICAO: International Civil Aviation Organisation

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International

Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation IATA: International Air Transport Association

ACGIH: American Conference of Governmental Industrial Hygienists

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

NFPA: National Fire Protection Association (USA)

HMIS: Hazardous Materials Identification System (USA)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic vPvB: very Persistent and very Bioaccumulative

NIOSH: National Institute for Occupational Safety

OSHA: Occupational Safety & Health

TLV: Threshold Limit Value

PEL: Permissible Exposure Limit

REL: Recommended Exposure Limit

Skin Irrit. 2: Skin corrosion/irritation - Category 2

Eye Irrit. 2A: Serious eye damage/eye irritation – Category 2A

Resp. Sens. 1: Respiratory sensitisation - Category 1

Skin Sens. 1: Skin sensitisation - Category 1

Carc. 2: Carcinogenicity – Category 2

STOT SE 3: Specific target organ toxicity (single exposure) – Category 3 STOT RE 2: Specific target organ toxicity (repeated exposure) – Category 2

* Data compared to the previous version altered.

USA