

DESCRIPTION

Zincweld is a zinc-based weld-through primer that provides superior corrosion protection between welded substrates while minimizing heat affected zones and welding spatter.

FEATURES

- Zinc-based formula for best-in-class corrosion protection
- Enhanced adhesion to bare metal for added corrosion protection
- No flaking or peeling
- Not affected by cavity wax
- Minimizes the heat affected zone while welding
- Low weld spatter formula
- Smooth spraying and easy covering
- Compatible with MIG and STRSW welding

SUITABLE SUBSTRATES

- Bare metal

TYPICAL PROPERTIES

Part:	Product Name:	Color:	Container:
40773	Zincweld	Silver	16 oz. Aerosol

Coverage at 1 mil:	19 sq.ft. per can
MIR:	1.0 Max
Category:	WTP

Check local VOC regulations to ensure compliance of all products in your area.

HANDLING AND APPLICATION



PREPARATION:

1. Clean surface with **SEM Solve** or **XXX Universal Surface Cleaner**.
2. Sand with P80 grit paper. Surface must be bare metal.
3. Blow off dust and re-clean with **SEM Solve** or **XXX Universal Surface Cleaner**.



MIXING:

Shake can vigorously for one minute after mixing ball begins to rattle to ensure color uniformity and to prevent clogging. For best results, use only when can temperature is approximately 70°F (21°C).



Check local VOC regulations to ensure compliance of all products in your area.



APPLICATION:

Coats:	2 medium wet coats to both surfaces
Flash Time Between Coats:	3 – 5 minutes
Time to Weld:	20 minutes

Note: Remove any excess **Zincweld™** from exposed surfaces prior to applying any filler, primer or paint; otherwise lifting will occur.

Remove or scratch **Zincweld** from plug weld areas prior to performing MIG weld applications for maximum performance.

If clogging develops, remove spray button with a twisting motion and clean with **XXX Universal Gun Cleaner** or material compliant with VOC regulations in your area. Do not stick pin or other object into can. Gently replace spray button with top of can and spray button pointed away from you.



After each use, turn can upside down and spray several seconds to clear spray tip.



STORAGE:

Zincweld should be stored in a cool, dry place with adequate ventilation away from heat, sparks and flames. The shelf life for **Zincweld** is 18 months when stored under normal conditions.

RELATED PRODUCTS:

Part:	Product Name:	Size:
38371	SEM Solve	Gallon
38373	SEM Solve	20 oz. Aerosol
38374	SEM Solve	Square Quart
38375	SEM Solve	5 Gallon
77763	XXX Universal Gun Cleaner	20 oz. Aerosol
77771	XXX Universal Surface Cleaner	Gallon
77774	XXX Universal Surface Cleaner	Quart