

DESCRIPTION

MultiMax is a multi-purpose aerosol enamel for exterior or interior use on metal, wood, fiberglass and rigid plastic.

FEATURES

- Outstanding coverage
- Excellent filling properties
- Durable, fast drying finish
- Great adhesion
- Professional finish

SUITABLE SUBSTRATES

- Metal
- Wood
- Fiberglass
- Rigid plastic

TYPICAL PROPERTIES

Part:	Product Name:	Color:	Container:
61013	MultiMax	Flat Black	16 oz. Aerosol
61023	MultiMax	Semi-Gloss Black	16 oz. Aerosol
61033	MultiMax	Gloss Black	16 oz. Aerosol
61043	MultiMax	Aluminum	16 oz. Aerosol
61073	MultiMax	Clear	16 oz. Aerosol
61083	MultiMax	Red Oxide Primer	16 oz. Aerosol
61093	MultiMax	Gloss White	16 oz. Aerosol
61103	MultiMax	Gray Primer	16 oz. Aerosol
61113	MultiMax	Chassis Gray	16 oz. Aerosol

Regulatory VOC:	4.45-4.75 #/gal (535-570 g/L)
Actual VOC:	3.63-4.58 #/gal (436-550 g/L)
MIR 61023, 61033, 61043, 61113, 61093:	< 1.4
Category 61023, 61033, 61043, 61113, 61093:	NFP
MIR/Category 61013:	< 1.2 FCP
MIR/Category 61073:	< 1.1 CCP
MIR/Category 61083, 61103:	< 1.2 PCP



Check local VOC regulations to ensure compliance of all products in your area.

Check local VOC regulations to ensure compliance of all products in your area.

HANDLING AND APPLICATION

PREPARATION:

1. Clean surface thoroughly and dry.
2. Sand surface with 220-320 grit sandpaper.
3. Blow or wipe off dust and re-clean.

MIXING:

Agitate thoroughly! Shake can vigorously for one minute after mixing ball rattles to ensure color uniformity and to prevent clogging. For best results, use only when can temperature is approximately 70°F (21°C).

APPLICATION:

1. Prime any bare metal with **MultiMax Primer**.
2. Mask adjacent areas to protect from overspray
3. If priming, sand with 320 grit sandpaper. Allow primer to dry 30 minutes before top coating with **MultiMax**.
4. If not priming, test a small area for compatibility.
5. Apply light “mist” coats, allowing 5-10 minutes between coats.
6. If applying **MultiMax Clear**, allow **MultiMax** to dry 3 hours before clear coating.

Note:

If clogging develops, remove spray button with a twisting motion and clean with material compliant with VOC regulations in your area. Do not stick pin or other object into can. Gently replace spray button with top of can and spray button pointed away from you.

After each use, turn can upside down and spray several seconds to clear spray tip.

STORAGE:

MultiMax should be stored in a cool, dry place with adequate ventilation away from heat, sparks and flames. The shelf life for **MultiMax** is 3 years when stored under normal conditions.



IMPORTANT

Due to variation in computer monitors, the colors displayed can only serve as reference.



FORMERLY
PROMAX

MULTIMAX™




61013 **FLAT BLACK**



61083 **RED OXIDE PRIMER**



61023 **SEMI-GLOSS BLACK**



61093 **GLOSS WHITE**




61033 **GLOSS BLACK**




61103 **GRAY PRIMER**



61043 **ALUMINUM**



61113 **CHASSIS GRAY**



61073 **CLEAR**