

DESCRIPTION

XXX Adhesion Promoter increases adhesion of top coat materials to surfaces such as plastics, aluminum, steel, glass, chrome and previously painted surfaces.

FEATURES

- Superior bonding properties
- Top coat with most refinish products
- Excellent on olefin based plastics
- Easy to apply
- 3 convenient sizes

SUITABLE SUBSTRATES

- Olefin-based plastics
- Aluminum
- Steel
- Glass
- Chrome
- Previously painted surfaces

TYPICAL PROPERTIES

Part:	Product Name:	Color:	Container:
77721	XXX Adhesion Promoter	Clear	Gallon
77723	XXX Adhesion Promoter	Clear	Aerosol
77724	XXX Adhesion Promoter	Clear	Quart
Regulatory VOC (77721 / 77724):		6.36 #/gl (762.0 g/L)	
Actual VOC (77721 / 77724):		5.13 #/gl (615 g/L)	
MIR:		Category ABT < 1.75	

Check local VOC regulations to ensure compliance of all products in your area.



Check local VOC regulations to ensure compliance of all products in your area.

HANDLING AND APPLICATION

PREPARATION:

1. Clean area with **SEM Soap** (interior plastics) or **Scuff & Clean** (exterior plastics) and a gray scuff pad.
2. Rinse with water and allow to dry.
3. Clean with **Plastic & Leather Prep** or **XXX Universal Surface Cleaner** using a clean, lint free towel and wiping in one direction.
4. Sand non-plastic substrates to be refinished with 400 grit sandpaper.
5. Blow off dust.

APPLICATION:

1. Apply one light coat.
2. Allow 5 minutes flash time followed by one full wet coat.
3. Allow to flash 15 minutes but no longer than 30 minutes before top coating.
4. Refinish with **Color Coat**, **Bumper Coater**, **Marine Vinyl Coat**, **Marine Engine Paint**, all base coats, clear coats, urethanes, acrylic enamels, alkyd enamels and acrylic lacquers.

Note:

Adhesion improves with time. Do not rush to reinstall part.

Note:

If clogging develops, remove spray button with a twisting motion and clean with **XXX Gun Cleaner** or material compliant with VOC regulations in your area. Do not stick pin or other object into can. Gently replace spray button with top of can and spray button pointed away from you.

Note:

After each use, turn can upside down and spray several seconds to clear spray tip.

CLEAN UP:

Use appropriate cleaning materials compliant with VOC regulations in your area.

STORAGE:

XXX Adhesion Promoter should be stored in a cool, dry place with adequate ventilation away from heat, sparks and flames. The shelf life for **XXX Adhesion Promoter** is 5 years when stored under normal conditions.



Check local VOC regulations to ensure compliance of all products in your area.

RELATED PRODUCTS:

Part:	Product Name:	Size:
38351	Plastic & Leather Prep	Gallon
38353	Plastic & Leather Prep	Aerosol
38354	Plastic & Leather Prep	Quart
39362	SEM Soap	16 oz. Tube
38391	Scuff & Clean	Gallon
38398	Scuff & Clean	16 oz. Tube
77771	XXX Universal Surface Cleaner	Gallon
77774	XXX Universal Surface Cleaner	Quart
77743	XXX Gun Cleaner	20 oz. Aerosol
77763	XXX Universal Gun Cleaner	20 oz. Aerosol