



SPRAY MATCH SOLVENT BASED COATING

#16-3395, #C16-3395, #16-4395, #C16-4395, K16-4395

A specialized blend of solvents and propellant which can be used to aerosolize most enamel, lacquer, vinyl, and acrylic paints. The unique cap functions as the paint reservoir during the filling process. There is no prep or cleanup work involved. To be used exclusively with the Z-2500, Z-2501 and Z-2507 Fill One Machines.

Suggested Uses:

Aerosolize custom matched colors
Quickly touch up damaged areas
Automotive touch up
Maintenance and industrial
OEM applications

Benefits:

Individual cans can be aerosolized
Special colors
No brushes or rollers to clean up
Low odor
Reduced overspray

Packaging:

UPC Code	
Cans per case	12
Shipping weight per case	13.6 lbs.
Container	16 fluid ounce can
Label weight	8 ounces
Shipping Classification	Consumer Commodity ORM-D, UN 1950
Hazard Class	2.1

Properties:

Flammability	Extremely Flammable
Flash point	-19F
Specific Gravity	0.69
MIR value	0.74
HAPs content	0%
Storage Temperature	40-100F
Application Temperature	50-90F
Shelf life Unfilled:	Guaranteed for 2 years

Dry Time:

Not Applicable until modified

Gloss:

Not applicable until modified

Filled cans should be used as soon as possible.

Available Colors:

While Seymour of Sycamore has tested paints from many different manufacturers, compatibility with the **Solvent Blend** aerosols can not be guaranteed. Additional label information and/or warnings may be required if the injected product's safety information varies from that of the **Solvent Blend**. Filling aerosol cans is a manufacturing process, and the manufacturer is ultimately responsible for complying with hazardous labeling standards.