

# **Installation Instructions** *Standard Top*

(Part #, 908xx) 1987-1991 Jeep Wranglers

If your Wrangler does not have a soft top Windshield Channel, your installation requires the purchase of an aftermarket Windshield Channel (Smittybilt Part # 90101)

#### **INSTALLATION INSTRUCTIONS:**

**Included Components:** 

1- Brief

Before you begin, the temperature of the Brief should be above 70 degrees Fahrenheit. We suggest laying the Brief in the sunlight for 1 hour before installation.

1. Locate the front edge and fold over (Figure 1).





2. Place the Brief on top of Jeep. Insert folded edge into Windshield Channel, working from one side of vehicle to the other (Figures 2 & 3).

Figure 2



Figure 3





## **Installation Instructions**

Standard Top (Part #, 908xx) 1987-1991 Jeep Wranglers

3. Lay the back of the Brief over the central roll bar and pull the rear corner straps. Loop the straps around the rear side roll bar and attach to mating buckle (Figure 4).

Figure 4



4. Locate the Velcro straps on each side of the roll bar. Wrap the straps around roll bar and fasten. Do both the driver and passenger sides of the vehicle (Figure 5).

Figure 5



 Locate the center strap along the central roll bar. Run the center strap around the rear and under the central roll bar forward to the Footman Loop near the top center of the windshield. Run strap through Footman Loop and feed strap through its buckle securely (Figure 6).

Figure 6





### **Installation Instructions**

Standard Top (Part #, 908xx) 1987-1991 Jeep Wranglers

6. Re-adjust Velcro and tighten all straps to assure a wrinkle-free fit.

#### **Care and Maintenance Information**

To keep your product looking new and for the maximum possible wear, it requires periodic cleaning and maintenance.

**FABRIC** – The fabric should be washed using soap, warm water and a soft bristle brush. Rinse with clear water making sure to remove all soap.

**WINDOWS** – DO NOT use a brush on the windows. Wash the windows with a well water soaked sponge or soft cloth and a mild dishwashing detergent. Never wipe the windows when they are dry.

**ZIPPERS** – To keep the zippers operating smoothly keep them clean and lubricated by using a silicone type of lubricant.

**SNAPS** – Keeping the snaps cleaned and lubricated with silicone will help prevent the snaps from sticking.