



Installation Instructions
Replacement Top (Part # 987xx)
86-94 Suzuki Sidekick/Geo Tracker

Note: Please read instructions entirely before installing this product.

Step 1: Remove OEM top (if equipped). Remove the top skin only, not the bow assembly. Fold the front header back. (Fig A) Remove the fiberglass rod in the rear window for later use.

Step 2: Attach the rear window to top. Drape the new top over the vehicle and bow assembly. (Fig B)



(Fig A)



(Fig B)

Step 3: Slide the front of the top over front header. (Fig C) Hook the five clips into the slots on the bottom of the header. Its easier to clip the middle three first and then the ones on each side. (Fig D)



(Fig C)



(Fig D)



Installation Instructions
Replacement Top (Part # 987xx)
86-94 Suzuki Sidekick/Geo Tracker

Step 4: Snap the rear five snaps on the top to the snaps on the rear bow. (Fig E)

Step 5: Attach and hook the rear plastic corner on the top onto the corners of the vehicle. (Fig F)



(Fig E)



(Fig F)

Step 6: Pull the side window retainer bar outward away from vehicle. Separate the Velcro around the window on the top. Insert the front part of the retainer bar into the window and secure with the Velcro. Then proceed to fit the corner of the retainer into the corner of the window and then slide the bottom portion of the retainer bar into the window and secure with the Velcro (Fig G)
Note: Use caution when pulling the retainer bar outward in order not to break the factory clip its secured into. There is also a web strap on the inside that needs to be disconnected.



(Fig G)



(Fig H)



Installation Instructions
Replacement Top (Part # 987xx)
86-94 Suzuki Sidekick/Geo Tracker

Step 7: Locate the straps on the side of the top near the center sports bar. Pull them forward and slide through the loops on the end of tension assembly located near the base of the front header bar. (Fig H) Pull strap back and snap together.

Step 8: Locate the flap with snaps in the center of the top. This folds over and snaps to the center sport bar around the down light. (Fig I) **Note:** The strap is used to secure the windshield header when you have it folded back.



(Fig I)



(Fig J)

Step 9: Push the side windows back towards the vehicle and latching the retainer bar into the factory bracket located on the vehicle. Secure inside with retainer bar strap also. (Fig J, K)



(Fig K)



(Fig L)



Installation Instructions
Replacement Top (Part # 987xx)
86-94 Suzuki Sidekick/Geo Tracker

Step 10: Slide the rear window fiberglass rod from your factory top through the bottom of your new window. (Fig L) Hook the rear retainer bar into the center bracket of the tailgate first and then proceed to the side brackets. **Note:** It may be easier if you remove your spare tire.

Step 11: Pull down the front header bar and secure with the factory latches. (Fig M) Installation is now complete. (Fig N)



(Fig M)



(Fig N)