

Surface Mounts Light



Black Housing

Single

Black Housing, 10-16 Vdc Chrome Housing, 10-16 Vdc White Housing, 10-16 Vdc

Black Housing, 10-30 Vdc Chrome Housing, 10-30 Vdc White Housing, 10-30 Vdc

Black Housing, 10-16 Vdc, ECE 65 Certified Chrome Housing, 10-16 Vdc, ECE 65 Certified White Housing, 10-16 Vdc, ECE 65 Certified Xylex Lens; amber, blue and red on all housing colors

Black Housing, 10-30 Vdc, ECE R65/EMC Certified Chrome Housing, 10-30 Vdc, ECE R65/EMC Certified White Housing, 10-30 Vdc, ECE R65/EMC Certified Amber, blue and red on all housing colors

Single Stop/Tail

Black Housing, 10-30 Vdc, Red LEDs Black Housing, 10-30 Vdc, Amber LEDs Chrome Housing, 10-30 Vdc, Red LEDs White Housing, 10-30 Vdc, Red LEDs White Housing, 10-30 Vdc, Blue LEDs

Single Spot

Black Housing, 10-30 Vdc, White LEDs Chrome Housing, 10-30 Vdc, White LEDs White Housing, 10-30 Vdc, White LEDs #EGHST2(x)-12 #EGHST2(x)C-12 #EGHST2(x)W-12

#EGHST2(x) #EGHST2(x)C #EGHST2(x)W

#EGHSTE2(x)B-EU #EGHSTE2(x)C-EU #EGHSTE2(x)W-EU

#EGHSTE2(x)B #EGHSTE2(x)C #EGHSTE2(x)W

#EGHSTT2RB #EGHSTT2AB #EGHSTT2RC #EGHSTT2RW #EGHSTT2BW

#EGHSTS2W #EGHSTS2WC #EGHSTS2WW



Dual Stacked

Black Housing, 10-16 Vdc Chrome Housing, 10-16 Vdc White Housing, 10-16 Vdc Black Housing, 10-30 Vdc Chrome Housing, 10-30 Vdc White Housing, 10-30 Vdc Black Housing

#EGHST6(x)B-12 #EGHST6(x)C-12 #EGHST6(x)W-12 #EGHST6(x)B #EGHST6(x)C #EGHST6(x)W

Features

- Sleek, narrow surface mount light, fits almost anywhere
- Premium optics offer optimal power and brightness
- Includes rubber mounting gasket and mounting hardware with 3-wire cable



Chrome Housing



White Housing

 Replace (x) in the Order Number for Color Selection

 Solid Colors: A =
 B =
 G =
 R =
 W =

 Dual/Split Colors: A =
 B =
 G =
 H =
 J =
 M =
 N =
 P =
 R =
 W =

Technical Specifications

FLASH PATTERNS	33 flash patterns
LIGHT SYNC	4 single and 2 dual-stacked
LED COUNT	Single: 6 LEDs
	Dual Stacked: 12 LEDs (6 per module)
INPUT VOLTAGE	10-16 Vdc or 10-30 Vdc
CURRENT DRAW	Single: 0.75 Amps (flash pattern dependent)
	Dual Stacked: > 1.5 Amps
OPERATING TEMPERATURE	-40° C to +65° C / -40° F to +149° F
DIMENSIONS	Single/Stop Tail: 5.7" (14 cm) L x 1.06" (2.7 cm) H x 1.8" (4.6 cm) D
	Dual Stacked: 5.4" (14 cm) L x 2.4" (6.1 cm) H x 1' (2.5 cm) D
MOUNTING	Single: On 4.9" (12.4 cm) centers
	Dual Stacked: 4.85" (12 cm) centers
CERTIFICATIONS	SAE J595, Class 1 certified; Article 22, CA Title 13 compliant;
	Two, ECE 65 certified and 72/245/EEC, EMC certified
WARRANTY	Five-year

ACCESSORIES

Coundan



Light not included.

- a. Side Mirror Grommet (pair), Ford Interceptor Sedan, 2013+ **#PGHSTSMMFPI**
- b. Behind the grille installation, includes driver and passenger sides, Chevy Tahoe, 2015 **#PNFSLDGSB-TH**
- c. Single Surface Mount Vertical License Plate

#PNFSLBRK2LPV







Features

- Sleek, narrow surface mount light, fits almost anywhere
- Premium optics offer optimal power and brightness
- Includes rubber mounting gasket and mounting hardware with 3-wire cable



Chrome Housing



White Housing



Surface Mounts



Black Housing

Single

Black Housing, 10-16 Vdc Chrome Housing, 10-16 Vdc White Housing, 10-16 Vdc

Black Housing, 10-30 Vdc Chrome Housing, 10-30 Vdc White Housing, 10-30 Vdc

Black Housing, 10-16 Vdc, ECE 65 Certified Chrome Housing, 10-16 Vdc, ECE 65 Certified White Housing, 10-16 Vdc, ECE 65 Certified Xylex Lens; amber, blue and red on all housing colors

Black Housing, 10-30 Vdc, ECE R65/EMC Certified Chrome Housing, 10-30 Vdc, ECE R65/EMC Certified White Housing, 10-30 Vdc, ECE R65/EMC Certified Amber, blue and red on all housing colors

Single Stop/Tail

Black Housing, 10-30 Vdc, Red LEDs Black Housing, 10-30 Vdc, Amber LEDs Chrome Housing, 10-30 Vdc, Red LEDs White Housing, 10-30 Vdc, Red LEDs White Housing, 10-30 Vdc, Blue LEDs

Single Spot

Black Housing, 10-30 Vdc, White LEDs Chrome Housing, 10-30 Vdc, White LEDs White Housing, 10-30 Vdc, White LEDs

#EGHST2(x)-12 #EGHST2(x)C-12 #EGHST2(x)W-12

#EGHST2(x) #EGHST2(x)C #EGHST2(x)W

#EGHSTE2(x)B-EU #EGHSTE2(x)C-EU #EGHSTE2(x)W-EU

#EGHSTE2(x)B #EGHSTE2(x)C #EGHSTE2(x)W

#EGHSTT2RB #EGHSTT2AB #EGHSTT2RC #EGHSTT2RW #EGHSTT2BW

#EGHSTS2W #EGHSTS2WC #EGHSTS2WW



Dual Stacked

Black Housing, 10-16 Vdc Chrome Housing, 10-16 Vdc White Housing, 10-16 Vdc Black Housing, 10-30 Vdc Chrome Housing, 10-30 Vdc White Housing, 10-30 Vdc Black Housing

#EGHST6(x)B-12 #EGHST6(x)C-12 #EGHST6(x)W-12 #EGHST6(x)B #EGHST6(x)C #EGHST6(x)W _ Replace (x) in the Order Number for Color Selection_

Solid Colors: $A = \blacksquare B = \blacksquare G = \blacksquare R = \blacksquare W = \Box$

Technical Specifications

•	
FLASH PATTERNS	33 flash patterns
LIGHT SYNC	4 single and 2 dual-stacked
LED COUNT	Single: 6 LEDs
	Dual Stacked: 12 LEDs (6 per module)
INPUT VOLTAGE	10-16 Vdc or 10-30 Vdc
CURRENT DRAW	Single: 0.75 Amps (flash pattern dependent)
	Dual Stacked: > 1.5 Amps
OPERATING TEMPERATURE	-40° C to +65° C / -40° F to +149° F
DIMENSIONS	Single/Stop Tail: 5.7" (14 cm) L x 1.06" (2.7 cm) H x 1.8" (4.6 cm) D
	Dual Stacked: 5.4" (14 cm) L x 2.4" (6.1 cm) H x 1' (2.5 cm) D
MOUNTING	Single: On 4.9" (12.4 cm) centers
	Dual Stacked: 4.85" (12 cm) centers
CERTIFICATIONS	SAE J595, Class 1 certified; Article 22, CA Title 13 compliant;
	Two, ECE 65 certified and 72/245/EEC, EMC certified
WARRANTY	Five-year



single surface mount brackets

Light not included.

ACCESSORIES

- a. Behind the grille installation, includes driver and passenger sides, Chevy Tahoe, 2015
- b. Single Surface Mount Vertical License Plate

#PNFSLDGSB-TH

#PNFSLBRK2LPV





Dual Stacked Surface Mount (SM) Black Housing: #EGHST6(x)B Cł rome Housing: #EGHST6(x)C White Housing: #EGHST6(x)W



NEW/



White Housing shown.



Upper module illuminated in Red LEDs in chrome housing shown.





- The original GHOST light now in a Dual Stacked SM (surface mount)
- Die cast aluminum housing in your choice of Black, White or Chrome
- Available in 15 solid or split colors
- **Premium optics offer the most power & brightness** increasing safety for emergency workers & civilians alike
- *12 powerful Gen3 LEDs* (6 per module) offer maximum brightness, color consistency & reliability
- *Moisture & vibration resistant* for heavy duty & exterior applications
- *Light Sync Technology to synchronize your lights* to alternate the flash patterns or flash simultaneously
- *Includes* Santoprene Rubber Mounting Gasket & Mounting Hardware with 18" of 3-wire Shielded Cable
- Also available in a Single SM, see web or catalog for details

Tech Specs	pecs GHOST™ Dual Stacked SM		
Flash Patterns:	33 Flash Patterns		
Light Sync:	Yes		
Technology:	12 Gen3 LEDs (6 per module)		
Mounting:	ting: Surface Mount on 4.85" (12 cm) centers		
Input Voltage:	:: 10 - 30 Vdc		
Current Draw:	Draw: less than 1.5 amps (flash pattern dependent)		
Dimensions:	<u>W</u> idth x <u>H</u> eight x <u>D</u> epth 5.4" (14 cm) L x 2.4" (61 mm) H x 1" (25 mm) D		
Operating Temp.:	-40° to $+65^{\circ}$ C / -104° to $+149^{\circ}$ F		



NEXUS

new

THINK

- and G

Single Surface Mount Vertical License Plate Bracket

December 2013

Allows nFORCE and Ghost Single Mount lights to adapt to:

Chevry Tahoe Utility 2013+ Rear Dodge Charger 2010+ Ford SUV Utility 2013+ Ford Taurus Sedan 2013+ Front and Rear

Front Front and Rear

nFORCE is the only Perimeter Lighting product line on the market that can be specifically tailored to

your unique requirements.

nFORCE Light Certifications

SAE: J595, Class 1 Certified CA Title 13: Article 22 Compliant EMC Tested and Certified, 72/245/EEC ECE Certified (ECE R65 can only be specified with 9 LED solid color)

The Ghost light features a sleek, narrow surface mount that fits almost anywhere. Also features premium optics that has optimal power and brightness.

Ghost Light Certifications

SAE J595, Class 1 Article 22, CA Title 13 Compliant Two, ECE65, Tested and Certified 72/245/EEC, EMC, Tested and Certified



nFORCE Single Surface Mount

6 LED, Solid or Split Color	#ENFSSS1(x)
9 LED, Solid Color	#ENFSSS2(x)
12 LED, Solid or Dual Color	#ENFSSS3(x)
18 LED, Tri Color - Blue/Red/Amber	#ENFSSS4BRA
18 LED, Tri Color - Blue/Red/White	#ENFSSS4BRW



Black Housing Chrome Housing White Housing

10-30 Vdc #EGHST2(x) #EGHST2(x)C #EGHST2(x)W 10-16 Vdc #EGHST2(x)-12 #EGHST2(x)C-12 #EGHST2(x)W-12

ECE R65/EMC (amber, blue, red only) #EGHSTE2(x)-B #EGHSTE2(x)-C #EGHSTE2(x)-W



March 2015



Bracket Kit for the 2015 Chevy Tahoe nFORCE® Single, FIT and GHOST® Single Surface Mounts



#PNFSLDGSB-TH

(includes both passenger and driver sides | lights are sold separately | behind the grille installation)





Single and FIT Surface Mounts



US and Foreign patents pending

#ENFSSE2(x)



Single Surface

6 LED, Solid or Split Colors	#ENFSSS1(x)
9 LED, Solid Colors	#ENFSSS2(x)
12 LED, Solid or Dual Colors	#ENFSSS3(x)
18 LED, Tri Color - Blue/Red/Amber or Blue/Red/White	#ENFSSS4(xxx)
High Output 9 LED Solid Color - Amber/Amber	#ENFSSS2AA-PC

FIT Surface

3 LED, Solid Colors		#ENF
6 LED, Solid or Dual Colors		#ENF
9 LED, Tri-Colors - Blue/Red/Amber or Blue/Red	d/White	#ENFI

FTSSMS3(x) FTSSMS6(x) FTSSMS9(xxx)

Single Surface Mount



Xylex Lens and ECE R65

9 LED, Solid Colors - Amber, Blue, Red or White

8	Housing Color	10-16 Vdc	10-30 Vdc	ECE 65 Certified/10-16 Vdc (Xylex Lens; amber, blue and red only)	ECER65/EMC Certified/10-30 Vdc (amber, blue and red only)
/	Black	#EGHST2(x)-12	#EGHST2(x)	#EGHSTE2(x)B-EU	#EGHSTE2(x)-B
	Chrome	#EGHST2(x)C-12	#EGHST2(x)C	#EGHSTE2(x)C-EU	#EGHSTE2(x)-C
	White	#EGHST2(x)W-12	#EGHST2(x)W	#EGHSTE2(x)W-EU	#EGHSTE2(x)-W

THINK New Smart Design.

October 2013



This grommet allows the Ghost Light to be mounted to the side mirrors of the 2011+ Ford Interceptor Sedan models. Sold as a pair.

Surface Mount Side Mirror Grommet for the Ford Interceptor Sedan



Mirror Grommet



Lights sold separately.

#PGHSTSMMFPI (pair)

Features

- · Sleek, narrow surface mount light, fits almost anywhere
- Premium optics offer optimal power and brightness
- Includes santoprene rubber mounting gasket and mounting hardware with 18" of 3-wire cable

Certifications: SAE J595 Class 1 Article 22 CA Title 13 Compliant Two ECE65 Tested and Certified and 72/245/EEC EMC Tested and Certified

TECHNICAL SPECIFICATIONS: Ghost Surface Mount Light

FLASH PATTERNS	33 flash patterns
LIGHT SYNC	Yes
TECHNOLOGY	Single: 6 Gen3 LEDs , Dual Stacked: 12 Gen3 LEDs (6 per module)
INPUT VOLTAGE	10 - 16 Vdc or 10 - 30 Vdc
CURRENT DRAW	Single: 0.75 amps (flash pattern dependent), Dual Stacked: less than 1.5 amps
OPERATING TEMPERATURE	-40° to +65° C / -40° to +149° F
LENGTH/DIMENSION	Single/Stop Tail: 5.7" (14 cm) L x 1.06" (2.8 mm) H x 1.8" (4.6 cm) D
	Dual Stacked: 5.4" (14 cm) L x 2.4" (61 mm) H x 1' (2.5 cm) D
WARRANTY	Five-year
SURFACE MOUNTS	Single: On 4.9" (12.4 cm) centers, Dual Stacked: 4.85" (12 cm) centers