

Mini Lightbars: EPL7000 and EPL7100

Features

- > Magnetic mount has cig plug with 2-button switch panel (on, off and flash pattern advance)
 - Red LED indicator light and 10' cord length
 - 4 extra strong magnets each with an 85 pound pull each to prevent the lightbar from slipping or moving
- > Permanent mount with 12' cable with bare wires for hard wire installation
- > Fusion II Technology - optic for a bright, extra wide output
- > Non-volatile memory - recalls last flash pattern used
- > EPL7000, Class 1 certified for blue and red solid colors
- > EPL7100, Class 1 certified for amber color



#EPL7000

Clear Dome, 4 Module

Magnetic with Cig Plug **#EPL7M+(x)C**
 Standard Permanent **#EPL7PD(x)C**
 High Height Permanent **#EPL7HD(x)C**

Amber Dome, Amber LEDs, 4 Module

Magnetic with Cigar Plug **#EPL7M+AA**
 Standard Permanent **#EPL7PDAA**
 High Height Permanent **#EPL7HDAA**

Clear Dome, 4 Module (25 foot cable)

Standard Permanent **#EPL7PF(x)C**
 High Height Permanent **#EPL7HF(x)C**

Amber Dome, 4 Module (25 foot cable)

Standard Permanent **#EPL7PFAA**
 High Height Permanent **#EPL7HFAA**

Replace (x) in the Order Number for Color Selection

Solid Colors: A= ■ B= ■ G= ■ R= ■ W= 											
Dual/Split Colors: D= ■ E= ■ F= ■ H= ■ J= ■ ■ K= ■ ■ L= ■ ■ M= ■ ■ N= ■ ■											
P= ■ ■											



#EPL7100

Permanent Mount, 4 Module

LED Color	Dome Color	Order Number
Amber	Amber	#EPL71PDAA
Amber	Clear	#EPL71PDAC
Amber/White	Clear	#EPL71PDFC
Red/Amber	Clear	#EPL71PDKC
Blue/Amber	Clear	#EPL71PDMC

Magnetic Mount, 4 Module

LED Color	Dome Color	Order Number
Amber	Amber	#EPL71M+AA
Amber	Clear	#EPL71M+AC
Amber/White	Clear	#EPL71M+FC
Red/Amber	Clear	#EPL71M+KC
Blue/Amber	Clear	#EPL71M+MC

Technical Specifications: EPL7000 and EPL7100

INPUT VOLTAGE RANGE	10-16 Vdc
CURRENT DRAW	2 Amps average @ 12.8 Vdc
LED COUNT	24 LEDs
FLASH PATTERNS	28 flash patterns
OPERATING TEMPERATURE	-40° C to +65° C / -40° F to +149° F
DIMENSIONS	14.16" (36 cm) L x 8.27" (21 cm) W x 1.90" (4.8 cm) H
MOUNTS	Magnetic: 2.97" (7.5 cm) Overall height, 0.87" (2.2 cm) clearance Low Permanent: 2.28" (5.8 cm) Overall height 0.38" (1.0 cm) clearance High Permanent: 4.25" (10.8 cm) Overall height 2.35" (6.0 cm) clearance
CERTIFICATIONS	EPL7000: SAE J845 Class 1 certified (blue and red solid colors only) EPL7100: SAE J845 Class 1 certified (amber solid color only)
WARRANTY	Five-year



Mini Lightbars: EPL7000



#EPL7000

Clear Dome, 4 Module

Magnetic with Cig Plug
Standard Permanent
High Height Permanent

#EPL7M+(x)C
#EPL7PD(x)C
#EPL7HD(x)C

Clear Dome, 4 Module (25 foot cable)

Standard Permanent
High Height Permanent

#EPL7PF(x)C
#EPL7HF(x)C

Amber Dome, Amber LEDs, 4 Module

Magnetic with Cigar Plug
Standard Permanent
High Height Permanent

#EPL7M+AA
#EPL7PDAA
#EPL7HDAA

Amber Dome, 4 Module (25 foot cable)

Standard Permanent
High Height Permanent

#EPL7PFAA
#EPL7HFAA

Replace (x) in the Order Number for Color Selection

Solid Colors: A= B= G= R= W=	
Dual/Split Colors: D= E= F= H= J= K= L= M= N=	
P=	

Technical Specifications

INPUT VOLTAGE RANGE	10-16 Vdc
CURRENT DRAW	2 Amps average @ 12.8 Vdc
LED COUNT	24 LEDs
FLASH PATTERNS	28 flash patterns
OPERATING TEMPERATURE	-40° C to +65° C / -40° F to +149° F
DIMENSIONS	14.16" (36 cm) L x 8.27" (21 cm) W x 1.90" (4.8 cm) H
MOUNTS	Magnetic: 2.97" (7.5 cm) Overall height, 0.87" (2.2 cm) clearance Low Permanent: 2.28" (5.8 cm) Overall height 0.38" (1.0 cm) clearance High Permanent: 4.25" (10.8 cm) Overall height 2.35" (6.0 cm) clearance
CERTIFICATIONS	SAE J845 Class 1 certified (blue and red solid colors only)
WARRANTY	Five-year

Features

- > Magnetic mount has cig plug with 2-button switch panel (on, off and flash pattern advance)
 - Red LED indicator light and 10' cord length
 - 4 extra strong magnets each with an 85 pound pull each to prevent the lightbar from slipping or moving
- > Permanent mount with 12' cable with bare wires for hard wire installation
- > Fusion II Technology - optic for a bright, extra wide output
- > Non-volatile memory - recalls last flash pattern used
- > Class 1 certified for blue and red solid colors



Mini Lightbars: EPL7100



#EPL7100

Permanent Mount, 4 Module

LED Color	Dome Color	
Amber	Amber	#EPL71PDAA
Amber	Clear	#EPL71PDAC
Amber/White	Clear	#EPL71PDFC
Red/Amber	Clear	#EPL71PDKC
Blue/Amber	Clear	#EPL71PDMC

Magnetic Mount, 4 Module

LED Color	Dome Color	
Amber	Amber	#EPL71M+AA
Amber	Clear	#EPL71M+AC
Amber/White	Clear	#EPL71M+FC
Red/Amber	Clear	#EPL71M+KC
Blue/Amber	Clear	#EPL71M+MC

Features

- > Magnetic mount has cig plug with 2-button switch panel (on, off and flash pattern advance)
 - Red LED indicator light and 10' cord length
 - 4 extra strong magnets each with an 85 pound pull each to prevent the lightbar from slipping or moving
- > Permanent mount with 12' cable with bare wires for hard wire installation
- > Fusion II Technology - optic for a bright, extra wide output
- > Non-volatile memory - recalls last flash pattern used
- > Class 1 certified for amber color

Technical Specifications

INPUT VOLTAGE RANGE	10-16 Vdc
CURRENT DRAW	2 Amps average @ 12.8 Vdc
LED COUNT	24 LEDs
FLASH PATTERNS	28 flash patterns
OPERATING TEMPERATURE	-40° C to +65° C / -40° F to +149° F
DIMENSIONS	14.16" (36 cm) L x 8.27" (21 cm) W x 1.90" (4.8 cm) H
MOUNTS	Magnetic: 2.97" (7.5 cm) Overall height, 0.87" (2.2 cm) clearance Low Permanent: 2.28" (5.8 cm) Overall height 0.38" (1.0 cm) clearance High Permanent: 4.25" (10.8 cm) Overall height 2.35" (6.0 cm) clearance
CERTIFICATIONS	SAE J845 Class 1 certified (amber solid color only)
WARRANTY	Five-year

up DATE Smart Design.



EPL7100 Mini Lightbar: SAE Class 1 Certified

A new SAE Class 1 certified mini lightbar has been added to the Pinnacle offering.



#EPL7100

Features

- Magnetic mount has Cig plug with 2-button switch panel (on, off and flash pattern advance)
 - Red LED indicator light and 10' cord length
 - 4 extra strong magnets each with an 85 pound pull each to prevent the bar from slipping or moving
- Permanent mount with 12' cable with bare wires for hard wire installation
- Fusion II Technology - optic for a bright, extra wide output
- Non-volatile memory - recalls last flash pattern used

Permanent Mount, 4 Module

LED Color	Dome Color	Product Number
Amber	Amber	#EPL71PDAA
Amber	Clear	#EPL71PDAC
Amber and White	Clear	#EPL71PDFC
Red and Amber	Clear	#EPL71PDKC
Blue and Amber	Clear	#EPL71PDMC

Magnetic Mount, 4 Module (shown above)

LED Color	Dome Color	Product Number
Amber	Amber	#EPL71M+AA
Amber	Clear	#EPL71M+AC
Amber and White	Clear	#EPL71M+FC
Red and Amber	Clear	#EPL71M+KC
Blue and Amber	Clear	#EPL71M+MC

TECHNICAL SPECIFICATIONS

INPUT VOLTAGE RANGE	10-16 Vdc
CURRENT DRAW	2 Amps average to 4 Amps maximum
LED COUNT	24 LEDs
FLASH PATTERNS	28 flash patterns
OPERATING TEMPERATURE	-40° C to +65° C / -40° F to +149° F
DIMENSIONS	14.16" (36 cm) L x 8.27" (21 cm) W x 1.90" (4.8 cm) H
MOUNTS	Magnetic: 2.97" (7.5 cm) Overall height, 0.87" (2.2 cm) clearance Low Permanent: 2.28" (5.8 cm) Overall height 0.38" (1.0 cm) clearance
CERTIFICATIONS	SAE Class 1 certified
WARRANTY	Five-year