



Ø 280 mm

Ø 11"

AMP connector Code 180908
AMP terminal Code 42098-2
Suggested mounting torque: 3(+1/-0) Nm with screw M5
Weight 1,5 Kg. approx.

PRODUCT FEATURES

Waterproof motor, IP 68	✓
Long life	✓
LL and VLL version*	✓
Waterproof connector	✓
Accessories: all the fixing kits	✓

* for OEM applications only.

✓ = Standard feature

✓ = Available upon request

suction

blowing

Static pressure mm H ₂ O	suction			blowing			Static pressure inH ₂ O
	Airflow Portata m ³ /h	Current input Corrente assorbita A	Airflow Portata CFM	Airflow m ³ /h	Current input A	Airflow CFM	
0	1580	8,6	932	1600	7,9	944	0
5	1340	8,9	791	1340	8,6	791	0,2
10	1170	9,4	690	1060	9,2	625	0,4
12,5	940	8,8	555	970	8,9	572	0,5
15	710	9,0	419	840	9,0	496	0,6
17,5	600	8,8	354	690	9,0	407	0,7
20	430	9,3	254	460	9,1	271	0,8
22,5	340	9,2	201	240	8,4	142	0,9
25	190	9,1	112	0	8,7	0	1
30	0	8,8	0				1,2

Test volta ge 13 V. d.c.