



Ø 305 mm

Ø 12"

AMP connector Code 180908  
AMP terminal Code 42098-2  
Suggested mounting torque: 3(+1/-0) Nm with screw M5  
Weight 1,5 Kg. approx.

PRODUCT FEATURES  
CARATTERISTICHE PRODOTTO

suction / aspirante

blowing / soffiante

Waterproof motor, IP 68	✓
Low noise	✓
Long life	✓
LL and VLL version*	✓
Waterproof connector	✓
Accessories: all the fixing kits	✓

Static pressure Pressione statica mm H <sub>2</sub> O	suction / aspirante			blowing / soffiante			Static pressure Pressione statica inH <sub>2</sub> O
	Airflow Portata m <sup>3</sup> /h	Current input Corrente assorbita A	Airflow Portata CFM	Airflow Portata m <sup>3</sup> /h	Current input Corrente assorbita A	Airflow Portata CFM	
0	2078	12,3	1226	2161	10,8	1275	0
5	1845	12,5	1089	1883	11,8	1111	0,2
10	1422	12,6	839	1550	12,5	915	0,4
12	932	11,9	550	1393	12,6	822	0,5
15	739	11,8	436	1078	12,7	636	0,6
17	651	12	384	547	11,4	323	0,7
20	489	12,3	289	417	11,8	246	0,8
22	342	12,2	202	246	12,1	145	0,9
25	0	12,7	0	0	12,6	0	1,0

\* for OEM applications only. ✓ = Standard feature

✓ = Available upon request

Test voltage 13 V. d.c.