

# SPEC-D

*Tuning*

## 2009-2012 FORD F150 FRONT GRILL

### INSTALLATION INSTRUCTIONS



- \*If you experience any difficulties that the instructions did not cover, Please seek assistance at local automotive shop.
- \*Please wear protection before you work on your vehicle.
- \*An assistant is useful when removing the front bumper from your vehicle.
- \*Please be cautious when working with the bumper or any parts belonging to the vehicles' body prevent scratching.
- \*Do not make direct contact with the halogen bulb or the wire assembly until the unit has cooled down after use.

#### TOOLS AND SUPPLIES REQUIRED

½" Drive Ratchet

Phillips Screwdriver

10mm Socket

Trim Pad Remover

Phillips Screwdriver

Trim Pad Remover

If your Headlight is Halo type, you also need:

Wire Stripper

Wire Crimper

4 Blue Quick Splice Wire Connectors

4 Blue Male Quick Wire Connectors

4 Blue Female Quick Wire Connectors

2 Red Wires (8 inch)

2 Black Wires (8 inch)

#### Product Part Numbers:

HG-F15009CVT

HG-F15009JMVT



# 2009-2012 FORD F150 FRONT GRILL

## INSTALLATION INSTRUCTIONS

If you experience any difficulties that the instruction did not cover, Please seek assistance at a local automotive shop

Please wear protection before you work on any vehicle.



An assistant is useful when removing the front bumper from your vehicle.

Please be cautions when working with the bumper or any parts belonging to the vehicles's body to prevent scratching.

Do not make direct contact with the halogen bulbs or the wire assembly until the unit has cooled down after use.



1. (6) 10mm nuts location



2. Remove the (6) 10mm nuts



3. (2) 10mm bolts location



4. Remove the (2) 10mm bolts



5. Pry on the top of the front grill to release



6. Remove the front grill



7. Location of the (6) bolts



8. Remove the (6) bolts from the stock grill



9. Place the (6) bolts in the new grill



10. Place the new grill in the stock location





11. Tighten the (2) 10mm bolts



12. Tighten the (6) 10mm nuts



13. The installation is now complete

