

SPEC-D *Tuning*

2009-UP DODGE RAM 1500 **MESH GRILLE**

INSTALLATION INSTRUCTIONS

If you experience any difficulties that the instruction did not cover, Please seek assistance at a local automotive shop

Please wear protection before you work on any vehicle.



An assistant is useful when removing the front bumper from your vehicle.

Please be cautions when working with the bumper or any parts belonging to the vehicles's body to prevent scratching.

Do not make direct contact with the halogen bulbs or the wire assembly until the unit has cooled down after use.

TOOLS AND SUPPLIES REQUIRED

Trim Pad remover

10mm Socket

¼" Drive Ratchet

Product Part Numbers:

HG-RAM09JM

HG-RAM09C



2009-UP DODGE RAM 1500 MESH GRILLE INSTALLATION INSTRUCTIONS

If you experience any difficulties that the instruction did not cover, Please seek assistance at a local automotive shop

Please wear protection before you work on any vehicle.



An assistant is useful when removing the front bumper from your vehicle.

Please be cautious when working with the bumper or any parts belonging to the vehicle's body to prevent scratching.

Do not make direct contact with the halogen bulbs or the wire assembly until the unit has cooled down after use.



1. 6 plastic clips location



2. Remove 6 plastic clips



3. Remove Plastic Guard



4. 4 10mm bolts location



5. Remove the (4) 10mm bolts



6. Place the new grill in the stock location



7. Remove the front grill



8. Tighten the (4) 10mm screws



9. Replace the plastic guard



10. Replace the (6) plastic clips



11. The installation is now complete

