

# SPEC-D *Turning*

## 2010-UP HYUNDAI GENESIS PROJECTOR HEADLIGHTS INSTALLATION INSTRUCTIONS



- \*If you experience any difficulties that the instructions did not cover, Please seek assistance at local automotive shop.
- \*Please wear protection before you work on your vehicle.
- \*An assistant is useful when removing the front bumper from your vehicle.
- \*Please be cautious when working with the bumper or any parts belonging to the vehicles' body prevent scratching.
- \*Do not make direct contact with the halogen bulb or the wire assembly until the unit has cooled down after use.

### TOOLS AND SUPPLIES REQUIRED

Phillips screwdriver

6" Extension

¼" Drive Ratchet

10mm Socket

8mm Socket

If your Headlight is Halo type, you also need:

Wire Stripper

Wire Cimper

4 Blue Quick Splice Wire Connectors

4 Blue Male Quick Wire Connectors

4 Blue Female Quick Wire Connectors

2 Red Wires (8 inch)

2 Black Wires (8 inch)

### Product Part Numbers:

2LHP-GENS210-TM

2LHP-GENS210G-V2-TM

2LHP-GENS210JM-V2-TM



# 2008-UP HYUNDAI GENESIS PROJECTOR HEADLIGHTS INSTALLATION INSTRUCTIONS

If you experience any difficulties that the instruction did not cover, Please seek assistance at a local automotive shop

Please wear protection before you work on any vehicle.



An assistant is useful when removing the front bumper from your vehicle.

Please be cautious when working with the bumper or any parts belonging to the vehicle's body to prevent scratching.

Do not make direct contact with the halogen bulbs or the wire assembly until the unit has cooled down after use.



1. (4) plastic clips location



2. Remove the (4) plastic clips



3. Remove the 8mm screw



4. (8) plastic clips location



5. Remove the (8) plastic clips



6. Remove the front bumper



7. Remove the front bumper



8. Remove the (2) 10mm bolts



10. Remove the (2) 10mm bolts



11. Remove the plastic bracket



11. Remove the (2) 10mm bolts



12. Remove the (2) 10mm bolts



13. Remove the stock headlight and disconnect the headlight harness



14. Connect the headlight harness to the new headlight  
Please see the Halo and L.E.D installation instruction  
If your headlights don't have HALO or L.E.D. You can skip it



15. Tighten the (2) 10mm bolts



16. Tighten the (2) 10mm bolts



17. Tighten the (2) 10mm bolts



18. Tighten the (2) 10mm bolts



19. Replace the front bumper



20. Replace the (8) plastic clips



21. Tighten the 8mm screw



22. Replace the (4) plastic clips



23. Please repeat the steps in order from 1 to 22 for the opposite side



24. The installation is now complete

