

SPEC-D *Tuning*

2002-2009 CHEVROLET TRAILBLAZER PROJECTOR HEADLIGHTS INSTALLATION INSTRUCTIONS

If you experience any difficulties that the instruction did not cover, Please seek assistance at a local automotive shop

Please wear protection before you work on any vehicle.



An assistant is useful when removing the front bumper from your vehicle.

Please be cautious when working with the bumper or any parts belonging to the vehicle's body to prevent scratching.

Do not make direct contact with the halogen bulbs or the wire assembly until the unit has cooled down after use.

TOOLS AND SUPPLIES REQUIRED



Handy Remover Tool

Pliers

Product Part Numbers:

2LHP-TBLZ02JM-V2-RS

2LHP-TBLZ02G-V2-RS

2LHP-TBLZ02-V2-RS



2002-2009 CHEVROLET TRAILBLAZER PROJECTOR HEADLIGHTS INSTALLATION INSTRUCTIONS

If you experience any difficulties that the instruction did not cover, Please seek assistance at a local automotive shop

Please wear protection before you work on any vehicle.



An assistant is useful when removing the front bumper from your vehicle.

Please be cautions when working with the bumper or any parts belonging to the vehicles's body to prevent scratching.

Do not make direct contact with the halogen bulbs or the wire assembly until the unit has cooled down after use.



1. Before



2. Release the front grill retaining clips



3. Release the front grill retaining clips



4. Release the front grill retaining clips



5. Remove the front grill



6. Release the (2) headlight retainers by the pulling upwards



7. Remove the factory headlight



8. Disconnect the headlight harness



9. Remove the turn signal light socket



10. Remove the parking light socket



11. Connect headlight harness

Please see the " L. E. D. headlights installation instructions"
If your headlights don't have L.E.D. You can skip the installation instruction.



12. Place the new headlight in the stock location



13. Place the new headlight into the position



14. Lock the new headlight in place with the (2) headlight retainers



15. Replace the front grill
Please repeat the steps from 1 to 15 for the opposite side



16 The Installation now is complete