

SPEC-D *Tuning*

2003-2005 NISSAN 350Z PROJECTOR HEADLIGHTS INSTALLATION INSTRUCTIONS

If you experience any difficulties that the instruction did not cover, Please seek assistance at a local automotive shop

Please wear protection before you work on any vehicle.



An assistant is useful when removing the front bumper from your vehicle.

Please be cautious when working with the bumper or any parts belonging to the vehicle's body to prevent scratching.

Do not make direct contact with the halogen bulbs or the wire assembly until the unit has cooled down after use.

TOOLS AND SUPPLIES REQUIRED

1/4" Drive Ratchet

Trim Pad Remover

6" Extension

10mm Socket

Phillips Screwdriver

Product Part Numbers:

2LHP-350Z03JM-TM

2LHP-350Z03G-TM

2LHP-350Z03-TM



2003-2005 NISSAN 350Z PROJECTOR HEADLIGHTS INSTALLATION INSTRUCTIONS

If you experience any difficulties that the instruction did not cover, Please seek assistance at a local automotive shop

Please wear protection before you work on any vehicle.



An assistant is useful when removing the front bumper from your vehicle.

Please be cautions when working with the bumper or any parts belonging to the vehicles's body to prevent scratching.

Do not make direct contact with the halogen bulbs or the wire assembly until the unit has cooled down after use.



1. (10) 10mm bolts location



2. Remove the (10) 10mm bolts



3. Pull aside the inner fender liner



4. Remove the (2) phillips head screws



5. Phillips head screw location



6. Remove the phillips head screw



7. (6) plastic clips location



8. Remove the (6) plastic clips



9. Remove the front bumper



10. 10mm bolt location



11. Remove the 10mm bolt



12. (2) 10mm bolts location



13. Remove the (2) 10mm bolts



14. 10mm bolt location



15. Remove the 10mm bolt



16. Unplug the headlight harness



17. Remove the headlight



18. Plug in the new headlight to the headlight harness



19. Place the new headlight into the stock location
Please see the Halo and L.E.D installation instruction
If your headlights don't have HALO or L.E.D. You can skip it



20. Tighten the (2) 10mm bolts



21. Tighten the 10mm bolt



22. Tighten the 10mm bolt



23. Replace the front bumper



24. Replace the (6) plastic clips



25. Tighten the phillips head screw



26. Tighten the (2) phillips head screws



27. Tighten the (10) 10mm bolts
Please repeat the steps in order from 1 to 27 for
the opposite side



28. The installation is now complete