Installation & CARE



INNOVATE

PERFESSIONAL

SERVI

2008-2010 FORD F250 F350 F450 PROJECTOR HEADLIGHTS INSTALLATION INSTRUCTIONS

BEFORE INSTALLATION:

- If you experience any difficulties that the instructions did not cover, please seek assistance at a local automotive shop.
- · Please wear proper protective equipment before you work on any vehicle.
- · An assistant is recommended when removing the front bumper from your vehicle.
- · Please be cautious when working with the bumper or any parts belonging to the vehicle's body to prevent scratching.
- · Do not make direct contact with the halogen bulbs or the wire assembly until the unit has cooled down after use.

TOOLS AND SUPPLIES REQUIRED

7 mm socket Plastic Pry bar 1/2" Socket Extension

PRODUCT NUMBER

2LHP-F25008-TM 2LHP-F25008G-TM 2LHP-F25008JM-TM 2LHP-F25008BK-TM



LET'S START THE INSTALLATION



Remove the two 7mm headlight mounting bolts near the radiator



Remove the 7mm headlight mounting bolt at the bottom of the headlight



Remove the 7mm headlight mounting bolt at the top of the headlight



Unseat the factory headlight housing



Disconnect the headlight harness and remove the factory headlight housing



Remove the parking light socket and the signal light socket from the factory headlight



Reinstall the parking light socket and the signal light socket to the new headlight housing



Install the wire connector to connect the LED Halo wires to the car parking light, white wire to positive and black wire to negative



Connect the headlight harness



Seat the new headlight assembly in place



Reinstall the two 7mm headlight mounting bolts near the radiator



Reinstall the 7mm headlight mounting bolt at the top of the headlight



Reinstall the 7mm headlight mounting bolt at the bottom of the headlight



Please repeat the steps from 1 to 13 for the opposite side



Close the hood to complete installation



Installation & CARE



2008-2010 FORD F250 F350 F450 PROJECTOR HEADLIGHTS INSTALLATION INSTRUCTIONS

BEFORE INSTALLATION:

- If you experience any difficulties that the instructions did not cover, please seek assistance at a local automotive shop.
- · Please wear proper protective equipment before you work on any vehicle.
- · An assistant is recommended when removing the front bumper from your vehicle.
- · Please be cautious when working with the bumper or any parts belonging to the vehicle's body to prevent scratching.
- Do not make direct contact with the halogen bulbs or the wire assembly until the unit has cooled down after use.

2008-2010 FORD F250 F350 F450 PROJECTOR HEADLIGHTS INSTALLATION INSTRUCTIONS

