

SPEC-D *Tuning*

2000-2005 IMPALA PROJECTOR HEADLIGHTS INSTALLATION INSTRUCTIONS

If you experience any difficulties that the instruction did not cover, Please seek assistance at a local automotive shop

Please wear protection before you work on any vehicle.



An assistant is useful when removing the front bumper from your vehicle.

Please be cautious when working with the bumper or any parts belonging to the vehicle's body to prevent scratching.

Do not make direct contact with the halogen bulbs or the wire assembly until the unit has cooled down after use.


TOOLS AND SUPPLIES REQUIRED

 Trim Pad Remover

If your Headlight is Halo type, you also need:

 Wire Stripper

 Wire Crimper

 4 Blue Quick Splice Wire Connectors

 4 Blue Male Quick Wire Connectors

 4 Blue Female Quick Wire Connectors

 2 Red Wires (8 inch)

 2 Black Wires (8 inch)

Product Part Numbers:

2LHP-IPA00JM-TM

2LHP-IPA00G-TM

2LHP-IPA00-TM



CHEVY IMPALA PROJECTOR HEADLIGHTS INSTALLATION INSTRUCTIONS

If you experience any difficulties that the instruction did not cover, Please seek assistance at a local automotive shop

Please wear protection before you work on any vehicle.



An assistant is useful when removing the front bumper from your vehicle.

Please be cautious when working with the bumper or any parts belonging to the vehicle's body to prevent scratching.

Do not make direct contact with the halogen bulbs or the wire assembly until the unit has cooled down after use.



1. Before



2. (3) plastic clips location



3. Remove the (3) plastic clips



4. Remove the plastic cover



5. Remove the (2) headlight retainers



6. Remove the factory headlight



7. Disconnect the headlight harness



8. Connect the headlight harness to the new headlight

Please see the "L. E. D. and Halo head lights installation instructions"
If your head lights don't have L.E.D. and halo You can skip the installation instruction.



9. Place the new headlight in the factory location



10. Lock the new headlight in place with the (2) headlight retainers



11. Replace the plastic cover



12. Replace the (3) plastic clips
Please repeat the steps from 1 to 12 for the opposite side



13. The installation now is complete