

SPEC-D *Tuning*

2000-2001 NISSAN MAXIMA PROJECTOR HEADLIGHTS INSTALLATION INSTRUCTIONS



If you experience any difficulties that the instruction did not cover, Please seek local auto shop for advise. Please wear protection before you work on your vehicle.

An assistant is helpful when removing the front bumper.

Please be careful while working with the bumper or body part to avoid scratching.

Do not make direct contact with the halogen bulb or the wire assembly until the unit has cooled down after use.

TOOLS AND SUPPLIES REQUIRED

¼" Drive Ratchet

10mm Socket

Handy Remover

Trim Pad Remover

If your Headlight is Halo type, you also need:

Wire Stripper

Wire Crimper

4 Blue Quick Splice Wire Connectors

4 Blue Male Quick Wire Connectors

4 Blue Female Quick Wire Connectors

2 Red Wires (8 inch)

2 Black Wires (8 inch)

Product Part Numbers:

LHP-MAX00JM-TM

LHPIMAX00-TM



2000-2001 NISSAN MAXIMA PROJECTOR HEADLIGHTS INSTALLATION INSTRUCTIONS



If you experience any difficulties that the instruction did not cover, Please seek local auto shop for advise.
Please wear protection before you work on your vehicle.
An assistant is helpful when removing the front bumper.
Please be careful while working with the bumper or body part to avoid scratching.
Do not make direct contact with the halogen bulb or the wire assembly until the unit has cooled down after use.



1. Remove four clips



2. Remove two bolts



3. Pull the headlight out slightly



4. Remove the driving light socket and disconnect headlight bulb harness



5. Have the new projector ready and put back the driving light socket and connect headlight harness
Please see the Halo and L.E.D installation instruction
If your headlights don't have HALO or L.E.D. You can skip it



6. Make sure the new projector headlights are secure



7. Screw back the two 10mm headlight bolts



8. Put back the four clips



9. Please repeat the picture order from 1 to 9 for the opposite side



10. The installation is now complete