

SPEC-D *Turning*

2009-2015 HONDA PILOT **ROOF RACK** INSTALLATION INSTRUCTIONS

If you experience any difficulties that the instruction did not cover, Please seek assistance at a local automotive shop

Please wear protection before you work on any vehicle.



An assistant is useful when removing the front bumper from your vehicle.

Please be cautious when working with the bumper or any parts belonging to the vehicle's body to prevent scratching.

Do not make direct contact with the halogen bulbs or the wire assembly until the unit has cooled down after use.

TOOLS AND SUPPLIES REQUIRED



Flat tipped screwdriver

Phillips Screwdriver

Product Part Numbers:

RRB-PLT09BK



2009-2015 HONDA PILOT ROOF RACK INSTALLATION INSTRUCTIONS

If you experience any difficulties that the instruction did not cover, Please seek assistance at a local automotive shop

Please wear protection before you work on any vehicle.



An assistant is useful when removing the front bumper from your vehicle.

Please be cautions when working with the bumper or any parts belonging to the vehicles's body to prevent scratching.

Do not make direct contact with the halogen bulbs or the wire assembly until the unit has cooled down after use.



1. Before



2. Crossbar Bracket and hardware



3. Place the (2) nuts into bracket



4. Install the (2) tumb screw a few turns



5. Install the (2) thumb screws in brackets



6. Slide bracket over the end of the crossbar



7. Secure bracket to cross bar using washer and phillips screw



8. Disconnect the headlight harness



9. Remove the (2) rear roof rack covers



10. Slide assembled cross rails into the rear of the roof rack



12. Slide both rails into the roof rack and position



13 Secure cross bar to the roof rack by tightening thumb screws



14. Secure cross bar to roof rack by tightening thumb screws



15. Install the phillips head screw into the hole towards the rear end of the roof rack.



16. Reinstall the rear roof rack covers



17. The installation now is complete