

PRODUCT DATA SHEET

Honing & Cutting Oil, 1 Gal

Part Number: SL2523

Product Description An all-purpose metal working/ cutting lubricant that

extends tool life and improves machined surface finish.

Applications Valve refacing, piston pin fitting, honing, tapping,

reaming, grinding, threading, boring, broaching, drilling

and milling

Unit Package Description 1 Gallon Bottle

Brand Sta-Lube

Generic Description 1 Honing & Cutting Oil

Net Fill 1 Gal

UPC Code 072213252309

Unit Dimensions 10.63H x 4.75W x 6D in

Units Per Case 4

Case Dimensions 11.25H x 11.25W x 13.5D in

Cases Per Pallet 60
Case Weight 33 lbs

I 2 of 5 Code 30072213252300

Appearance Red Liquid
Flash point (F) 378°F
Flash point (C) 192°C
Flammability Class - CPSC None

Plastic Safe Yes

Spec Gravity Concentrate

Evaporation Rate <1 (butyl acetate=1)

0.89

ISO Viscosity Grade 32

SAE Grade 15W

Working Temp (F) 50 to 150°F


DOT Proper Shipping Name Not Regulated


VOC % (Federal) 2.9 VOC g/L (Federal) 26

Last revised: 5/4/2016

Page 1 of 2









PRODUCT DATA SHEET

VOC Lbs./Gal. (Federal) 0.2

VOC Category Cutting or Tapping Oil (Non-Aerosol)

Restricted from Sale In: SCAQMD



Last revised: 5/4/2016

Page 2 of 2



