



# PRODUCT DATA SHEET

Hi Temperature Disc Brake Wheel Bearing Grease, 7 Lbs  
Part Number: SL3166



|                           |   |
|---------------------------|---|
| Product Description       | A very stable resistant Aluminum Complex grease. Contains rust & oxidation inhibitors, anti-wear and extreme pressure additives & fortified with "moly" and graphite. For use in automotive disc/drum brakes, chassis and suspension systems  |
| Applications              | Automotive applications, ball joints, bearings, chassis points, construction ball & roller bearings, conveyor bearings, disc-brake systems, farm equipment, guides, mining applications, press rolls, roller bearings, slides, wheel bearings |
| Unit Package Description  | 7 Pound Pail  |
| Brand                     | Sta-Lube  |
| Generic Description 1     | Hi-Temp Disc Brake Wheel Grease   |
| Net Fill                  | 7 Lb  |
| UPC Code                  | 072213316605  |
| Unit Dimensions           | 7.75H x 7.5W x 7.5D in  |
| Units Per Case            | 4   |
| Case Dimensions           | 8H x 16.5W x 16.5D in   |
| Cases Per Pallet          | 54  |
| Case Weight               | 33 lbs  |
| I 2 of 5 Code             | 30072213316606  |
| Appearance                | Dark Gray Semi-Solid to Solid Grease  |
| Base Type                 | Aluminum Complex  |
| Flash point (F)           | >450°F  |
| Flash point (C)           | >232°C  |
| Flammability Class - CPSC | None  |
| Spec Gravity Concentrate  | 0.9 at 60°F   |
| NLGI Grade                | 2   |
| Timken OK Load [Lbs.]     | 60 Lbs  |
| Plastic Safe              | Not Determined  |

Last revised: 5/4/2016  
Page 1 of 2



CRC Industries is a worldwide leader in the production of specialty chemicals for maintenance and repair professionals serving industrial, electrical, aviation, automotive and marine markets. CRC is ISO 9001:2008 certified and adheres to the strictest guidelines for quality in all facets of research, development and production.



CRC®, K&W®, Sta-Lube®, Marykate® and products denoted with ® and ™ are trademarks of CRC Industries, Inc.



## PRODUCT DATA SHEET



|                          |   |
|--------------------------|---|
| Evaporation Rate         | <0.01 (Butyl Acetate=1)                           |
| Working Temp (F)         | 0 to 325°F  |
| Working Temp (C)         | -18 to 162.5°C                                    |
| 4 Ball EP                | 30 LWI, 315 Kg Weld                               |
| 4 Ball Wear              | 0.75 mm   |
| Drop Point               | 500°F   |
| Elastomer Compatibility  | 0 to 30% vol; 0 to 15 hard                        |
| Leakage                  | 10g Max   |
| Oil Separation           | <10%  |
| Oxidation Stability      | 2 to 3  |
| Pour Point (F)           | 0°F   |
| Pour Point (C)           | -17.78°C  |
| ISO Viscosity Grade      | 205   |
| Water Washout            | <15%  |
| Worked Penetration       | 265 to 295  |
| Propellant               | None  |
| DOT Proper Shipping Name | Not Regulated                                     |
| VOC % (Federal)          | 0.4   |
| VOC g/L (Federal)        | 3.6   |
| VOC Lbs./Gal. (Federal)  | 0.03  |
| VOC Category             | Not Regulated                                     |
| Removal (How To)         | Remove with a degreaser or brake cleaner product. |

Last revised: 5/4/2016  
Page 2 of 2



CRC Industries is a worldwide leader in the production of specialty chemicals for maintenance and repair professionals serving industrial, electrical, aviation, automotive and marine markets. CRC is ISO 9001:2008 certified and adheres to the strictest guidelines for quality in all facets of research, development and production.



CRC®, K&W®, Sta-Lube®, Marykate® and products denoted with ® and ™ are trademarks of CRC Industries, Inc.