

## PRODUCT DATA SHEET

## Synthetic Brake & Caliper Grease, 2.5 Wt Oz Part Number: SI 3301

**Product Description** 

Applications

A specially developed synthetic grease with a high-tech formula for use in disc & drum brake systems. High temperature grease is plastic & rubber safe. Use on metal to metal contact points and sliding surfaces. Resists moisture and will not washout.

Backing plates, brake pad contact points, caliper o-rings, calipers, disc brake pads, drum brake systems, grommets, parking brake areas of lubrication, pivot points, self adjusters

	-
Unit Package Description	2.5 Ounce Tube
Brand	Sta-Lube
Generic Description 1	Brake Caliper Synthetic Grease
Net Fill	2.5 Wt Oz
UPC Code	072213330106
Unit Dimensions	6.19H x 2W x 1.5D in
Units Per Case	6
Case Dimensions	2.88H x 4.75W x 7.38D in
Cases Per Pallet	700
Case Weight	2 lbs
I 2 of 5 Code	30072213330107
Appearance	Black Semi-Solid Grease
Base Type	Synthetic base with Molybdenum Disulfide, PTFE and Graphite
Flash point (F)	450°F
Flash point (C)	232°C
Flammability Class - CPSC	None
Spec Gravity Concentrate	0.89
NLGI Grade	2
Timken OK Load [Lbs.]	60 Lbs
Plastic Safe	Yes

Last revised: 5/4/2016 Page 1 of 2



USE ON EVERY BRAKE JOB!

CONTAINS MOLY, PTFE

& GRAPHITE **TEMPERATURE RANGE** 

-30°F TO 600°F PREVENTS BRAKE NOISE

MAXIMIZES BRAKE EFFICIENCY

CRE

Part No. SL3301

2.5 oz. (71 g)

and adheres to the strictest guidelines for quality in all facets of research, development and production.

 $CRC^{\circledast}, K\&W^{\circledast}, Sta-Lube^{\circledast}, Marykate^{\circledast} and products denoted with <math display="inline">^{\circledast}$  and  $^{\intercal}$  are trademarks of CRC Industries, Inc.

CRC Industries is a worldwide leader in the production of specialty chemicals for maintenance and repair professionals serving industrial, electrical, aviation, automotive and marine markets. CRC is ISO 9001:2008 certified



## **PRODUCT DATA SHEET**

Evaporation Rate	Slow
Working Temp (F)	-30 to 600°F
Working Temp (C)	-45.5 to 232°C
4 Ball EP	Not Determined
4 Ball Wear	0.67 mm
Drop Point	None
Leakage	None
Oil Separation	Not Determined
Oxidation Stability	5
Pour Point (F)	-20°F
Pour Point (C)	-29°C
ISO Viscosity Grade	Not Determined
Water Washout	1.7
Worked Penetration	265 to 295
Propellant	None
DOT Proper Shipping Name	Not Regulated
VOC % (Federal)	0.58
VOC g/L (Federal)	5.62
VOC Lbs./Gal. (Federal)	0.04
VOC Category	Not Regulated
Removal (How To)	Remove with a degreaser or brake cleaner product.

۲

USE ON EVERY BRAKE JOB! CONTAINS MOLY, PTFE & GRAPHITE TEMPERATURE RANGE -30°F TO 600°F\* PREVENTS BRAKE NOISE · MAXIMIZES BRAKE EFFICIENCY

> CRC Part No. SL3301 2.5 oz. (71 g)



Last revised: 5/4/2016





CRC®, K&W®, Sta-Lube®, Marykate® and products denoted with  $^{\circledast}$  and  $^{m}$  are trademarks of CRC Industries, Inc.

Page 2 of 2