

SAFETY DATA SHEET

1. Identification

Product identifier Engine Assembly Lube

Other means of identification

No. SL3333 (Item# 1007914) **Product Code** Recommended use Engine assembly lubricant

None known. **Recommended restrictions**

Manufacturer/Importer/Supplier/Distributor information

2. Hazard(s) identification

Physical hazards Not classified. Not classified. **Health hazards** Not classified. **Environmental hazards OSHA** defined hazards Not classified.

Label elements

Hazard symbol None. Signal word None.

Hazard statement The mixture does not meet the criteria for classification.

Precautionary statement

Prevention Observe good industrial hygiene practices.

Response Wash hands after handling.

Storage Store away from incompatible materials.

Disposal Dispose of contents/container in accordance with local/regional/national regulations.

Hazard(s) not otherwise

classified (HNOC)

None known.

3. Composition/information on ingredients

Mixtures

Chemical name	Common name and synonyms	CAS number	%
distillates (petroleum), hydrotreated heavy naphthenic		64742-52-5	50 - 60
residual oils (petroleum), solvent-dewaxed		64742-62-7	40 - 50
graphite		7782-42-5	< 1

Specific chemical identity and/or percentage of composition has been withheld as a trade secret.

4. First-aid measures

Inhalation If breathing is difficult, remove to fresh air and keep at rest in a position comfortable for breathing.

Call a physician if symptoms develop or persist.

Skin contact Remove and isolate contaminated clothing and shoes. Immediately flush skin with plenty of water.

Get medical attention if irritation develops and persists.

Eye contact Immediately flush eyes with plenty of water, occasionally lifting the upper and lower eyelids.

Remove contact lenses, if present and easy to do. Get medical attention if irritation develops and

persists.

Ingestion Rinse mouth. Do not induce vomiting without advice from poison control center. If material has

been swallowed and the exposed person is conscious, give small quantities of water to drink. Never give anything by mouth to a victim who is unconscious or is having convulsions. Get

medical attention if symptoms occur.

Most important symptoms/effects, acute and delayed

Direct contact with eyes may cause temporary irritation. Prolonged or repeated skin contact may

cause irritation.

Indication of immediate medical attention and special

Treat symptomatically.

treatment needed
General information

Ensure that medical personnel are aware of the material(s) involved, and take precautions to

protect themselves.

5. Fire-fighting measures

Suitable extinguishing media Unsuitable extinguishing Use fire-extinguishing media appropriate for surrounding materials.

None known.

Specific hazards arising from

the chemical

During fire, gases hazardous to health may be formed.

Special protective equipment and precautions for firefighters

Firefighters must use standard protective equipment including flame retardant coat, helmet with

face shield, gloves, rubber boots, and in enclosed spaces, SCBA.

Fire-fighting

media

equipment/instructions

Use water spray to keep fire-exposed containers cool and to knock down vapors which may result from product decomposition

from product decomposition.

General fire hazards No unusual fire or explosion hazards noted.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

Keep unnecessary personnel away. Ensure adequate ventilation. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. For personal protection, see section 8 of the SDS.

Methods and materials for containment and cleaning up

Sweep up or vacuum up spillage and collect in suitable container for disposal. Following product recovery, flush area with water. For waste disposal, see section 13 of the SDS.

Environmental precautions Avoid dischar

Avoid discharge into drains, water courses or onto the ground.

7. Handling and storage

Precautions for safe handling

Avoid contact with eyes, skin, and clothing. Provide adequate ventilation. Keep away from heat and sources of ignition. Wear appropriate personal protective equipment. Avoid release to the environment. Observe good industrial hygiene practices. Use care in handling/storage. For product usage instructions, see the product label.

Conditions for safe storage, including any incompatibilities

Store in a cool, dry place out of direct sunlight. Store in a well-ventilated place. Keep container tightly closed. Store away from incompatible materials (see Section 10 of the SDS).

8. Exposure controls/personal protection

Occupational exposure limits

The following constituents are the only constituents of the product which have a PEL, TLV or other recommended exposure limit. At this time, the other constituents have no known exposure limits.

US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000)

Components	Туре	Value	Form
distillates (petroleum), hydrotreated heavy naphthenic (CAS 64742-52-5)	PEL	5 mg/m3	Mist.
,		2000 mg/m3	

Material name: Engine Assembly Lube

SDS US

Components	Туре	Value	Form
graphite (CAS 7782-42-5)	PEL	500 ppm 5 mg/m3 15 mg/m3	Respirable fraction. Total dust.
US. OSHA Table Z-3 (29 CF	R 1910.1000)	·	
Components	Туре	Value	
graphite (CAS 7782-42-5)	TWA	15 mppcf	
US. ACGIH Threshold Limi Components	t Values Type	Value	Form
distillates (petroleum), hydrotreated heavy naphthenic (CAS 64742-52-5)	TWA	5 mg/m3	Inhalable fraction.
graphite (CAS 7782-42-5)	TWA	2 mg/m3	Respirable fraction.
residual oils (petroleum), solvent-dewaxed (CAS 64742-62-7)	TWA	5 mg/m3	Inhalable fraction.
US. NIOSH: Pocket Guide t	to Chemical Hazards		
Components	Туре	Value	Form
distillates (petroleum), hydrotreated heavy naphthenic (CAS 64742-52-5)	Ceiling	1800 mg/m3	
• · · · = • = • /	STEL	10 mg/m3	Mist.
	TWA	5 mg/m3	Mist.
graphite (CAS 7782-42-5)	TWA	2.5 mg/m3	Respirable.
logical limit values	No biological exposure limits noted for	• , ,	
propriate engineering trols	Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level.		
	s, such as personal protective equipm		
Eye/face protection	Wear safety glasses with side shield	s (or goggles).	
Skin protection			
Hand protection	Wear protective gloves such as: Nec	prene. Nitrile. Polyethylene. Po	olyvinyl chloride (PVC).
Other	Wear suitable protective clothing.		
Respiratory protection	If engineering controls are not feasible or if exposure exceeds the applicable exposure limits, use NIOSH-approved cartridge respirator with an organic vapor cartridge. Use a self-contained breathing apparatus in confined spaces and for emergencies. Air monitoring is needed to determine actual employee exposure levels.		
Thermal hazards	Wear appropriate thermal protective clothing, when necessary.		
neral hygiene siderations	Always observe good personal hygie and before eating, drinking, and/or security and the remove contaminants		

9. Physical and chemical properties

Appearance

Solid. **Physical state Form** Grease. Color Black.

Odor Mild petroleum. **Odor threshold** Not available. Not available. рΗ Melting point/freezing point Not available.

Material name: Engine Assembly Lube

equipment to remove contaminants.

Initial boiling point and boiling

range

680 °F (360 °C) estimated

450 °F (232.2 °C) Flash point

Evaporation rate Slow.

Flammability (solid, gas) Not available. Upper/lower flammability or explosive limits

Flammability limit - lower

Not available.

Flammability limit - upper

(%)

Not available.

< 0.1 mm Hg @ 68 °F Vapor pressure

Vapor density > 5 (air = 1)

Relative density 0.9 Solubility (water) Insoluble. **Partition coefficient** Not available.

(n-octanol/water)

500 °F (260 °C) estimated **Auto-ignition temperature**

Decomposition temperature Not available. Viscosity (kinematic) Not available. Percent volatile Not available.

10. Stability and reactivity

The product is stable and non-reactive under normal conditions of use, storage and transport. Reactivity

Material is stable under normal conditions. **Chemical stability**

Possibility of hazardous

reactions

No dangerous reaction known under conditions of normal use.

Conditions to avoid Contact with incompatible materials.

Incompatible materials Strong oxidizing agents. Hazardous decomposition

products

Carbon oxides. Metal oxides.

11. Toxicological information

Information on likely routes of exposure

Inhalation Prolonged inhalation may be harmful.

Skin contact Prolonged skin contact may cause temporary irritation. Eye contact Direct contact with eyes may cause temporary irritation. Ingestion Health injuries are not known or expected under normal use.

Symptoms related to the physical, chemical and toxicological characteristics Direct contact with eyes may cause temporary irritation.

Information on toxicological effects

Acute toxicity Not known.

Product Species Test Results

Engine Assembly Lube

Acute Dermal

ATEmix 2140.0856 mg/kg

Components **Test Results Species**

distillates (petroleum), hydrotreated heavy naphthenic (CAS 64742-52-5)

Acute Dermal

LD50 Rabbit > 2000 mg/kg

Components	Species	Test Results
Oral		
LD50	Rat	> 5000 mg/kg
graphite (CAS 7782-42-5)		
<u>Acute</u>		
Oral		
LD50	Rat	> 10000 ma/ka

^{*} Estimates for product may be based on additional component data not shown.

Skin corrosion/irritation Prolonged skin contact may cause temporary irritation. Direct contact with eyes may cause temporary irritation. Serious eye damage/eye

irritation

Not a respiratory sensitizer.

This product is not expected to cause skin sensitization. Skin sensitization

No data available to indicate product or any components present at greater than 0.1% are Germ cell mutagenicity

mutagenic or genotoxic.

Carcinogenicity Not classifiable as to carcinogenicity to humans.

IARC Monographs. Overall Evaluation of Carcinogenicity

Respiratory sensitization

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

US. National Toxicology Program (NTP) Report on Carcinogens

Not listed.

This product is not expected to cause reproductive or developmental effects. Reproductive toxicity

Specific target organ toxicity -

single exposure

Ecotoxicity

Not classified.

Specific target organ toxicity -

repeated exposure

Not classified.

Not an aspiration hazard. **Aspiration hazard**

Chronic effects Prolonged inhalation may be harmful.

Further information This product has no known adverse effect on human health.

12. Ecological information

The product is not classified as environmentally hazardous. However, this does not exclude the possibility that large or frequent spills can have a harmful or damaging effect on the environment.

Components		Species	Test Results
distillates (petroleum)	, hydrotreated heav	y naphthenic (CAS 64742-52-5)	
Aquatic			
Crustacea	EC50	Water flea (Daphnia magna)	1000 mg/l, 48 hours
Fish	LC50	Rainbow trout,donaldson trout (Oncorhynchus mykiss)	5000 mg/l, 96 hours
graphite (CAS 7782-4	2-5)		
Aquatic			
Acute			
Fish	LC50	Fish	> 1800 mg/l, 96 hours

^{*} Estimates for product may be based on additional component data not shown.

Persistence and degradability

No data available. Bioaccumulative potential Mobility in soil No data available.

No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation Other adverse effects

potential, endocrine disruption, global warming potential) are expected from this component.

13. Disposal considerations

Disposal of waste from residues / unused products This product is not a RCRA hazardous waste (See 40 CFR Part 261.20 – 261.33). Empty containers may be recycled. Collect and reclaim or dispose in sealed containers at licensed waste disposal site. Do not allow this material to drain into sewers/water supplies. Do not contaminate ponds, waterways or ditches with chemical or used container. Dispose in accordance with all

applicable regulations.

Hazardous waste code

Not regulated.

Contaminated packaging

Empty containers should be taken to an approved waste handling site for recycling or disposal. Since emptied containers may retain product residue, follow label warnings even after container is

emptied.

14. Transport information

DOT

Not regulated as dangerous goods.

IATA

Not regulated as dangerous goods.

IMDG

Not regulated as dangerous goods.

15. Regulatory information

US federal regulations

This product is not known to be a "Hazardous Chemical" as defined by the OSHA Hazard

Communication Standard, 29 CFR 1910.1200.

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

Not regulated.

SARA 304 Emergency release notification

Not regulated.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

Not regulated.

US EPCRA (SARA Title III) Section 313 - Toxic Chemical: Listed substance

CERCLA Hazardous Substance List (40 CFR 302.4)

Not listed.

CERCLA Hazardous Substances: Reportable quantity

Not listed.

Spills or releases resulting in the loss of any ingredient at or above its RQ require immediate notification to the National Response Center.

Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List

Not regulated.

Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)

Not regulated.

Safe Drinking Water Act

(SDWA)

Not regulated.

Food and Drug Not regulated.

Administration (FDA)

Superfund Amendments and Reauthorization Act of 1986 (SARA)

Immediate Hazard - No Section 311/312 Delayed Hazard - No **Hazard categories** Fire Hazard - No

Pressure Hazard - No Reactivity Hazard - No

SARA 302 Extremely hazardous substance

US state regulations

US. California. Candidate Chemicals List. Safer Consumer Products Regulations (Cal. Code Regs, tit. 22, 69502.3, subd.

(a))

distillates (petroleum), hydrotreated heavy naphthenic (CAS 64742-52-5) residual oils (petroleum), solvent-dewaxed (CAS 64742-62-7)

Material name: Engine Assembly Lube

SDS US

US. New Jersey Worker and Community Right-to-Know Act

graphite (CAS 7782-42-5)

US. Massachusetts RTK - Substance List

graphite (CAS 7782-42-5)

US. Pennsylvania Worker and Community Right-to-Know Law

graphite (CAS 7782-42-5)

US. Rhode Island RTK

distillates (petroleum), hydrotreated heavy naphthenic (CAS 64742-52-5) graphite (CAS 7782-42-5)

US. California Proposition 65

California Safe Drinking Water and Toxic Enforcement Act of 1986 (Proposition 65): This material is not known to contain any chemicals currently listed as carcinogens or reproductive toxins.

Volatile organic compounds (VOC) regulations

EPA

VOC content (40 CFR

100 %

51.100(s))

Consumer products (40 CFR 59, Subpt. C)

Not regulated

State

Consumer products

Not regulated

VOC content (CA)

< 0.1 %

VOC content (OTC)

< 0.1 %

Inventory name

International Inventories

Country(s) or region

		(,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,
Australia	Australian Inventory of Chemical Substances (AICS)	Yes
Canada	Domestic Substances List (DSL)	Yes
Canada	Non-Domestic Substances List (NDSL)	No
China	Inventory of Existing Chemical Substances in China (IECSC)	Yes
Europe	European Inventory of Existing Commercial Chemical Substances (EINECS)	Yes
Europe	European List of Notified Chemical Substances (ELINCS)	No
Japan	Inventory of Existing and New Chemical Substances (ENCS)	No
Korea	Existing Chemicals List (ECL)	Yes
New Zealand	New Zealand Inventory	Yes
Philippines	Philippine Inventory of Chemicals and Chemical Substances (PICCS)	Yes
United States & Puerto Rico	Toxic Substances Control Act (TSCA) Inventory	Yes

^{*}A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s)

A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the gove

16. Other information, including date of preparation or last revision

Issue date10-23-2017Prepared byAllison Yoon

Version # 01

Further information Not available.

HMIS® ratings Health: 1
Flammability: 1

Physical hazard: 0 Personal protection: B

NFPA ratings Health: 1

Flammability: 1 Instability: 0

Material name. Engine Assembly Lube

On inventory (yes/no)*

A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).

NFPA ratings



Disclaimer

The information contained in this document applies to this specific material as supplied. It may not be valid for this material if it is used in combination with any other materials. This information is accurate to the best of CRC's knowledge or obtained from sources believed by CRC to be accurate. Before using any product, read all warnings and directions on the label. For further clarification of any information contained on this (M)SDS consult your supervisor, a health & safety professional, or CRC Industries, Inc..