

PRODUCT DATA SHEET

Super White™ Multi-Purpose Lithium Grease, 1.75 Wt Oz

Part Number: SL3361

Product Description A high purity, NLGI Grade 1.5 multi-purpose white lithium

grease. Provides superior lubrication & durability in any weather and most temperatures. Bright white in color.

Ideal for when appearance is important.

Applications Assembly lubes, bearings, break-in lubrication for

bearings, cables, chains, chassis points, conveyor bearings, door tracks, garage door channels & openers, hinges, latches, machinery, open gears, overhead door

tracks, roller bearings, sleeve bearings.

Unit Package Description 1.75 Ounce Squeeze Tube

Brand Sta-Lube

Generic Description 1 White Lube
Net Fill 1.75 Wt Oz

UPC Code 072213336108

Unit Dimensions 1.19H x 1.44W x 7.06D in

Units Per Case 24

Case Dimensions 7.63H x 6.38W x 7.5D in

Cases Per Pallet 185
Case Weight 4 lbs

I 2 of 5 Code 30072213336109

Appearance White Semi-Solid to Solid Grease

Base Type Lithium-12

Flash point (F) 475°F
Flash point (C) 246°C
Flammability Class - CPSC None

Spec Gravity Concentrate 0.9 at 60°F

NLGI Grade 1.5

Timken OK Load [Lbs.] 25 Lbs


Plastic Safe Not Determined


Evaporation Rate <0.01 (Butyl Acetate=1)

Last revised: 5/4/2016

Page 1 of 2









PRODUCT DATA SHEET

0 to 300°F

10

Working Temp (F)

Working Temp (C) -17.8 to 148.9°C

Drop Point 350°F

Leakage 5

Oil Separation 5

Oxidation Stability

Pour Point (F) 0°F

Pour Point (C) -17.78°C

I SO Viscosity Grade 165 Water Washout 10

Worked Penetration 285 to 295

Propellant None NSF Category Code H2

NSF Number 147593

DOT Proper Shipping Name Not Regulated

VOC % (Federal) <0.1 VOC g/L (Federal) <0.9

VOC Lbs./Gal. (Federal) < 0.01

VOC Category Not Regulated

Removal (How To) Remove with a degreaser or brake cleaner product.



Last revised: 5/4/2016

Page 2 of 2

