


STAMPEDE™ AUTOMOTIVE ACCESSORIES

SIDEWIND DEFLECTOR INSTALLATION and CLEANING

I - Sheet Number STMPD154 Rev.A





70°-100° F (Install temp.)



The material that your product is made from can be recycled. Please also consider recycling the packaging that your product came in.



- 1 This product is designed to be placed inside the window channel. Roll down window. Buff the inside felt surface with scotch brite pad. Then clean with alcohol pad.
- 2 Remove the tape liner from the front & rear flanges. Peel back 2" of tape liner from each end of top flange. Insert visor into window channel, front flange first.
- 3 Apply pressure to all flange edges to ensure proper adhesion. Remove tape liner by pulling on free ends.
- 4 **NOTE:** It is necessary to both hold the visor up into the window channel **AND** pull the bottom of the visor slightly outward while raising the glass to seat visor properly.
- 5 Continue to apply pressure to ensure that the visor remains properly seated inside the window channel as window is slowly closed. Leave window up for 72 hours to secure visor to window channel.
- 6 Install the rear visors using the same methods as the front visor, with the exception of the rear side flange. Using a flathead screwdriver install C1 clip at end of visor flange to compress visor into rubber window channel.
- 7 **NOTE:** It is necessary to both hold the visor up into the window channel **AND** pull the bottom of the visor slightly outward while raising the glass to seat visor properly.
- 8 If the visor does not seat correctly, roll down window and repeat **Step 8**. Repeat **Steps 1 thru 8** for passenger side.



IMPORTANT: Clean with a **SOFT** cloth and soap and water **ONLY!** Using abrasive cleaners, chemicals, or solvents will **VOID** the warranty on this product.

Find out more about stone and bug deflectors we have.