



**NOTE:**

- 1) INSTRUCTION SHEET P/N PLITSTR43
- 2) PACKING: P/N SCART200Z  
INCLUDES:  
(1) UNIT BOX P/N PCARTZFOLDU  
(1) 10 x 12 POLY BAG P/N P30024-14  
(1) MASTER CARTON P/N PCART200Z12 (12 UNITS)
- 3) BOX LABEL BLANK P/N PLAB64
- 4) LENS COLORS: AMBER, BLUE, CLEAR, GREEN, RED  
\* = A, B, C, G, R

**SPECIFICATIONS**

Typical Input Voltage Range: 10–16VDC  
 Typical Current Draw: .5A @ 12VDC  
 Flash Rate: Single Flash 65sfpm  
 Output Power: Single Flash 3.1W  
 Connections: 18" Min. wires exiting the unit.  
 Permanent Mounting: 2 Holes on  $\phi$ 2.75 Center  
 Dimensions: (Short Dome): 4.25" tall x  $\phi$ 4.25".  
 Individual Shipping weight: 1.5 lbs.

UNLESS OTHERWISE SPECIFIED: DIMENSIONS ARE IN INCHES Drill Tolerances $\pm$ 0.003 Artwork and board size TOLERANCES: ANGULAR: $\pm$ 2 DEG. .X $\pm$ .100 .XX $\pm$ .020 .XXX $\pm$ .005 .XXXX $\pm$ .001		DRAWN BY: DPL	<b>STAR HEADLIGHT &amp; LANTERN CO., INC.</b>	
RoHS COMPLIANT: NA		MODEL: 201Z-12V-* (12VDC, 0.5A)		
MATERIAL: NA		TITLE: MODEL DRAWING MODEL 201Z SINGLE FLASH STROBE LIGHT		
FINISH: NA		DWG. NO. 201Z		
		REV D		
		SCALE: 1:1	DO NOT SCALE FROM DRAWING	SHEET 1 OF 1