



9016LED-AA-A



9016LEDV-AA-C

Specifications and Features

- New Scene [Lighting](#) now available
- M-Tech Plus® LED technology provides superior 360° warning light image
- Durable polycarbonate domes
- Fluted lens over LEDs
- Conformal coated circuitry protects against shock and vibration
- Rugged one-piece, extruded, anodized aluminum base
- Permanent mount - 20 customer selectable flash patterns via external pattern select wire, S-Link System™ synchronizing capability with up to six other Star LED units, 24" wire leads
- Magnet mount - 20 customer selectable flash pattern select switch on plug, 12' cig plug with lighted on/off and pattern select switch
- Dimensions: 3 3/4"H x 16"L x 8 3/8"D
- Voltage: permanent mount - 10-30V DC, magnet mount - 10-16V DC
- Amp Draw: (Amber or Red) 2 amps max, (Blue, White, Green, Blue, Blue/White), 3.6 amps max, (Amber/White, Amber/Green, Red/Blue) 2.8 amps max
- Dome Colors:
- LED Color with a Clear dome only:
- LED Colors:
- Approvals: SAE J845 Class I (A, B, R, W)*, California Title 13 available upon request*
* = does not apply to all flash patterns

Model Numbers/Descriptions:

9016LED	Starbeam™, M-Tech Plus® LED, permanent mount
9016LEDM	Starbeam™, M-Tech Plus® LED, magnet mount
9016LEDV	Starbeam™, M-Tech Plus® LED, vacuum magnet mount
9016SLED	Starbeam™, M-Tech Plus® LED, scene lighting, permanent mount