

**NEW**

## **C2 LED BEACON**



### **Specs & Features:**

- Two Star Generation IV LEDs
- 28 customer selectable flash patterns, including steady-on
- Shipped in a quad flash pattern
- **256 Series:** Durable polycarbonate twist on/off lens, lightweight polycarbonate, universal flange base (3-hole permanent mount, 1" pipe mount, optional vacuum or magnet mount with cig. plug)
- **240 Series:** Durable polycarbonate screw on lens, rugged die-cast aluminum base with powder coat finish and universal mounting (permanent mount, flange mount, standard 1/2" pipe mount)
- 256 Series Dimensions: Short dome - 4-3/4" tall x 6-13/32" dia.  
Tall dome - 6-11/16" tall x 6-13-32" dia.
- 240 Series Dimensions: Short dome - 4-1/4" tall x 5-1/2" dia.  
Tall dome - 6" tall x 5-1/2" dia.
- Voltage: 10-16V DC
- Amp draw: 0.43 max
- Color: Amber or Clear only
- Approvals: SAE Class II

### **Model Numbers / Descriptions:**

- 240SFL: C2 LED beacon short dome, flange die-cast base permanent mount
- 240CFL: C2 LED beacon tall dome, flange die-cast base permanent mount
- 256TSL: C2 LED beacon short dome, flange plastic base permanent mount
- 256TCL: C2 LED beacon tall dome, flange plastic base permanent mount  
(magnet mount available)