



INSTALLATION INSTRUCTIONS STILLEN BRAKE COOLING DUCTS

2009 NISSAN GTR
P/N GTR308396

Materials supplied:

1. (2) Rear Ducts
2. (8) Speed Clips
3. (2) Hose Clamps
4. (2) Small Adel Clamps
5. (2) Ducting Hose
6. (8) Self Tapping Screws
7. (4) Washers
8. (2) Duct Tip

Equipment needed:

1. +,- Screwdriver
2. Assorted pliers/wrenches
3. Assorted sockets/ratchets



WARNING:

IF YOU ARE NOT EXPERIENCED IN THE AREA
OF AUTOMOTIVE MECHANICS WE STRONGLY
URGE THAT YOU REFER THIS INSTALLATION
TO YOUR MECHANIC.

INSTALLATION

1. First you will begin by jacking up the rear of the vehicle. Look in your owners manual for proper jackpoints.
2. Remove the rear wheels and set aside.
3. Right behind the rear wheel is where you will be locating the brake cooling duct. You will need to drill 3 small clearance holes then install speed clips in the locations shown. Use the provided hardware to mount the duct onto the vehicle.





4. Using the provided hardware you will need to secure the hose onto the suspension as shown and orient the hose outlet at the caliper pocket. See (Fig.2)

