



STREET SCENE EQUIPMENT, INC.

950-76932 BLACK CHROME
 &
 950-77932 SATIN FINISH
 &
 950-78932 CHROME FINISH
 2005
 MUSTANG GT
MAIN GRILLE INSERT

INSTALLATION INSTRUCTIONS

VERY IMPORTANT ! Read and understand all directions and check the following parts list before starting installation.

NOTE: Fits GT Models ONLY
For 6 CYL Models Use 950-7X931

PARTS LIST					
1	Center Grille Section	1	Instruction Sheet	8	Push In Fasteners
1	RT Grille Section	1	Street Scene Emblem	1	Care For Grilles Sheet
1	LT Grille Section	8	11" Ladder Ties		

TOOL LIST
Flat Blade Screwdriver, Side Cut Pliers, Drill Motor, 1/4" Drill Bit

1. Open hood.
2. Remove the air deflector panel between the front fascia and radiator by prying up the " push in " fasteners securing the panel.
3. Unplug the wiring harness from lights in grille.
4. Remove the grille by lifting the center tabs on fascia with a small flat screwdriver while pulling grille forward.
5. Remove the Mustang Emblem.
6. Refer to photo and drill 1/4" holes in grille as indicated.

PHOTO



Passenger Side



Driver's Side



7. Install ladder ties through Speed Grille (where they can not be seen) and attach to grille shell by pushing both ends through holes drilled in step six and fastening in back side. Tighten ladder ties snugly. **DO NOT** over tighten. Cut off excess.
8. Install grille back into fascia making sure all attaching points are tight. Plug in wire harness to lights.
9. Install the air deflector panel removed in step two using the new " push in " fasteners supplied.

THE SPEED GRILLE™ may be covered by one or more of the following U.S. Patents: D427,119,D425,834,D421,585,D420,961,D420,960,D420,959, and D420,958 may be covered by one or more pending U.S. Patent applications.