



# STREET SCENE EQUIPMENT, INC.

**950-74590 BLACK SATIN  
POWDER COAT**  
 &  
**950-76590 BLACK CHROME**  
 &  
**950-77590 SATIN FINISH**  
 &  
**950-78590 CHROME FINISH**  
**STREET SCENE GRILLE  
SHELL W / SPEED  
GRILLE INSERTS**

## INSTALLATION INSTRUCTIONS

**VERY IMPORTANT !** Read and understand all directions and check the following parts list before starting installation.

**NOTE: THIS GRILLE IS FOR THE GT MODEL ONLY**

PARTS LIST					
<b>1</b>	Grille Shell W / Speed Grille Inserts			<b>2</b>	14" Wire Harness Extensions
<b>2</b>	11" Wire Tie Straps	<b>1</b>	Instruction Sheet	<b>8</b>	Washer Head Phillips Screws # 71834
<b>1</b>	Care For Grilles	<b>1</b>	Street Scene Emblem		

TOOL LIST
1/8" Drill Bit, # 6 Torx Socket, Panel Removal Tool, Flat Blade Screwdriver, 1/8" Drill Bit, Phillips Screwdriver, Drill Motor

1. Open hood and remove the 6 push in fasteners that secure the plastic header panel cover, by prying up the center pin and then prying up the body. Save fasteners.
2. Reach in and unplug the wire harness connections at the fog lamps in grille.
3. Remove the OEM Grille Shell from the front fascia by depressing the tabs on fascia while pushing the tab on grille shell in opposite direction.
4. Remove the fog lamps from the grille shell and install into the Street Scene grille shell. Drill an 1/8" hole in center of light mounting. Install light using the screws provided.
5. Connect the harness extensions to the light harness connection. Route to center of vehicle. Use a wire tie on each harness extension to support.
6. Install grille shell back into vehicle.
7. Install the plastic header panel removed in step 1.