



## INSTALLATION INSTRUCTIONS

**VERY IMPORTANT !** Read and understand all directions and check the following parts list before starting installation.

PARTS LIST					
1	Instruction Sheet	1	Upper Grille Insert	30	Installation Clips # 71098
1	Grille Care Instructions	1	Lower Grille Insert		

TOOL LIST	
Phillips Head Screw Driver, Flat Head Screw Driver, 10MM Socket, Ratchet, Extension	

**Remove front fascia, this can be done in six easy steps.**

1. Remove the six 10MM head bolts on the under side of vehicle. **NOTE:** For reassembly, that the two center bolts are of a shoulder design and are shorter than the outward bolts.
2. Remove the three phillip head screws in each wheel well housing. Turn the front wheels to access.
3. Remove the hex / phillip head bolt located at the corner of each wheel well, were the fascia meets the front fender.
4. Remove the air intake by removing the three fastners securing it to the core support. Pry the center pin up and then the outside body.
5. Remove the ABS filler panel between the fascia and core support, by removing the push in fastners as in step four. See photo below.

### PHOTO



6. With the aid of another person remove the front fascia. The fascia will unsnap from the front fender. Pull the fascia out and reach down and unplug the light harness from the lights. You will also need to unplug the wire harness from the metal light bracket. See photo below.

### PHOTO



## Installing Speed Grille

1. Set the fascia on a covered table or bench. Install the upper speed grille into opening. See photo and clip speed grille to fascia. Install the lower speed grille into opening. Due to the severe angles of the opening this grille will require a little more work when installing. See photo and clip speed grille to opening as shown.

**PHOTO**



**PHOTO**



Install fascia back on vehicle.