



STREET SCENE EQUIPMENT, INC.

950-70126
FRONT VALANCE
99-02 GMC SIERRA

2000-04 YUKON & YUKON XL
GENERATION 3

INSTALLATION INSTRUCTIONS

NOTE: Fit all parts before painting (See Special Instructions For Paint Prep.) Parts that have been installed, preped, or painted are not returnable.

VERY IMPORTANT ! Read and understand all directions and check the following parts list before starting installation.

PARTS LIST					
1	Front Valance	1	Instruction Sheet	1	Street Scene Decal

TOOL LIST
Flat Blade Screwdriver. Drill Motor, 1/2" Drill Bit, Safety Glasses.

NOTE:

Valance Prep & Paint - A professional shop experienced in painting urethane parts is highly recommended: Use standard urethane paint preparation procedures on the entire outer surface standard procedures include cleaning with silicone removing solvent, finish sanding till all shiny surfaces are dull, using a primer with adhesion promoter, and adding flex agent to the paint.

1. Before beginning installation be sure to wear proper eye protection.
2. Remove the stock valance and retaining clips by prying up with a flat blade screwdriver the center locking pin in the quick connect fasteners and removing the 13 fasteners from valance. Remove valance
3. Set the factory valance against the top edge of the SS valance. Carefully mark the location of the mounting holes on the SS valance. Drill 1/2" hole at these location. Use the original fasteners to install valance.