



**NOTE: Fit all parts before painting ( See Special Instructions For Paint Prep. ) Parts that have been installed, preped, or painted are not returnable.**

**VERY IMPORTANT !** Read and understand all directions and check the following parts list before starting installation.

<b>PARTS LIST</b>					
1	Rear Fascia Lip	1	Instruction Sheet	15 FT.	1/2" Wide Two Sided Tape
		1	Urethane Prep Sheet	1	Street Scene Decal
				2	Black Mounting Screws

<b>TOOL LIST</b>	

**NOTE:** For proper adhesion of the two sided tape you must follow paint and prep instructions. The back side of body parts must be cleaned and sanded thoroughly. Adhesion promoter should be used for installation of all urethane parts.

1. Clean the backside of rear Fascia throughly. Skuff up the tape edge. Prepare edge with adhesion promoter. Apply the two sided tape as shown in photo 1. DO NOT remove backing at this time.
2. With the aid of another person set the fascia on the body. The lower edge will fit on the lip. Mark location of fascia to body. Remove fascia and skuff the paint on the body with a scotch brite pad where the two sided tape will contact the body. Apply adhesion promoter to this area.
3. Remove backing on the two sided tape and mount the rear fascia to body. Drill two 1/8" holes at each rear wheel opening and install a mounting screw on each side.

**PHOTO 1**

