



STREET SCENE EQUIPMENT, INC.

CONNECTING STREET SCENE SIGNAL® MIRRORS

INSTRUCTIONS FOR PART NUMBERS		
950-15610	950-18620	950-27620
950-15620	950-18629	950-27625
950-17620	950-20620	950-27626
950-17625	950-20629	

1. Install Street Scene Signal® Mirrors assemblies to doors following mirror installation instructions.
2. Before beginning electrical hook-up, check the operation of turn signals in the front and rear of vehicle. If any problems exist repair before wiring Street Scene Signal® Mirrors.
3. Run the **RED / BLACK** wire from the mirror into the door. Pull the rubber boot out between the door and door frame. Guide the wire harness through the exposed hole in the door and out the opening vacated by the rubber boot. Remove any slack in the wire harness
4. The rubber boot between the door and vehicle wraps around a plastic connector as it enters the door frame. Use a small pry bar to pull out the connector from the door frame.
5. Separate the rubber boot from the connector.
6. Pass the wire harness through the rubber boot and remove any slack in the wire harness.
7. There is a small channel between the wire guides and plastic connector. Guide the wire harness through this channel and then pass the wire into the truck through the door frame. Remove any slack in the wire harness and stretch the rubber boot back over the plastic connector. Snap the plastic connector back into the door frame.
8. To better access the wire harness coming through the door frame the kick panel needs to be removed.
9. Do the same on the passenger side. Run the wire across the dash over to the driver side area.
10. The vehicle's electrical wiring is located under the dashboard to the left of the brake pedal. Locate the solid **LIGHT GREEN** wire near the top of the wire block. Turn the ignition key so that electrical power is on and activate the driver side turn signal. Probe the wire with the wire tester to verify that flashing turn signal power is present. Label that wire as "**Driver Side Turn**". Locate the solid **LIGHT BROWN** wire near the top of the wire block. Activate the passenger side turn signal and probe the wire with the wire tester to verify that flashing turn signal power is present. Label that wire as "**Passenger Side Turn**".
11. Make sure the harness are routed securely under the dash and enough slack is left for splicing.
12. Splice the **RED** wire from the driver side harness into the solid **LIGHT GREEN** wire previously labeled "**Driver's Side Turn**".
13. Splice the **RED** wire from the passenger side harness into the solid **LIGHT BROWN** wire previously labeled "**Passenger Side Turn**". When attaching wires use the quick splice connectors provided. Do not cut any wires.
14. Strip and twist together the ends of the **BLACK** wire from each harness. Crimp them together in the supplied ring connector and ground to a suitable nearby location on the metal framework of the vehicle.
15. Activate each turn signal to verify that the Street Scene Signal® Mirrors are working.



Connecting Street Scene Heated Mirror Conversion Kit

Instructions For Part Numbers:		
950-16620	950-20620	950-27626
950-19620	950-20629	
950-19629	950-27620	

SPECIAL NOTE:

If you are installing Street Scene Mirrors with Signal option the wiring for the heaters will have a push on terminal and a ring connector on. The wires for the signal system will have no connectors on them. Do not mix up

1. Install Street Scene Heated Mirrors following mirror installation instructions.
2. Mount the switch in a suitable location. A good place is on the lower dash panel. Drill a 1/2" diameter hole and insert the switch from the front side and install the nut from the back side and tighten.

NOTE: LOCATION OF WIRES ON SWITCH

Top Of Switch: (Marked "Earth") Black wire from four foot power connecting harness.

Center Of Switch: (Marked "Load") Red wires from right & left mirror heaters.

Bottom Of Switch: (Marked "Supply") Red wire from four foot power connecting harness.

Locate a switched 12 volt power supply at the fuse panel (Power goes off when ignition switch is in the " off " position). Using the blue quick splice connector supplied, crimp the Red wire from the switch harness to the wire found at the fuse block. DO NOT connect to a constant 12 volt power supply.

3. Run the **Red / Black** wire from the mirror into the door. Pull the rubber boot out between the door and door frame, Guide the wire harness thru the exposed hole in the door and out the opening vacated by the rubber boot. Remove any slack in the wire harness.
4. The rubber boot between the door and vehicle wraps around a plastic connector as it enters the door frame. Use a small pry bar to pull out this connector from the door frame.
5. Separate the rubber boot from the connector.
6. Pass the wire harness through the rubber boot and remove any slack in the wire harness.
7. There is a small channel between the wire guides and the plastic connector. Guide the wire harness thru this channel and then pass the wire into the truck through the door frame. Remove any slack in the wire harness and stretch the rubber boot back over the plastic connector. Snap the plastic connector back into the door frame.
8. To better access the wire harness coming through the door frame the kick panel needs to be removed.
9. Do the same on the passenger side, Run the wire across the dash to the left of the steering column.
10. Connect the **RED** wire from the right and left wire harness to the center pin on the switch using the " **One to Two** " connector.
11. Attach the **BLACK** wires with the ring connectors to a suitable nearby ground location on the metal framework on the vehicle.