

# High Performance SUV - HTR Sport H/P

## High Performance SUV - HTR Sport H/P



- 1 Twin reversible sidewall designs; smooth sidewall for clean shiny appearance, serration style sidewall for a more decorative look.
- 2 Two-in-one shoulder block design provides for superb lateral grip, reduced irregular wear, maximum wet grip and stability.
- 3 Four wide, deep circumferential grooves for excellent anti-hydroplaning capability.
- 4 Jointless nylon band technology promotes stable, predictable handling, excellent uniformity, and smooth ride.
- 5 Versatile design for the plus sized look and the real world load requirements of SUVs and light trucks. Some sizes in reinforced construction.



**HTR Sport H/P**

**UTQG - 480 A A**

Product Code	Tire Size	Service Description	Measuring Rim Width (in)	Approved Rim Width		Maximum		Overall Diameter (in)	Section Width (in)	Tread Width (in)	Static Loaded Radius (in)	Revs. Per. Mile	Tread Depth	Ship Weight (lbs)
				Min. (in)	Max. (in)	Air (lbs psi)	Load (lbs)							
5521412	285/60R18	116H	8.5	8.0	10.0	51	2,756	31.5	11.5	9.0	14.1	675	14	48.4
5521421	255/55R18	109H*	8.0	7.0	9.0	50	2,271	29.0	10.0	8.7	13.2	728	14	39.6
5521416	P275/60R20	114H	8.0	7.5	9.5	51	2,601	33.0	10.9	8.7	15.0	638	14	47.0
5521426	275/55R20	117H	8.5	7.5	9.5	50	2,833	32.1	11.0	9.4	14.6	658	14	45.2
5521435	285/50R20	116H*	9.0	8.0	10.0	50	2,756	31.3	11.2	9.8	14.3	673	14	46.2
5521437	305/50R20	120H*	9.5	8.5	11.0	50	3,086	32.0	12.0	10.5	14.6	659	14	50.6
5521448	275/45R20	110H*	9.0	8.5	10.0	50	2,337	29.8	10.6	9.2	13.7	700	14	39.6
5521450	P295/45R20	114H*	10.0	9.5	11.0	50	2,601	30.4	11.6	9.8	13.9	687	14	44.0
5521454	285/45R22	114H*	9.5	9.0	10.5	50	2,601	32.0	11.1	9.6	14.8	651	14	42.7
5521458	P305/45R22	118H	9.5	9.5	11.5	50	2,910	32.8	12.0	10.2	15.1	637	14	52.9
5521462	265/40R22	106H	9.5	9.0	10.5	50	2,094	30.3	10.6	9.5	14.2	684	14	37.9
5521468	305/40R22	114H*	11.0	10.0	12.0	50	2,601	31.6	12.3	10.9	14.6	658	14	48.5
5521480	265/35R22	102H	9.5	9.0	10.5	50	1,874	29.3	10.6	9.6	13.8	705	14	36.4
5521482	285/35R22	106H*	10.0	9.5	11.0	50	2,094	29.9	11.2	10.3	14.0	693	14	39.7
5521492	305/35R24	112H	11.0	10.0	12.0	50	2,469	32.4	12.2	11.0	15.2	638	14	46.9

\* Extra Load (Reinforced) Tire. This tire requires more air pressure to carry the same load as the same size in a standard load construction. See the Reinforced Tire Specification Chart for the correct air pressure and carrying capacity of this tire.

**SAFETY WARNING - SUMITOMO TIRE DOES NOT RECOMMEND ANY PLUS FITMENT THAT HAS A LOWER LOAD INDEX THAN THE ORIGINAL EQUIPMENT TIRES. FAILURE TO FOLLOW PUBLISHED LOAD AND INFLATION SPECIFICATIONS IS VERY DANGEROUS.**