


# ST727

# ST717

## Utility Series | All Position Rib

- Sumitomo four steel belt casing construction resists punctures, increases vehicle stability and contributes to more retread cycles.
- Application specific tread compound resists the effects of scuffing from sharp turns and promotes long mileage.
- 5-rib design provides better vehicle stability in all weather conditions.



These lines offer many hard to find sizes and ply ratings. Every tire is engineered to be Sumitomo tough.

### ST727

Product Code	Tire Size	Service Desc.	Load Range / Ply	Pref Rim Width (inch)	Min Rim Width (inch)	Single Max Load (lbs)	Dual Max Load (lbs)	I.P. (psi)	Overall Diameter (inch)	Section Width (inch)	Min Dual Spacing (inch)	Skid Depth (X/32")	Static Loaded Radius (inch)	Revs Per Mile	Max Speed (mph)
5530504*	8.25R15	130/128K	G/14	6.50	6.00	4,080	3,860	120	33.1	9.3	10.6	14	15.5	627	68
5530507*	10.00R15	137/135K	G/14	7.50	7.00	5,070	4,805	105	36.1	10.7	12.5	16	16.5	566	68
5530540	10R17.5	134/132L	H/16	7.50	6.75	4,675	4,410	115	33.9	9.8	11.4	16	15.8	615	75
5530566	215/75R17.5	135/133J	H/16	6.00	6.00	4,805	4,540	125	30.6	8.3	14.9	16	16.7	687	62
5530570	235/75R17.5	143/141J	J/18	6.75	6.75	6,005	5,675	125	31.5	9.3	10.3	16	14.5	659	62
5530510*	8.25R20	136/134K	G/14	6.50	6.00	4,940	4,675	120	37.9	9.1	10.6	16	17.8	546	68
5530513*	9.00R20	138/136K	F/12	7.00	6.50	5,205	4,940	100	40.1	10.0	11.7	17	18.8	518	68
5530517*	10.00R20	146/143L	H/16	7.50	7.00	6,610	6,005	120	41.2	10.9	12.5	17	19.2	506	75
5530520*	11.00R20	150/147L	H/16	8.00	7.50	7,390	6,780	120	42.5	11.5	13	18	19.9	490	75
5530523*	12.00R20	154/151K	J/18	8.50	8.00	8,270	7,610	120	44.1	11.8	14.2	19	20.6	473	68
5530546	9R22.5	136/134L	G/14	6.75	6.00	4,940	4,675	120	38.1	8.9	10.3	16	17.8	545	75
5530548	10R22.5	141/139L	G/14	7.50	6.75	5,675	5,355	115	40.2	10.0	11.4	16	18.9	515	75
5530552	11R22.5	146/143L	H/16	8.25	7.50	6,610	6,005	120	41.2	10.9	12.6	17	19.3	504	75
5530555	12R22.5	150/147M	H/16	9.00	8.25	7,390	6,780	120	42.5	11.3	13.5	18	19.8	491	81
5530587	255/70R22.5	140/137M	H/16	7.50	6.75	5,510	5,070	120	36.3	9.9	11.3	16	17.1	569	81
5530596	275/70R22.5	148/145M	H/16	8.20	7.50	6,940	6,395	130	37.8	10.9	-	17	17.5	549	81
5530559	11R24.5	149/146L	H/16	8.25	7.50	7,160	6,610	120	43.4	11.0	12.6	17	20.3	479	75

### ST717

5530438	9R17.5	129/127K	G/14	6.75	6.00	4,080	3,860	120	33.1	8.9	10.3	16	15.4	632	68
5530442	11R17.5	137/135K	G/14	8.25	7.50	5,050	4,805	105	36.4	11.7	12.6	17	16.7	582	68
5530426*	13/80R20	153/149K	J/18	9.00	8.50	8,050	7,160	110	41.2	12.5	14.5	19	19.2	506	68
5530429*	14/80R20	157K	J/18	10.00	9.00	9,090	-	120	43	13.5	-	20	19.8	491	68

\* Includes tube and flap