

2007-2009 Mercedes-Benz GL320

2010-2012 Mercedes-Benz GL350

2007-2012 Mercedes-Benz GL450

2008-2012 Mercedes-Benz GL550

2010-2011 Mercedez-Benz GLK350

2007-2009 Mercedes-Benz ML 320

2005-2011 Mercedes-Benz 350

2010-2011 Mercedes-Benz ML 450

2005-2009 Mercedes-Benz ML 500

2008-2011 Mercedes-Benz ML 550

2007-2011 Mercedes-Benz ML63 AMG





129M-15-R Installation Guide

BEFORE YOU BEGIN THE REMOVAL OR INSTALLATION, PLEASE READ ALL OF THE INSTRUCTIONS THOROUGHLY!


THE WARRANTY WILL BE VOID IF INSTRUCTIONS ARE NOT FOLLOWED EXACTLY. DO NOT WORK UNDER A VEHICLE SUPPORTED BY A JACK.




THE WARRANTY WILL BE VOID IF INSTRUCTIONS ARE NOT FOLLOWED EXACTLY. DO NOT WORK UNDER A VEHICLE SUPPORTED BY A JACK.

ALWAYS SUPPORT THE VEHICLE ON SAFETY STANDS.


1. Raise vehicle on lifting platform.



2. Remove cover (#5) and unscrew four plastic nuts (Arrows B).




3. Unscrew threaded connections of air suspension pressure line (#6) from the air spring (#3).



4. Carefully pull the air spring (#3) downwards at its upper plastic framr (Arrows C) Until the air spring (#3) detaches from retaining clip.




ALWAYS SUPPORT THE VEHICLE ON SAFETY STANDS.



5. Carefully push the air spring (#3) together (Arrow D), in the process press the air spring centering (#4) out of the spring control arm (#7) from below.



6. Remove air spring (#3) downwards at an angle (Arrow E).



- 7. Install new retaining spreader clip (#6) on frame floor.
- 8. Install rear air spring in reverse order.