




PS1000

3/8" Power Steering Hose Repair Kit

**S.U.R.&R.
EXCLUSIVE**



Double Braided Hose Pressure: Rated up to 6,000 PSI



- Working Pressure 1,500 PSI, Burst Pressure 6,000 PSI
- Temperature Range (-40° F to +250° F, -40° C to +121° C)
- Exceeds SAE J188 Type 1 Specifications

Repair High And Low Pressure Power Steering Lines


- Use to make 5/16" and 3/8" line repairs
- On-the-car repairs made easy
- 95% coverage of standard power steering lines
- Universal – can be used to repair hundreds of different line types
- Use for power steering lines, clutch, industrial and heavy duty applications
- Includes 6", 12", 18", 24" and 30" lines – Qty 1 of each
- Compression end stamped for easy size identification



Heavy-duty compression connections that feature "double-seal" technology with o-ring and interchangeable ferrule

5 Hoses & 2 Ferrules

Repair Leaking Hoses In Minutes



COMMON PROBLEM:
Leaking hose at collar

PROBLEM SOLVED:
With new
Power Steering Hose

Easy Installation



1 Cut Tubing






2 Push hose onto line

3 Tighten with wrenches

KIT CONTENTS



■ Indicates quantity included in PS1000 Power Steering Hose Repair Kit

Power Steering Hose

IMAGE	PART#	KITS/ QTY	LINE SIZE	DESCRIPTION	REORDER QTY
	PS16	1	3/8" or 5/16"*	3/8" x 6" Power Steering Hose	1/pkg
	PS112	1	3/8" or 5/16"*	3/8" x 12" Power Steering Hose	1/pkg
	PS118	1	3/8" or 5/16"*	3/8" x 18" Power Steering Hose	1/pkg
	PS124	1	3/8" or 5/16"*	3/8" x 24" Power Steering Hose	1/pkg
	PS130	1	3/8" or 5/16"*	3/8" x 30" Power Steering Hose	1/pkg

* Lines include 3/8" ferrules which can be replaced with interchangeable 5/16" ferrules (sold separately)

Compression Union Ferrule

IMAGE	PART#	KITS/ QTY	LINE SIZE	DESCRIPTION	REORDER QTY
	PS810	2	5/16"	5/16" Compression Union Ferrule	2/pkg
	PS820	2	3/8"	3/8" Compression Union Ferrule	2/pkg