

PS1000M

10mm Power Steering Hose Repair Kit

S.U.R.&R. EXCLUSIVE



Double Braided Hose Pressure: Rated up to 6,000 PSI



- Working Pressure 1,500 PSI, Burst Pressure 6,000 PSI
- Temperature Range (-40° F to +250° F, -40° C to +121° C)
- Exceeds SAE J188 Type 1 Specifications


Repair High And Low Pressure Power Steering Lines

- Use to make 8mm and 10mm line repairs
- On-the-car repairs made easy
- 95% coverage of metric power steering lines
- Universal can be used to repair hundreds of different line types
- Use for power steering lines, clutch, industrial and heavy duty applications
- Includes 6", 12", 18", 24" and 30" lines –
 Qty 1 of each
- Compression end stamped for easy size identification



Heavy-duty compression connections that feature "double-seal" technology with o-ring and interchangeable ferrule

Repair Leaking Hoses In Minutes



COMMON PROBLEM: Leaking hose at collar PROBLEM SOLVED: With new Power Steering Hose

5 Hoses & 2 Ferrules

Easy Installation



Cut Tubing

Push hose onto line

Tighten with wrenches

KIT CONTENTS

Power Steering Hose

IMAGE	PART#	KITS/ QTY	LINE SIZE	DESCRIPTION	REORDER QTY
	PS16M	1	10mm or 8mm*	10mm x 6" Power Steering Hose	1/pkg
	PS112M	1	10mm or 8mm*	10mm x 12" Power Steering Hose	1/pkg
	PS118M	1	10mm or 8mm*	10mm x 18" Power Steering Hose	1/pkg
	PS124M	1	10mm or 8mm*	10mm x 24" Power Steering Hose	1/pkg
	PS130M	1	10mm or 8mm*	10mm x 30" Power Steering Hose	1/pkg

^{*} Lines include 10mm ferrules which can be replaced with interchangeable 8mm ferrules (sold separately)

Compression Union Ferrule

IMAGE	PART#	KITS/ QTY	LINE SIZE	DESCRIPTION	REORDER QTY
	PS810M	2	8mm	8mm Compression Union Ferrule	2/pkg
	PS820M	2	10mm	10mm Compression Union Ferrule	2/pkg