

54768

51768

13-15 NISSAN
ALTIMA SEDAN



54768

51768

13-15 NISSAN
ALTIMA SEDAN

NISSAN ALTIMA

Main Grille

Install time: 35 Mins.

TOOLS REQUIRED:

Flat Screwdriver
Screwdriver
1/8 Drillbit+Drill
Socket Wrench

PARTS LIST:

(1) Grille
(4) L-Brackets
(4) Fender Flatwashers
(8) 6/32 Nylon Lock Nuts

PLEASE READ AND UNDERSTAND ALL INSTRUCTIONS
BEFORE ATTEMPTING INSTALLATION.

Step 1 Grille Installation

- Remove 8 Clips across the top of the Plastic Cover and remove. (Fig. 1)
 - Remove 2 More Clips to Remove the Plastic. (Fig. 2)
 - Place the Mesh Grille over the Factory Grille and Mark where the Top Threaded Studs that are on the Mesh Grille are. (Fig. 3)
 - With a 1/8 Drillbit, Drill where you marked the Threaded Studs were. (Fig. 4)
 - Place back the Mesh Grille.
 - Place a Fender Flatwasher and Nylon Lock Nut along the top Threaded Studs on the Mesh Grille. (Fig. 5)
 - Place an L-Bracket along the Bottom Threaded Studs on the Mesh Grille so it Latches onto the Factory Grille. (Fig. 6)
- Repeat for remaining Studs.

INSTALLATION COMPLETE

