

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Revision date: 02/10/2017 Supersedes: 09/04/2015 Version: 1.2

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product form : Mixture

Trade name : BLUE MAGIC NON-FLAMMABLE FLAT FIXER 12 OZ.

Product code : 975

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture : Flat Fix

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

GHS-US classification

Compressed gas H280 Eye Irrit. 2B H320

Full text of H statements : see section 16

2.2. Label elements

GHS-US labeling

Hazard pictograms (GHS-US)



GHS04

Signal word (GHS-US) : Warning

Hazard statements (GHS-US) : H280 - Contains gas under pressure; may explode if heated

H320 - Causes eye irritation

Precautionary statements (GHS-US) : P264 - Wash affected areas thoroughly after handling

P305+P351+P338 - If in eyes: Rinse cautiously with water for several minutes. Remove contact

lenses, if present and easy to do. Continue rinsing

P337+P313 - If eye irritation persists: Get medical advice/attention P410+P403 - Protect from sunlight. Store in a well-ventilated place

2.3. Other hazards

Other hazards not contributing to the

classification

: Contains gas under pressure; may explode if heated. None under normal conditions.

2.4. Unknown acute toxicity (GHS US)

No data available

SECTION 3: Composition/Information on ingredients

3.1. Substance

Not applicable

3.2. Mixture

Name	Product identifier	%	GHS-US classification
Water	(CAS No) 7732-18-5	30 - 50	Not classified
1,1,1,2-Tetrafluoroethane	(CAS No) 811-97-2	10 - 30	Liquefied gas, H280
Polymer Latex	(CAS No) Proprietary	10 - 30	Eye Irrit. 2B, H320
1,1-Difluoroethane, Liquefied, Under Pressure	(CAS No) 75-37-6	1 - 5	Liquefied gas, H280
Ethanol	(CAS No) 64-17-5	2.7625 - 2.925	Flam. Liq. 2, H225
2-Propanol	(CAS No) 67-63-0	1 - 5	Flam. Liq. 2, H225 Eye Irrit. 2A, H319 STOT SE 3, H336

10/02/2017 EN (English US) 1/12

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Name	Product identifier	%	GHS-US classification
2-Aminoethanol	(CAS No) 141-43-5	<= 0.6908	Acute Tox. 4 (Oral), H302 Acute Tox. 4 (Dermal), H312 Acute Tox. 4 (Inhalation), H332 Skin Corr. 1A, H314
Methanol	(CAS No) 67-56-1	0 - 0.1625	Flam. Liq. 2, H225 Acute Tox. 3 (Oral), H301 Acute Tox. 3 (Dermal), H311 Acute Tox. 3 (Inhalation:dust,mist), H331 STOT SE 1, H370
Ammonium Hydroxide, Aqueous Solution, Conc=25%	(CAS No) 1336-21-6	< 1	Skin Corr. 1B, H314 Aquatic Acute 1, H400
Methyl Isobutyl Ketone	(CAS No) 108-10-1	0 - 0.0325	Flam. Liq. 2, H225 Acute Tox. 3 (Inhalation:gas), H331 Eye Irrit. 2A, H319 STOT SE 3, H335
Proprietary Inhibitor Package	(CAS No) Proprietary	<= 0.0144	Not classified

The exact percentage is a trade secret.

SECTION 4: First aid measures

4.1. Description of first aid measures

First-aid measures general : Never give anything by mouth to an unconscious person. If you feel unwell, seek medical

advice (show the label where possible).

First-aid measures after inhalation : Allow victim to breathe fresh air. Allow the victim to rest.

First-aid measures after skin contact : Remove affected clothing and wash all exposed skin area with mild soap and water, followed

by warm water rinse.

First-aid measures after eye contact : IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present

and easy to do. Continue rinsing.

First-aid measures after ingestion : Rinse mouth. Do NOT induce vomiting. Obtain emergency medical attention.

4.2. Most important symptoms and effects, both acute and delayed

Symptoms/injuries : If you feel unwell, seek medical advice.

Symptoms/injuries after skin contact : Frostbites. Itching. May cause slight irritation . Red skin. Skin rash/inflammation.

Symptoms/injuries after eye contact : Inflammation/damage of the eye tissue. Irritation of the eye tissue. Redness of the eye tissue.

Causes eye irritation.

Symptoms/injuries after ingestion : May be harmful if swallowed and enters airways. May be fatal if swallowed and enters airways.

4.3. Indication of any immediate medical attention and special treatment needed

No additional information available

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media : Foam. Dry powder. Carbon dioxide. Water spray. Sand.

Unsuitable extinguishing media : Do not use a heavy water stream.

5.2. Special hazards arising from the substance or mixture

No additional information available

5.3. Advice for firefighters

Firefighting instructions : Use water spray or fog for cooling exposed containers. Exercise caution when fighting any

chemical fire. Prevent fire-fighting water from entering environment.

Protection during firefighting : Do not enter fire area without proper protective equipment, including respiratory protection.

Other information : NFPA Aerosol Level 1.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General measures : Remove ignition sources.

6.1.1. For non-emergency personnel

Protective equipment : Gloves. Safety glasses.

Emergency procedures : Evacuate unnecessary personnel.

6.1.2. For emergency responders

Protective equipment : Equip cleanup crew with proper protection.

Emergency procedures : Ventilate area.

6.2. Environmental precautions

Prevent entry to sewers and public waters. Notify authorities if liquid enters sewers or public waters.

10/02/2017 EN (English US) 2/12

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

6.3. Methods and material for containment and cleaning up

For containment : Dam up the liquid spill. Contain released substance, pump into suitable containers. Plug the

leak, cut off the supply.

Methods for cleaning up : Store away from other materials.

6.4. Reference to other sections

See Heading 8. Exposure controls and personal protection.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Additional hazards when processed

: Pressurized container: Do not pierce or burn, even after use.

Precautions for safe handling : Wash hands and other exposed areas with mild soap and water before eating, drinking or

smoking and when leaving work. Provide good ventilation in process area to prevent formation

of vapor

Hygiene measures : Do not eat, drink or smoke when using this product. Separate working clothes from town

clothes. Launder separately. Wash contaminated clothing before reuse. Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work. Always wash hands after handling the product. Remove contaminated clothes. Wash

affected areas thoroughly after handling.

7.2. Conditions for safe storage, including any incompatibilities

Technical measures : Proper grounding procedures to avoid static electricity should be followed. Comply with

applicable regulations.

Storage conditions : Keep only in the original container in a cool, well ventilated place away from : Keep container

closed when not in use.

Incompatible products : Strong bases. Strong acids.
Incompatible materials : Sources of ignition. Direct sunlight.
Storage area : Store in a well-ventilated place.

7.3. Specific end use(s)

Follow Label Directions.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

2-Aminoethanol (141-43-5)		
USA ACGIH	ACGIH TWA (ppm)	3 ppm (Ethanolamine; USA; Time-weighted average exposure limit 8 h; TLV - Adopted Value)
USA ACGIH	ACGIH STEL (ppm)	6 ppm (Ethanolamine; USA; Short time value; TLV - Adopted Value)
Ammonium Hydroxide, Aqueous Solution, Conc=25% (1336-21-6)		
USA ACGIH	ACGIH TWA (ppm)	24 ppm
USA ACGIH	ACGIH STEL (ppm)	35 ppm
USA OSHA	OSHA PEL (TWA) (ppm)	50 ppm
2-Propanol (67-63-0)		
USA ACGIH	ACGIH TWA (mg/m³)	980 mg/m³
USA ACGIH	ACGIH TWA (ppm)	400 ppm
USA ACGIH	ACGIH STEL (mg/m³)	1225 mg/m³
USA ACGIH	ACGIH STEL (ppm)	500 ppm
USA OSHA	OSHA PEL (TWA) (mg/m³)	980 mg/m³
USA OSHA	OSHA PEL (TWA) (ppm)	400 ppm
Methanol (67-56-1)		
USA ACGIH	ACGIH TWA (mg/m³)	262 mg/m³
USA ACGIH	ACGIH TWA (ppm)	200 ppm (Methanol; USA; Time-weighted average exposure limit 8 h; TLV - Adopted Value)
USA ACGIH	ACGIH STEL (mg/m³)	328 mg/m³
USA ACGIH	ACGIH STEL (ppm)	250 ppm
USA OSHA	OSHA PEL (TWA) (mg/m³)	260 mg/m³
USA OSHA	OSHA PEL (TWA) (ppm)	200 ppm

10/02/2017 EN (English US) 3/12

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Methyl Isobutyl Ketone (10	3-10-1)	
USA ACGIH	ACGIH TWA (ppm)	20 ppm (Methyl isobutyl ketone; USA; Time-weighted average exposure limit 8 h; TLV - Adopted Value)
USA ACGIH	ACGIH STEL (ppm)	75 ppm (Methyl isobutyl ketone; USA; Short time value; TLV - Adopted Value)

8.2. Exposure controls

Appropriate engineering controls : Local exhaust venilation, vent hoods . Ensure good ventilation of the work station.

Personal protective equipment : Gloves. Safety glasses. Avoid all unnecessary exposure.





Materials for protective clothing : GIVE EXCELLENT RESISTANCE:

Hand protection : Wear protective gloves.

Eye protection : Chemical goggles or safety glasses.

Skin and body protection : Wear suitable protective clothing.

Respiratory protection : Wear appropriate mask.

Environmental exposure controls : Avoid release to the environment.

Consumer exposure controls : Avoid contact during pregnancy/while nursing.

Other information : Do not eat, drink or smoke during use.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state: GasAppearance: Liquid.Color: White.

Odor : Mild ammonia.
Odor threshold : No data available

pH : 9 - 10

Relative evaporation rate (butyl acetate=1) : No data available Melting point : No data available : No data available Freezing point **Boiling point** : No data available : No data available Flash point Auto-ignition temperature No data available Decomposition temperature No data available Flammability (solid, gas) : No data available Vapor pressure : No data available Relative vapor density at 20 °C No data available

Relative density : 0.99 - 1

Solubility : Soluble in water.
Log Pow : No data available
Log Kow : No data available
Viscosity, kinematic : No data available
Viscosity, dynamic : No data available

Explosive properties : Heating may cause an explosion.

Oxidizing properties : No data available Explosion limits : No data available

9.2. Other information

VOC content : 5.1 %

Gas group : Compressed gas

SECTION 10: Stability and reactivity

10.1. Reactivity

No additional information available

10.2. Chemical stability

Not established.

10/02/2017 EN (English US) 4/12

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Not established.

exposure)

symptoms

Aspiration hazard

Potential Adverse human health effects and

Symptoms/injuries after skin contact

Symptoms/injuries after eye contact

Symptoms/injuries after ingestion

10.4. Conditions to avoid

Direct sunlight. Extremely high or low temperatures.

10.5. Incompatible materials

Strong acids. Strong bases.

10.6. Hazardous decomposition products

Toxic fume. . Carbon monoxide. Carbon dioxide.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity : Not classified

Acute toxicity	: Not classified	
2-Aminoethanol (141-43-5)		
LD50 oral rat	1720 mg/kg (Rat)	
LD50 dermal rabbit	1018 mg/kg (Rabbit)	
2-Propanol (67-63-0)		
LD50 dermal rabbit	12870 mg/kg (Rabbit; Experimental value; Equivalent or similar to OECD 402; 16.4; Rabbit)	
LC50 inhalation rat (mg/l)	73 mg/l/4h (Rat)	
1,1-Difluoroethane, Liquefied, Under Pressure (75-37-6)		
LC50 inhalation rat (mg/l)	176 mg/l/4h (Rat; Literature study)	
LC50 inhalation rat (ppm)	> 437500 ppm/4h Mortality in 2/6 at 43.75% and 1/6 at 38.3%. At ≥ 17.52% lethargy, laboured breathing, reduced responsiveness to sound were observed. At 6.64% only hyperaemia and shallow breathing were observed.	
1,1,1,2-Tetrafluoroethane (811-97-2)		
LC50 inhalation rat (mg/l)	> 2000 mg/l/4h (Rat; Literature study)	
LC50 inhalation rat (ppm)	> 359300 ppm/4h (Rat; Literature study)	
Methanol (67-56-1)		
LD50 oral rat	>= 2528 mg/kg body weight application as 50% aqueous solution	
LD50 dermal rabbit	17100 mg/kg corresponding to 20 ml/kg bw according to the authors	
LC50 inhalation rat (mg/l)	128.2 mg/l/4h Air	
Methyl Isobutyl Ketone (108-10-1)		
LD50 oral rat	2080 mg/kg (Rat; Equivalent or similar to OECD 401; Experimental value)	
LD50 dermal rat	>= 2000 mg/kg body weight (Rat; Experimental value; OECD 402: Acute Dermal Toxicity)	
LD50 dermal rabbit	> 16000 mg/kg (Rabbit)	
LC50 inhalation rat (mg/l)	8.2- 16.4,Rat; Experimental value	
LC50 inhalation rat (ppm)	2000 ppm/4h (Rat; Experimental value,Rat; Experimental value)	
Skin corrosion/irritation	: Not classified	
	pH: 9 - 10	
Serious eye damage/irritation	: Causes eye irritation.	
	pH: 9 - 10	
Respiratory or skin sensitization	: Not classified	
Germ cell mutagenicity	: Not classified	
Carcinogenicity	: Not classified	
2-Propanol (67-63-0)		
IARC group	3	
Reproductive toxicity	: Not classified	
Specific target organ toxicity (single exposure)	: Not classified	
Specific target organ toxicity (repeated	: Not classified	

10/02/2017 EN (English US) 5/12

: Based on available data, the classification criteria are not met.

: Frostbites. Itching. May cause slight irritation . Red skin. Skin rash/inflammation.

Inflammation/damage of the eye tissue. Irritation of the eye tissue. Redness of the eye tissue.

: May be harmful if swallowed and enters airways. May be fatal if swallowed and enters airways.

: Not classified

Causes eye irritation.

Safety Data Sheet according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

150 mg/l (LC50; 96 h; Salmo gairdneri)
140 mg/l (EC50; 24 h)
35 mg/l (EC50; 72 h)
9640 mg/l (LC50; OECD 203: Fish, Acute Toxicity Test; 96 h; Pimephales promelas; Flow-through system; Fresh water; Experimental value)
13299 mg/l (EC50; Other; 48 h; Daphnia magna)
> 1000 mg/l Toxicity to fish sludge (96 hours) (Carp)
450 mg/l (LC50; 96 h)
980 mg/l (EC50; 48 h)
300 mg/r (2000; 40 m)
45100 ### OFO FDA 000/0 75/000 001
15400 mg/l (LC50; EPA 660/3 - 75/009; 96 h; Lepomis macrochirus; Flow-through system; Fresh water; Experimental value)
> 10000 mg/l (EC50; DIN 38412-11; 48 h; Daphnia magna; Static system; Fresh water; Experimental value)
10800 mg/l (LC50; 96 h; Salmo gairdneri)
R 12 OZ.
Not established.
Not established.
Not established.
Readily biodegradable in water. Biodegradable in the soil.
0.80 g O ₂ /g substance
1.34 g O ₂ /g substance
2.49 g O ₂ /g substance
0.32
Not established.
Conc=25% (1336-21-6)
Readily biodegradable in water. Biodegradable in the soil. No (test)data on mobility of the components available. Ozonation in the air.
Readily biodegradable in water. Biodegradable in the soil. Biodegradable in the soil under anaerobic conditions. No (test)data on mobility of the substance available.
1.19 g O ₂ /g substance
2.23 g O ₂ /g substance
2.40 g O ₂ /g substance
rre (75-37-6)
Biodegradability in water: no data available.
Diodogradability in water. No data available.
Ned on a 4th bit advantable to conde
Not readily biodegradable in water.
Readily biodegradable in water. Biodegradable in the soil. Highly mobile in soil.
0.6 - 1.12 g O ₂ /g substance
1.42 g O ₂ /g substance
1.5 g O ₂ /g substance
0.8 (Literature study)
Readily biodegradable in water. Biodegradable in the soil. Biodegradable in the soil under anaerobic conditions. Low potential for adsorption in soil. Photolysis in the air. Not established.

EN (English US) 10/02/2017 6/12

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

2.16 g O ₂ /g substance 2.72 g O ₂ /g substance 0.76
2.72 g O ₂ /g substance
0.76
R 12 OZ.
Not established.
Not established.
-1.91
Bioaccumulation: not applicable.
Not established.
Conc=25% (1336-21-6)
Not bioaccumulative.
140t bloaccumulative.
O.O.F. (Mysight of spidous as prography Others O.F. 90)
0.05 (Weight of evidence approach; Other; 25 °C)
Low potential for bioaccumulation (Log Kow < 4).
re (75-37-6)
0.75 (Experimental value)
Low potential for bioaccumulation (Log Kow < 4).
5 - 58 (BCF)
1.06 (OECD 107: Partition Coefficient (n-octanol/water): Shake Flask Method)
Low potential for bioaccumulation (BCF < 500).
< 10 (BCF; 72 h; Leuciscus idus)
-0.77 (Experimental value; Other)
Low potential for bioaccumulation (BCF < 500).
2 - 5 (BCF)
1.9 (Experimental value; OECD 117: Partition Coefficient (n-octanol/water), HPLC method)
Low potential for bioaccumulation (BCF < 500). Not established.
0.050 N/m
0.021 N/m (25 °C)
0.021 14/11 (23 0)
0.000 N/m /00 °C\
0.023 N/m (20 °C)
Koc,PCKOCWIN v1.66; 1; Calculated value
T 0 0 0 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1
0.024 N/m (20 °C)
Koc,101.85; Weight of evidence; Calculated value; log Koc; 2.008; Weight of evidence; Calculated value
: Avoid release to the environment.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

: Dispose of contents/container to appropriate waste disposal facility, in accordance with local, regional, national, international regulations. . Dispose in a safe manner in accordance with Waste disposal recommendations

local/national regulations.

Ecology - waste materials : Avoid release to the environment.

10/02/2017 EN (English US) 7/12

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

SECTION 14: Transport information

In accordance with ADR / RID / IMDG / IATA / ADN

US DOT (ground): UN1950, Aerosols, Non-flammable, 2.2, Limited Quantity ICAO/IATA (air): UN1950, Aerosols, Non-flammable, 2.2, Limited Quantity IMO/IMDG (water): UN1950, Aerosols, Non-flammable, 2.2, Limited Quantity

UN proper shipping name

Proper Shipping Name (DOT) : Aerosols, Non-flammable

Non-flammable, (each not exceeding 1 L capacity)

Class (DOT) : 2.2 - Class 2.2 - Non-flammable compressed gas 49 CFR 173.115

Hazard labels (DOT) : 2.2 - Non-flammable gas



DOT Packaging Exceptions (49 CFR 173.xxx) : 306 DOT Packaging Non Bulk (49 CFR 173.xxx) : None DOT Packaging Bulk (49 CFR 173.xxx) : None

14.3. Additional information

Other information : No supplementary information available.

Overland transport

No additional information available

Transport by sea

DOT Vessel Stowage Location : A - The material may be stowed "on deck" or "under deck" on a cargo vessel and on a

passenger vessel

DOT Vessel Stowage Other 48 - Stow "away from" sources of heat,87 - Stow "separated from" Class 1 (explosives) except

Division 14,126 - Segregation same as for Class 9, miscellaneous hazardous materials

Air transport

DOT Quantity Limitations Passenger aircraft/rail : 75 kg

(49 CFR 173.27)

DOT Quantity Limitations Cargo aircraft only (49 : 150 kg

CFR 175.75)

SECTION 15: Regulatory information

SARA Section 311/312 Hazard Classes

15.1. US Federal regulations		
BLUE MAGIC NON-FLAMMABLE FLAT FIXER 12 OZ.		
SARA Section 311/312 Hazard Classes	Immediate (acute) health hazard Sudden release of pressure hazard	
2-Aminoethanol (141-43-5)		
SARA Section 311/312 Hazard Classes	Immediate (acute) health hazard	
2-Propanol (67-63-0)		
Listed on the United States TSCA (Toxic Substances Control Act) inventory		
SARA Section 311/312 Hazard Classes	Immediate (acute) health hazard Fire hazard	
1,1-Difluoroethane, Liquefied, Under Pressure (75-37-6)		
Listed on the United States TSCA (Toxic Substances Control Act) inventory		
SARA Section 311/312 Hazard Classes	Fire hazard Sudden release of pressure hazard Immediate (acute) health hazard	
1,1,1,2-Tetrafluoroethane (811-97-2)		
Listed on the United States TSCA (Toxic Substances Control Act) inventory		

10/02/2017 EN (English US) 8/12

Sudden release of pressure hazard Immediate (acute) health hazard

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Methanol (67-56-1)	
Subject to reporting requirements of United States SARA Section 313 Listed on the United States TSCA (Toxic Substances Control Act) inventory Listed on the United States SARA Section 302 Listed on the United States SARA Section 355	
SARA Section 311/312 Hazard Classes	Immediate (acute) health hazard Delayed (chronic) health hazard Fire hazard

15.2. International regulations

CANADA

BLUE MAGIC NON-FLAMMABLE FLAT FIXER 12 OZ.		
WHMIS Classification	Class A - Compressed Gas	
2-Propanol (67-63-0)		
Listed on the Canadian DSL (Domestic Substances List)		
WHMIS Classification	Class B Division 2 - Flammable Liquid	
1,1-Difluoroethane, Liquefied, Under Pressure (75-37-6)		
WHMIS Classification	Class A - Compressed Gas Class B Division 5 - Flammable Aerosol	
1,1,1,2-Tetrafluoroethane (811-97-2)		
WHMIS Classification	Class A - Compressed Gas	
Methanol (67-56-1)		
Listed on the Canadian DSL (Domestic Substances List)		
WHMIS Classification	Class B Division 2 - Flammable Liquid Class D Division 1 Subdivision B - Toxic material causing immediate and serious toxic effects Class D Division 2 Subdivision A - Very toxic material causing other toxic effects Class D Division 2 Subdivision B - Toxic material causing other toxic effects	

EU-Regulations

2-Propanol (67-63-0)

Listed on the EEC inventory EINECS (European Inventory of Existing Commercial Chemical Substances)

1,1-Difluoroethane, Liquefied, Under Pressure (75-37-6)

1,1,1,2-Tetrafluoroethane (811-97-2)

Methanol (67-56-1)

Listed on the EEC inventory EINECS (European Inventory of Existing Commercial Chemical Substances)

Classification according to Regulation (EC) No. 1272/2008 [CLP]

Classification according to Directive 67/548/EEC [DSD] or 1999/45/EC [DPD]

F+; R12

Full text of R-phrases: see section 16

15.2.2. National regulations

2-Propanol (67-63-0)

Listed on the AICS (Australian Inventory of Chemical Substances)

Listed on the Japanese ENCS (Existing & New Chemical Substances) inventory

Listed on KECI (Korean Existing Chemicals Inventory)

Listed on PICCS (Philippines Inventory of Chemicals and Chemical Substances)

1,1-Difluoroethane, Liquefied, Under Pressure (75-37-6)

1,1,1,2-Tetrafluoroethane (811-97-2)

Methanol (67-56-1)

Listed on the Canadian IDL (Ingredient Disclosure List)

15.3. US State regulations

BLUE MAGIC NON-FLAMMABLE FLAT FIXER 12 OZ.	
U.S California - Proposition 65 - Carcinogens List	No
U.S California - Proposition 65 - Developmental Toxicity	No
U.S California - Proposition 65 - Reproductive Toxicity - Female	No
U.S California - Proposition 65 - Reproductive	No

10/02/2017 EN (English US) 9/12

Safety Data Sheet according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

BLUE MAGIC NON-FLAMM	MABLE FLAT FIXER 12 OZ.				
Toxicity - Male					
State or local regulations		U.S California - Proposition	nia - Proposition 65		
Water (7732-18-5)	LILO O-life-m-i-	110 0-18	LLO California	Non-significant deleteral	
U.S California - Proposition 65 - Carcinogens List	U.S California - Proposition 65 - Developmental Toxicity	U.S California - Proposition 65 - Reproductive Toxicity - Female	U.S California - Proposition 65 - Reproductive Toxicity - Male	Non-significant risk level (NSRL)	
No	No	No	No		
2-Aminoethanol (141-43-5)					
U.S California - Proposition 65 - Carcinogens List	U.S California - Proposition 65 - Developmental Toxicity	U.S California - Proposition 65 - Reproductive Toxicity - Female	U.S California - Proposition 65 - Reproductive Toxicity - Male	Non-significant risk level (NSRL)	
No	No	No	No		
Proprietary Inhibitor Packa					
U.S California - Proposition 65 - Carcinogens List	U.S California - Proposition 65 - Developmental Toxicity	U.S California - Proposition 65 - Reproductive Toxicity - Female	U.S California - Proposition 65 - Reproductive Toxicity - Male	Non-significant risk level (NSRL)	
No	No	No	No		
	ueous Solution, Conc=25%				
U.S California - Proposition 65 - Carcinogens List	U.S California - Proposition 65 - Developmental Toxicity	U.S California - Proposition 65 - Reproductive Toxicity - Female	U.S California - Proposition 65 - Reproductive Toxicity - Male	Non-significant risk level (NSRL)	
No	No	No	No		
2-Propanol (67-63-0)					
U.S California - Proposition 65 - Carcinogens List	U.S California - Proposition 65 - Developmental Toxicity	U.S California - Proposition 65 - Reproductive Toxicity - Female	U.S California - Proposition 65 - Reproductive Toxicity - Male	Non-significant risk level (NSRL)	
No	No	No	No		
Polymer Latex (Proprietary	y)				
U.S California - Proposition 65 - Carcinogens List	U.S California - Proposition 65 - Developmental Toxicity	U.S California - Proposition 65 - Reproductive Toxicity - Female	U.S California - Proposition 65 - Reproductive Toxicity - Male	Non-significant risk level (NSRL)	
No	No	No	No		
1,1-Difluoroethane, Liquef	ied, Under Pressure (75-37-	-6)			
U.S California - Proposition 65 - Carcinogens List	U.S California - Proposition 65 - Developmental Toxicity	U.S California - Proposition 65 - Reproductive Toxicity - Female	U.S California - Proposition 65 - Reproductive Toxicity - Male	Non-significant risk level (NSRL)	
No	No	No	No		
1,1,1,2-Tetrafluoroethane (811-97-2)				
U.S California - Proposition 65 - Carcinogens List	U.S California - Proposition 65 - Developmental Toxicity	U.S California - Proposition 65 - Reproductive Toxicity - Female	U.S California - Proposition 65 - Reproductive Toxicity - Male	Non-significant risk level (NSRL)	
No	No	No	No		
Methanol (67-56-1)					
U.S California - Proposition 65 -	U.S California - Proposition 65 -	U.S California - Proposition 65 -	U.S California - Proposition 65 -	Non-significant risk level (NSRL)	
Carcinogens List	Developmental Toxicity	Reproductive Toxicity - Female	Reproductive Toxicity - Male		

10/02/2017 EN (English US) 10/12

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Methyl Isobutyl Ketone (108-10-1)						
U.S California - Proposition 65 - Carcinogens List	U.S California - Proposition 65 - Developmental Toxicity	U.S California - Proposition 65 - Reproductive Toxicity - Female	U.S California - Proposition 65 - Reproductive Toxicity - Male	Non-significant risk level (NSRL)		
Yes	No	No	No			

2-Propanol (67-63-0)

State or local regulations

- U.S. New Jersey Right to Know Hazardous Substance List
- U.S. Pennsylvania RTK (Right to Know) Environmental Hazard List

1,1-Difluoroethane, Liquefied, Under Pressure (75-37-6)

State or local regulations

- U.S. New Jersey Right to Know Hazardous Substance List
- U.S. Pennsylvania RTK (Right to Know) List
- U.S. Massachusetts Right To Know List

Methanol (67-56-1)

State or local regulations

U.S. - California - Proposition 65

New Jersey Right-to-Know

Florida Right to Know

U.S. - Massachusetts - Right To Know List

U.S. - Pennsylvania - RTK (Right to Know) List

Methyl Isobutyl Ketone (108-10-1)

State or local regulations

U.S. - California - Proposition 65

SECTION 16: Other information

Other information : None.

Full text of H-phrases:

H225	Highly flammable liquid and vapor
H280	Contains gas under pressure; may explode if heated
H301	Toxic if swallowed
H302	Harmful if swallowed
H311	Toxic in contact with skin
H312	Harmful in contact with skin
H314	Causes severe skin burns and eye damage
H319	Causes serious eye irritation
H320	Causes eye irritation
H331	Toxic if inhaled
H332	Harmful if inhaled
H335	May cause respiratory irritation
H336	May cause drowsiness or dizziness
H370	Causes damage to organs
H400	Very toxic to aquatic life


NFPA health hazard : 1 - Exposure could cause irritation but only minor residual

injury even if no treatment is given.

NFPA fire hazard : 1 - Must be preheated before ignition can occur.

NFPA reactivity : 0 - Normally stable, even under fire exposure conditions,

and are not reactive with water.



HMIS III Rating

Health : 1 Slight Hazard - Irritation or minor reversible injury possible

Flammability : 1 Slight Hazard Physical : 1 Slight Hazard

Personal Protection : B

SDS US (GHS HazCom 2012) - TCC

10/02/2017 EN (English US) 11/12

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

The Supplier identified in Section 1 of this SDS has evaluated this product and certifies it to be labeled and packaged in compliance with the applicable provisions of the Federal Hazardous Substance Act as stated in 16 CFR 1500 and enforced by the Consumer Product Safety Commission, and where applicable the products that require Child Resistant Closures are packaged in accordance with the Poison Prevention Packaging Act as stated in 16 CFR 1700 and enforced by the Consumer Product Safety Commission. All closures have been tested in accordance with the latest protocols. No other testing is required to certify compliance with the above. The date of manufacture is stamped on the product

Disclaimer: The information and recommendations contained herein are based upon tests believed to be reliable. However, the manufacturer/distributor of this product does not guarantee their accuracy or completeness NOR SHALL ANY OF THIS INFORMATION CONSTITUTE A WARRANTY, WHETHER EXPRESSED OR IMPLIED, AS TO THE SAFETY OF THE GOODS, THE MERCHANTABILITY OF THE GOODS, OR THE FITNESS OF THE GOODS FOR A PARTICULAR PURPOSE. Adjustment to conform to actual conditions of usage may be required. The manufacturer/distributor assumes no responsibility for results obtained or for incidental or consequential damages, including lost profits, arising from the use of these data. No warranty against infringement of any patent, copyright or trademark is made or implied.

10/02/2017 EN (English US) 12/12