

# TEPRAFLEX

## INSTALLATION GUIDE

### Installation Guide for the YJ Wrangler Front Swaybar Quick Disconnects Kit

Part #001733400

for 2.5-4" lift (QDFYL)

Part #001733200

for 0-2.5" lift (QDFYS)



QDFY components for YJs with 2.5 to 4.0 inches of lift

Part No.	Description	Units
QD132-Y11	Disconnect Arm Assembly	2
QD4-Y	Upper Stud, Stainless	2
QD4-YL	Lower Stud, Stainless	2
QD4-YLS	Spacer for Lower Stud	2
QD9	Hitch Pin, Stainless	4
WASHER1/2L	Lock Washer, 1/2" Stainless	2
WASHERF3/4	Flat Washer, 3/4" x 1.5" Zinc	4

This product should be disconnected prior to off-roading. When disconnected, please store the disconnect arms, washers, hitch pins, and spacers in a secure place until the time they are reconnected.

Please check all components prior to beginning installation.

1. Remove the stock sway bar links.
2. Locate the lower stainless steel mounting stud. The lower stud has four holes in the rounded end and has a threaded center.
3. Check the threads where the sway bar links originally connected. Be sure that the threads are in good condition prior to attempting to attach the stud to the mount.
4. Install the lower stud over the threaded mount.
5. Tighten the stud securely.  
**Note: It is highly recommended to use loctite on the stud.**
6. Position the upper stainless stud so that the threaded portion goes through the end of the sway bar and points to the inside of the vehicle. The rounded portion of the stud should point to the outside of the vehicle.

7. Fasten the upper stud to the sway bar using the 1/2" nut and lock washer included with the kit.  
**Hint: A hitch pin inserted into the end of the stud will make it easier to secure the stud while properly tightening the nut.**

8. Place the metal spacer on the lower stud before attaching the disconnect arm assembly.
9. Connect the arm to the upper and lower studs.

**Note: Be sure that the grease zerks on the lower end of the disconnect point to the rear of the vehicle. The eyelets of the quick disconnect arms are slightly offset. The lower portion of the disconnect arm should be nearer the outside edge of the vehicle.**

10. Secure arms in place using the 3/4" flat washers and hitch pins.

# **TERAFLEX** **PRODUCT INFORMATION**

## **MAINTENANCE INFORMATION:**

It is the buyer's responsibility to have all suspension, drivetrain, steering, and other components checked for proper tightness and torque after the first 100 miles and every 3000 miles after that.

## **NOTICE TO INSTALLER:**

The enclosed "Warning to Driver" sticker must be installed in the vehicle in driver's view. This sticker is to act as a constant safety reminder when operating the vehicle. It is your responsibility as the equipment installer to install the provided sticker and to forward the product instructions to the vehicle's owner for review. If a "Warning to Driver" sticker or product installation guide were not included in the kit, FREE replacement stickers and instructions are available by request. It is the installer's duty to ensure a safe and controllable vehicle after the modifications have been performed.

## **WARNING:**

Neither the seller nor the manufacturer will be liable for any loss, damage, or injury directly or indirectly arising from the use of or inability to determine the use of these products. Before using, the user shall determine the suitability of the products for its intended use, and the user shall assume all responsibility and risk in connection therewith.

## **WARNING TO DRIVER:**

This vehicle has been modified to enhance off road performance and has unique handling characteristics. Use in harsh environments can cause extreme stress on the components. Vehicle should be inspected after being off road to make sure that all the components are in working order and safe to travel on the highway. All fasteners should be checked so that they are at the correct torque specifications as the vibration and stresses from off roading may cause critical fasteners to work loose. Extra care should be taken to inspect the critical components, steering, and brake systems. During each oil change components such as arms, tie rod ends, etc should be greased and checked for excessive wear. Any worn components should be replaced. When returning to the pavement always set or restore tire air pressure to the factory recommendation and connect or engage any disabled sway bar mechanisms. Because of the higher center of gravity and larger tires, this vehicle handles and reacts differently than many passenger cars, both on and off road. You must drive it safely! Extreme care should be taken to prevent vehicle rollover or loss of control, which can result in serious injury or death. Avoid sudden sharp turns or abrupt maneuvers. Generally, braking performance and capabilities are decreased when significantly larger/heavier tires are used, especially when used in combination with transfer case low-range reduction kits. Take this into consideration while driving. Do not add, alter or fabricate any factory or aftermarket parts to increase vehicle height over the intended height of the TeraFlex product purchased. Mixing component brand is not recommended. TeraFlex Inc. will not be responsible for any altered product or any improper installation or use of our products. We will be happy to answer any questions concerning the design, function, and correct use of our products. It is ultimately the buyer's responsibility to have all bolts/nuts checked for tightness after the first 100 miles and then every 3000 miles. Wheel alignment, steering system, suspension and drive line systems must be inspected by a qualified professional mechanic at least every 3000 miles.